

1 15A NCAC 02D .1101 is proposed for readoption without changes as follows:

2

3

**SECTION .1100 - CONTROL OF TOXIC AIR POLLUTANTS**

4

**15A NCAC 02D .1101 PURPOSE**

6 This Section sets forth the rules for the control of toxic air pollutants to protect human health.

7

8 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107(a)(1),(3),(4),(5); 143B-282; S.L. 1989, c. 168, s. 45;

9

*Eff. May 1, ~~1990~~ 1990;*

10

*Readopted Eff.*

11

12

13

14

1 15A NCAC 02D .1102 is proposed for readoption without substantive changes as follows:

2

3 **15A NCAC 02D .1102 APPLICABILITY**

4 (a) ~~The toxic air pollutant rules in this Section~~15A NCAC 02D .1103 through .1108 apply to all facilities that emit a  
5 toxic air pollutant that are required to have a permit ~~under~~ pursuant to 15A NCAC 2002Q .0700. All other rules in  
6 this Section apply as specified therein.

7 (b) Sources at facilities subject to this Section shall comply with the requirements of this Section as well as with any  
8 applicable requirements in ~~Sections~~15A NCAC 02D .0500, .0900, and .1200 ~~of this Subchapter.~~ with such exceptions  
9 as may be allowed pursuant to 15A NCAC 02Q .0700.

10

11 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107(a)(1),(3),(4),(5); 143B-282; S.L. 1989, c. 168, s. 45;

12 Eff. May 1, 1990;

13 Amended Eff. July 1, 1998; December 1, ~~1991~~.1991;

14 Readopted Eff. \_\_\_\_\_.

15

16

17

18

1 15A NCAC 02D .1103 is proposed for reoption without substantive changes as follows:

2  
3 **15A NCAC 02D .1103 DEFINITION**

4 For the purpose of this Section, the following definitions apply:

- 5 (1) "Asbestos" means asbestos fibers as defined in 40 CFR 61.141.
- 6 (2) "Bioavailable chromate pigments" means the group of chromium (VI) compounds consisting of  
7 calcium chromate (CAS No.13765-19-0), calcium dichromate (CAS No. 14307-33-6), strontium  
8 chromate (CAS No. 7789-06-2), strontium dichromate (CAS No. 7789-06-2), zinc chromate (CAS  
9 No. 13530-65-9), and zinc dichromate (CAS No. 7789-12-0).
- 10 (3) "CAS Number" means the Chemical Abstract Service registry number identifying a particular  
11 substance.
- 12 (4) "Chromium (VI) equivalent" means the molecular weight ratio of the chromium (VI) portion of a  
13 compound to the total molecular weight of the compound multiplied by the associated compound  
14 emission rate or concentration at the facility.
- 15 (5) "Non-specific chromium (VI) compounds" means the group of compounds consisting of any  
16 chromium (VI) compounds not specified in this Section as a bioavailable chromate pigment or a  
17 soluble chromate compound.
- 18 (6) "Cresol" means o-cresol, p-cresol, m-cresol or any combination of these compounds.
- 19 (7) "GACT" means any generally available control technology emission standard applied to an area  
20 source or facility pursuant to Section 112 of the federal Clean Air Act.
- 21 (8) "Hexane isomers except n-hexane" means 2-methyl pentane, 3-methyl pentane, 2,2-dimethyl  
22 butane, 2,3-dimethyl butane, or any combination of these compounds.
- 23 (9) "MACT" means any maximum achievable control technology emission standard applied to a source  
24 or facility pursuant to Section 112 of the federal Clean Air Act.
- 25 (10) "Nickel, soluble compounds" means the soluble nickel salts of chloride (NiCl<sub>2</sub>, CAS No. 7718-54-  
26 9), sulfate (NiSO<sub>4</sub>, CAS No. 7786-81-4), and nitrate (Ni(NO<sub>3</sub>)<sub>2</sub>, CAS No. 13138-45-9).
- 27 (11) "Polychlorinated biphenyls" means any chlorinated biphenyl compound or mixture of chlorinated  
28 biphenyl compounds.
- 29 (12) "Soluble chromate compounds" means the group of chromium (VI) compounds consisting of  
30 ammonium chromate (CAS No. 7788-98-9), ammonium dichromate (CAS No. 7789-09-5), chromic  
31 acid (CAS No. 7738-94-5), potassium chromate (CAS No. 7789-00-6), potassium dichromate (CAS  
32 No. 7778-50-9), sodium chromate (CAS No. 7775-11-3), and sodium dichromate (CAS No. 10588-  
33 01-9).
- 34 (13) "Toxic air pollutant" means any of those carcinogens, chronic toxicants, acute systemic toxicants,  
35 or acute irritants listed in ~~Rule .1104 of this Section.~~ 15A NCAC 02D .1104.
- 36

37 *History Note: Authority G.S. 143-213; 143-215.3(a)(1); 143B-282; S.L. 1989, c. 168, s. 45;*

1  
2  
3  
4  
5

*Eff. May 1, 1990;*  
*Amended Eff. April 1, 2001; July 1, ~~1998~~ 1998;*  
*Readopted Eff. \_\_\_\_\_.*

1 15A NCAC 02D .1104 is proposed for readoption with substantive changes as follows:

2

3 **15A NCAC 02D .1104 TOXIC AIR POLLUTANT GUIDELINES**

4 A facility shall not emit any of the following toxic air pollutants in such quantities that may cause or contribute beyond  
 5 the facility's premises (~~adjacent property boundary~~) to any significant ambient air concentration that may adversely  
 6 affect human ~~health~~, health with such exceptions as may be allowed pursuant to 15A NCAC 2Q .0700. In determining  
 7 these significant ambient air concentrations, the Division shall be guided by the following list of acceptable ambient  
 8 levels in milligrams per cubic meter at 77° F (25° C) and 29.92 inches (760 mm) of mercury pressure (except for  
 9 asbestos):

10

<u>Acceptable Ambient Levels (AAL) in Milligrams per Cubic Meter (mg/m<sup>3</sup>) Except Where Noted</u>				
Pollutant (CAS Number)	Annual (Carcinogens)	24-hour (Chronic Toxicants)	1-hour (Acute Systemic Toxicants)	1-hour (Acute Irritants)
acetaldehyde (75-07-0)				.27
acetic acid (64-19-7)				3.7
acrolein (107-02-8)				0.08
acrylonitrile (107-13-1)		0.03	.1	
ammonia (7664-41-7)				2.7
aniline (62-53-3)			.1	
arsenic and inorganic arsenic compounds	2.1 x 10 <sup>-6</sup>			
asbestos (1332-21-4)	2.8 x 10 <sup>-6</sup> fibers/ml			
aziridine (151-56-4)		0.006		
benzene (71-43-2)	1.2 x 10 <sup>-4</sup>			
benzidine and salts (92-87-5)	1.5 x 10 <sup>-8</sup>			
benzo(a)pyrene (50-32-8)	3.3 x 10 <sup>-5</sup>			
benzyl chloride (100-44-7)			0.5	
beryllium (7440-41-7)	4.1 x 10 <sup>-6</sup>			
beryllium chloride (7787-47-5)	4.1 x 10 <sup>-6</sup>			
beryllium fluoride (7787-49-7)	4.1 x 10 <sup>-6</sup>			
beryllium nitrate (13597-99-4)	4.1 x 10 <sup>-6</sup>			

<u>Acceptable Ambient Levels (AAL) in Milligrams per Cubic Meter (mg/m<sup>3</sup>) Except Where Noted</u>				
Pollutant (CAS Number)	Annual (Carcinogens)	24-hour (Chronic Toxicants)	1-hour (Acute Systemic Toxicants)	1-hour (Acute Irritants)
bioavailable chromate pigments, as chromium (VI) equivalent	.8.3 x 10 <sup>-8</sup>			
bis-chloromethyl ether (542-88-1)	3.7 x 10 <sup>-7</sup>			
bromine (7726-95-6)				.0.2
1,3-butadiene (106-99-0)	4.4 x 10 <sup>-4</sup>			
cadmium (7440-43-9)	5.5 x 10 <sup>-6</sup>			
cadmium acetate (543-90-8)	5.5 x 10 <sup>-6</sup>			
cadmium bromide (7789-42-6)	5.5 x 10 <sup>-6</sup>			
carbon disulfide (75-15-0)		0.186		
carbon tetrachloride (56-23-5)	.6.7 x 10 <sup>-3</sup>			
chlorine (7782-50-5)		0.0375		.0.9
chlorobenzene (108-90-7)		2.2		
chloroform (67-66-3)	4.3 x 10 <sup>-3</sup>			
chloroprene (126-99-8)		0.44	3.5	
cresol (1319-77-3)			2.2	
p-dichlorobenzene (106-46-7)				.66
<del>dichlorodifluoromethane (75-71-8)</del>		248		
<del>dichlorofluoromethane (75-43-4)</del>		0.5		
di(2-ethylhexyl)phthalate (117-81-7)		0.03		
dimethyl sulfate (77-78-1)		0.003		
1,4-dioxane (123-91-1)		0.56		
epichlorohydrin (106-89-8)	8.3 x 10 <sup>-2</sup>			
ethyl acetate (141-78-6)			.140	
ethylenediamine (107-15-3)		0.3	2.5	
ethylene dibromide (106-93-4)	4.0 x 10 <sup>-4</sup>			
ethylene dichloride (107-06-2)	3.8 x 10 <sup>-3</sup>			
ethylene glycol monoethyl ether (110-80-5)		0.12	.1.9	
ethylene oxide (75-21-8)	.2.7 x 10 <sup>-5</sup>			
ethyl mercaptan (75-08-1)			.0.1	

<u>Acceptable Ambient Levels (AAL) in Milligrams per Cubic Meter (mg/m<sup>3</sup>) Except Where Noted</u>				
Pollutant (CAS Number)	Annual (Carcinogens)	24-hour (Chronic Toxicants)	1-hour (Acute Systemic Toxicants)	1-hour (Acute Irritants)
fluorides		.0016	.025	
formaldehyde (50-00-0)				.015
hexachlorocyclopentadiene (77-47-4)		.00006	.001	
hexachlorodibenzo-p-dioxin (57653-85-7)	$7.6 \times 10^{-8}$			
n-hexane (110-54-3)		.11		
hexane isomers except n-hexane				.360
hydrazine (302-01-2)		.00006		
hydrogen chloride (7647-01-0)				.07
hydrogen cyanide (74-90-8)		.014	.11	
hydrogen fluoride (7664-39-3)		.003		.025
hydrogen sulfide (7783-06-4)		.012		
maleic anhydride (108-31-6)		.0012	.01	
manganese and compounds		.0031		
manganese cyclopentadienyl tricarbonyl (12079-65-1)		.00006		
manganese tetroxide (1317-35-7)		.00062		
mercury, alkyl		.000006		
mercury, aryl and inorganic compounds		.00006		
mercury, vapor (7439-97-6)		.00006		
methyl chloroform (71-55-6)		.12		.245
methylene chloride (75-09-2)	$2.4 \times 10^{-2}$		.17	
methyl ethyl ketone (78-93-3)		3.7		.88.5
methyl isobutyl ketone (108-10-1)		2.56		.30
methyl mercaptan (74-93-1)			.005	
nickel carbonyl (13463-39-3)		.00006		
nickel metal (7440-02-0)		.0006		
nickel, soluble compounds, as nickel		.00006		
nickel subsulfide (12035-72-2)	$2.1 \times 10^{-6}$			

<u>Acceptable Ambient Levels (AAL) in Milligrams per Cubic Meter (mg/m<sup>3</sup>) Except Where Noted</u>				
Pollutant (CAS Number)	Annual (Carcinogens)	24-hour (Chronic Toxicants)	1-hour (Acute Systemic Toxicants)	1-hour (Acute Irritants)
nitric acid (7697-37-2)				.1
nitrobenzene (98-95-3)		.006	.05	
n-nitrosodimethylamine (62-75-9)	.50 x 10 <sup>-5</sup>			
non-specific chromium (VI) compounds, as chromium (VI) equivalent	.83 x 10 <sup>-8</sup>			
pentachlorophenol (87-86-5)		0.003	0.025	
perchloroethylene (127-18-4)	.19 x 10 <sup>-1</sup>			
phenol (108-95-2)			0.95	
phosgene (75-44-5)		0.0025		
phosphine (7803-51-2)				.013
polychlorinated biphenyls (1336-36-3)	.83 x 10 <sup>-5</sup>			
soluble chromate compounds, as chromium (VI) equivalent		6.2 x 10 <sup>-4</sup>		
styrene (100-42-5)			.106	
sulfuric acid (7664-93-9)		0.012	.01	
tetrachlorodibenzo-p-dioxin (1746-01-6)	.30 x 10 <sup>-9</sup>			
<del>1,1,1,2-tetrachloro-2,2-</del> <del>difluoroethane (76-11-9)</del>		<del>52</del>		
<del>1,1,2,2-tetrachloro-1,2-</del> <del>difluoroethane (76-12-0)</del>		<del>52</del>		
1,1,2,2-tetrachloroethane (79-34-5)	.63 x 10 <sup>-3</sup>			
toluene (108-88-3)		4.7		.56
toluene diisocyanate, 2,4- (584-84-9) and 2,6- (91-08-7) isomers		0.0002		
trichloroethylene (79-01-6)	.59 x 10 <sup>-2</sup>			
<del>trichlorofluoromethane (75-69-4)</del>			<del>.560</del>	



<u>Acceptable Ambient Levels (AAL) in Milligrams per Cubic Meter (mg/m<sup>3</sup>) Except Where Noted</u>				
Pollutant (CAS Number)	Annual (Carcinogens)	24-hour (Chronic Toxicants)	1-hour (Acute Systemic Toxicants)	1-hour (Acute Irritants)
<del>1,1,2 trichloro 1,2,2-trifluoroethane (76-13-1)</del>				<del>.950</del>
vinyl chloride (75-01-4)	.38 x 10 <sup>-4</sup>			
vinylidene chloride (75-35-4)		.012		
xylene (1330-20-7)		2.7		.65

1  
2  
3  
4  
5  
6  
7  
8  
9  
10

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3),(4),(5); 143B-282;*  
*Eff. May 1, 1990;*  
*Amended Eff. September 1, 1992; March 1, 1992;*  
*Temporary Amendment Eff. July 20, 1997;*  
*Amended Eff. July 7, 2014; May 1, 2014; March 1, 2010; June 1, 2008; April 1, 2005; April 1, 2001;*  
*July 1, ~~1998-1998~~;*  
*Readopted Eff. \_\_\_\_\_.*

1 15A NCAC 02D .1105 is proposed for readoption without substantive changes as follows:

2

3 **15A NCAC 02D .1105 FACILITY REPORTING, RECORDKEEPING**

4 The Director may require, according to ~~Section .0600 of this Subchapter,~~ 15A NCAC 02D .0600, the owner or operator  
5 of a source subject to this Section to monitor emissions of toxic air pollutants, to maintain records of these emissions,  
6 and to report these emissions. The owner or operator of any toxic air pollutant emission source subject to the  
7 requirements of this Section shall comply with the monitoring, recordkeeping, and reporting requirements in ~~Section~~  
8 ~~.0600 of this Subchapter.~~ 15A NCAC 02D .0600.

9

10 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107(a)(4),(5); 143B-282;

11 *Eff. May 1, 1990;*

12 *Amended Eff. April 1, 1999; October 1, ~~1991.~~ 1991;*

13 *Readopted Eff. \_\_\_\_\_.*

14

15

16

17

1 15A NCAC 02D .1106 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02D .1106 DETERMINATION OF AMBIENT AIR CONCENTRATION**

4 (a) Modeling shall not be used for enforcement. Modeling shall be used to determine process operational and air  
5 pollution control parameters and emission rates for toxic air pollutants to place in the air quality permit for that facility  
6 that will prevent any of the acceptable ambient levels in ~~Rule .1104 of this Section~~ 15A NCAC 02D .1104 from being  
7 exceeded, with such exceptions as may be allowed ~~under pursuant to~~ 15A NCAC 2Q .0700. Enforcing these permit  
8 stipulations and conditions shall be the mechanism used to ensure that the requirements of ~~Rule .1104 of this Section,~~  
9 15A NCAC 02D .1104, with such exceptions as may be allowed by 15A NCAC 2Q .0700, are met.

10 (b) The owner or operator of the facility may provide a modeling analysis or may request the Division to perform a  
11 modeling analysis of the facility or provide the analysis himself. If the owner or operator of the facility  
12 requests the Division to perform the modeling analysis, ~~he the owner or operator~~ shall provide emissions rates, stack  
13 parameters, and other information that the Division needs to ~~do~~ conduct the modeling. The data that the owner or  
14 operator of the facility provides the Division to use in the model or in deriving the data used in the model shall be the  
15 process, operational and air pollution control equipment parameters and emission rates that will be contained in the  
16 ~~facility=s~~ facility's permit. If the ~~Division=s~~ Division's initial review of the modeling request indicates extensive or  
17 inappropriate use of state ~~resources~~ resources, or if the ~~Division=s~~ Division's modeling analysis fails to show  
18 compliance with the acceptable ambient levels in ~~Rule .1104 of this Section,~~ 15A NCAC 02D .1104, the modeling  
19 demonstration becomes the responsibility of the owner or operator of the facility.

20 (c) When the owner or operator of the facility is responsible for providing the modeling demonstration and the data  
21 used in the modeling, the owner or operator of the facility shall use in the model or in deriving data used in the model  
22 the process operational and air pollution control equipment parameters and emission rates that will be contained in his  
23 permit. Sources that are not required to be included in the model ~~will~~ shall not be included in the permit to emit toxic  
24 air pollutants.

25 (d) For the following pollutants, modeled emission rates shall be based on the highest emissions occurring in any  
26 single 15 minute period. The resultant modeled 1-hour concentrations shall then be compared to the applicable 1-  
27 hour acceptable ambient levels to determine compliance. These pollutants are:

- 28 (1) acetaldehyde ~~(75-07-0)~~ (75-07-0);  
29 (2) acetic acid ~~(64-19-7)~~ (64-19-7);  
30 (3) acrolein ~~(107-02-8)~~ (107-02-8);  
31 (4) ammonia ~~(7664-41-7)~~ (7664-41-7);  
32 (5) bromine ~~(7726-95-6)~~ (7726-95-6);  
33 (6) chlorine ~~(7782-50-5)~~ (7782-50-5);  
34 (7) formaldehyde ~~(50-00-0)~~ (50-00-0);  
35 (8) hydrogen chloride ~~(7647-01-0)~~ (7647-01-0);  
36 (9) hydrogen fluoride ~~(7664-39-3)~~ (7664-39-3); and  
37 (10) nitric acid ~~(7697-37-2)~~ (7697-37-2).

1 (e) The owner or operator of the facility and the Division may use any model allowed by ~~40 CFR 51.166(l)~~ 40 CFR  
2 Part 51, Appendix W, provided that the model is appropriate for the facility being modeled. The owner or operator  
3 or the Division may use a model other than one allowed by ~~40 CFR 51.166(l)~~ 40 CFR Part 51, Appendix W provided  
4 that the Director determines that the model is equivalent to the model allowed by ~~40 CFR 51.166(l)~~ 40 CFR Part 51,  
5 Appendix W. ~~Regardless of model used, the owner or operator and the Division shall model for cavity effects and~~  
6 ~~shall comply with the modeling requirements for stack height set out in Rule .0533 of this Subchapter.~~

7 (f) Ambient air concentrations ~~are to~~ shall be evaluated for annual periods over a calendar year, for 24-hour periods  
8 from midnight to midnight, and for one-hour periods beginning on the hour.

9 (g) The owner or operator of the facility shall identify each toxic air pollutant emitted and its corresponding emission  
10 rate using mass balancing analysis, source testing, or other methods that the Director may approve as providing an  
11 equivalently accurate estimate of the emission rate.

12 (h) The owner or operator of the facility shall either submit a modeling plan prior to submitting modeling or submit  
13 a model protocol checklist with modeling to the Director and shall have received approval of that plan from the before  
14 ~~submitting a modeling demonstration to the Director.~~ The modeling plan or protocol checklist shall include:

- 15 (1) a diagram of the plant site, including locations of all stacks and associated buildings;
- 16 (2) on-site building dimensions;
- 17 (3) a diagram showing property boundaries, including a scale, key and north indicator;
- 18 (4) the location of the site on a United States Geological Survey (USGS) map;
- 19 (5) discussion of good engineering stack height and building wake effects for each stack;
- 20 (6) discussion of cavity calculations, impact on rolling and complex terrain, building wake effects, and  
21 urban/rural considerations;
- 22 (7) discussion of reasons for model selection;
- 23 (8) discussion of meteorological data to be used;
- 24 (9) discussion of sources emitting the pollutant that are not to be included in the model with an  
25 explanation of why they are being excluded (i.e. why the source will not affect the modeling  
26 analysis); and
- 27 (10) any other pertinent information.

28  
29 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3),(5); 143B-282; S.L. 1989, c. 168, s. 45;*  
30 *Eff. May 1, 1990;*  
31 *Amended Eff. July 1, ~~1998~~ 1998;*  
32 *Readopted Eff. \_\_\_\_\_.*  
33  
34  
35  
36

1 15A NCAC 02D .1107 is proposed for readoption without substantive changes as follows:

2  
3 **15A NCAC 02D .1107 MULTIPLE FACILITIES**

4 (a) If an acceptable ambient level in ~~Rule .1104 of this Section~~15A NCAC 02D .1104 is exceeded because of  
5 emissions of two or more facilities and if public exposure is such that the ~~commission~~Commission has evidence that  
6 human health may be adversely affected, then the Commission shall require the subject facilities to apply ~~addition~~  
7 additional controls or to otherwise reduce emissions. The type of evidence that the Commission shall consider shall  
8 include one or more of the following:

- 9 (1) emission ~~inventory, inventory;~~  
10 (2) ambient ~~monitoring, monitoring;~~  
11 (3) ~~modeling, modeling;~~ or  
12 (4) epidemiological study.

13 (b) The allocation of the additional reductions shall be based on the relative contributions to the pollutant  
14 concentrations unless the owners or operators agree otherwise.

15 (c) The owner or operator of a facility shall not be required to conduct the multi-facility ambient impact analysis  
16 described in Paragraph (a) of this Rule. This type of analysis shall be done by the ~~Division of Air Quality~~Division.  
17 In performing its analysis, the Division shall:

- 18 (1) develop a modeling plan that includes the elements set out in ~~Paragraph (f) of Rule .1106 of this~~  
19 ~~Section;~~ 15A NCAC 02D .1106(h);  
20 (2) use for the source modeling parameters, the modeling parameters used by the owner or operator of  
21 the source in his or her modeling demonstration, or if a modeling demonstration has not been done  
22 or if a needed parameter has not been used in the modeling demonstration, parameters contained in,  
23 or derived from data contained in, the source's permit;  
24 (3) use a model allowed by ~~Paragraph (e) of Rule .1106 of this Section;~~ 15A NCAC 02D .1106(e);  
25 ~~(4) model for cavity effects and comply with the modeling requirements for stack height set out in Rule~~  
26 ~~.0533 of this Section;~~  
27 ~~(5)(4)~~ use the time periods required by ~~Paragraph (d) of Rule .1106 of this Section;~~ 15A NCAC 02D  
28 .1106(f); and  
29 ~~(6)(5)~~ only consider impacts of a ~~facility=s~~facility's emissions beyond the premises of that facility.

30  
31 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3),(5); 143B-282;*  
32 *Eff. May 1, 1990;*  
33 *Amended Eff. July 1, 1998-1998;*  
34 *Readopted Eff. \_\_\_\_\_.*  
35  
36  
37  
38

1 15A NCAC 02D .1108 is proposed for readoption without changes as follows:

2

3 **15A NCAC 02D .1108 MULTIPLE POLLUTANTS**

4 If the Commission has evidence that two or more toxic air pollutants being emitted from a facility or combination of  
5 facilities act in the same way to affect human health so that their effects may be additive or enhanced and that public  
6 exposure is such that human health may be adversely affected, then the Commission will consider developing  
7 acceptable ambient levels for the combination of toxic air pollutants or other appropriate control measures.

8

9 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3),(5); 143B-282;

10 *Eff. May 1, 1990.*

11 *Readopted Eff.*

12

13

14

15

1 15A NCAC 02D .1109 is proposed for readoption without substantive changes as follows:

2  
3 **15A NCAC 02D .1109 112(J) CASE-BY-CASE MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY**

4 (a) Applicability. This Rule applies only to sources of hazardous air pollutants required to have a permit ~~under~~  
5 pursuant to 15A NCAC 02Q .0500 and as described in 40 CFR 63.50. This Rule does not apply to research or  
6 laboratory activities as defined in Paragraph (b) of this Rule.

7 (b) Definitions. For the purposes of this Rule, the definitions in 40 CFR 63.2, 63.51, 15A NCAC 02Q .0526, and the  
8 following definitions apply:

9 (1) "Affected source" means the collection of equipment, activities, or both within a single contiguous  
10 area and under common control that is in a Section 112(c) source category or subcategory that the  
11 Administrator has failed to promulgate an emission standard by the Section 112(j) deadline, and that  
12 is addressed by an applicable MACT emission limitation established pursuant to 40 CFR Part 63  
13 Subpart B;

14 (2) "Control technology" means measures, processes, methods, systems, or techniques to limit the  
15 emission of hazardous air pollutants including measures that:

16 (A) reduce the quantity, or eliminate emissions, of such pollutants through process changes,  
17 substitution of materials, or other modifications;

18 (B) enclose systems or processes to eliminate emissions;

19 (C) collect, capture, or treat such pollutants when released from a process, stack, storage, or  
20 fugitive emission point;

21 (D) are design, equipment, work practice, or operational standards (including requirements for  
22 operator training or certification) as provided in 42 USC 7412(h); or

23 (E) are a combination of Parts (A) through (D) of this definition.

24 (3) "EPA" means the United States Environmental Protection Agency or the Administrator of U.S.  
25 Environmental Protection Agency.

26 (4) "Hazardous air pollutant" means any pollutant listed ~~under~~ pursuant to Section 112(b) of the federal  
27 Clean Air Act.

28 (5) "MACT" means maximum achievable control technology.

29 (6) "Maximum achievable control technology" means:

30 (A) for existing sources,

31 (i) a MACT standard that EPA has proposed or promulgated for a particular category  
32 of facility or ~~source~~, source;

33 (ii) the average emission limitation achieved by the best performing 12 percent of the  
34 existing facilities or sources for which EPA has emissions information if the  
35 particular category of source contains 30 or more ~~sources~~, sources; or

- 1 (iii) the average emission limitation achieved by the best performing five facilities or  
2 sources for which EPA has emissions information if the particular category of  
3 source contains fewer than 30 ~~sources~~, sources; or
- 4 (B) for new sources, the maximum degree of reduction in emissions that is deemed achievable  
5 but not less stringent than the emission control that is achieved in practice by the best  
6 controlled similar source.
- 7 (7) "MACT floor" means:
- 8 (A) for existing sources:
- 9 (i) the average emission limitation achieved by the best performing 12 percent of the  
10 existing sources (for which EPA has emissions information) excluding those  
11 sources that have, within 18 months before the emission standard is proposed or  
12 within 30 months before such standard is promulgated, whichever is later, first  
13 achieved a level of emission rate or emission reduction which complies, or would  
14 comply if the source is not subject to such standard, with the lowest achievable  
15 emission rate (as defined in Section 171 of the federal Clean Air Act) applicable  
16 to the source category or subcategory for categories and subcategories with 30 or  
17 more sources; or
- 18 (ii) the average emission limitation achieved by the best performing five sources (for  
19 which EPA has emissions or could reasonably obtain emissions information) , in  
20 the category or subcategory, for categories or subcategories with fewer than 30  
21 sources;
- 22 (B) for new sources, the emission limitation achieved in practice by the best controlled similar  
23 source.
- 24 (8) "New affected source" means the collection of equipment, activities, or both, that constructed after  
25 the issuance of a Section 112(j) permit for the source pursuant to 40 CFR 63.52, is subject to the  
26 applicable MACT emission limitation for new sources. Each permit shall define the term "new  
27 affected source," that will be the same as the "affected source" unless a different collection is  
28 warranted based on consideration of factors including:
- 29 (A) Emission reduction impacts of controlling individual sources versus groups of sources;
- 30 (B) Cost effectiveness of controlling individual equipment;
- 31 (C) Flexibility to accommodate common control strategies;
- 32 (D) Cost/benefits of emissions averaging;
- 33 (E) Incentives for pollution prevention;
- 34 (F) Feasibility and cost of controlling processes that share common equipment (e.g., product  
35 recovery devices); and
- 36 (G) Feasibility and cost of ~~monitoring~~, monitoring.



1 (9) "New facility" means a facility for which construction is commenced after the Section 112(j)  
2 deadline, or after proposal of a relevant standard ~~under-pursuant to~~ Section 112(d) or (h) of the  
3 Federal Clean Air Act, whichever comes first.

4 (10) "Research or laboratory activities" means activities whose primary purpose is to conduct research  
5 and development into new processes and products; where such activities are operated under the  
6 supervision of technically trained personnel and are not engaged in the manufacture of products for  
7 commercial sale in commerce, except in a de minimis manner; and where the source is not in a  
8 source category specifically addressing research or laboratory activities, that is listed pursuant to  
9 Section 112(c)(7) of the Clean Air Act.

10 (11) "Section 112(j) deadline" means the date 18 months after the date for which a relevant standard is  
11 scheduled to be promulgated ~~under-pursuant to~~ 40 CFR Part 63, except that for all major sources  
12 listed in the source category schedule for which a relevant standard is scheduled to be promulgated  
13 by November 15, 1994, the Section 112(j) deadline is November 15, 1996, and for all major sources  
14 listed in the source category schedule for which a relevant standard is scheduled to be promulgated  
15 by November 15, 1997, the Section 112(j) deadline is December 15, 1999.

16 (12) "Similar source" means that equipment or collection of equipment that, by virtue of its structure,  
17 operability, type of emissions and volume and concentration of emissions, is substantially equivalent  
18 to the new affected source and employs control technology for control of emissions of hazardous  
19 air pollutants that is practical for use on the new affected source.

20 (c) Missed promulgation dates: 112(j). If EPA fails to promulgate a standard for a category of source ~~under-pursuant~~  
21 ~~to~~ Section 112 of the Federal Clean Air Act by the date established pursuant to Sections 112(e)(1) or (3) of the federal  
22 Clean Air Act, the owner or operator of any source in such category shall submit, within 18 months after such date, a  
23 permit application, in accordance with the procedures in 15A NCAC 02Q .0526, to the Director and to EPA to apply  
24 MACT to such sources. Sources subject to this Paragraph shall be in compliance with this Rule within three years  
25 from the date that the permit is issued.

26 (d) New facilities. The owner or operator of any new facility that is a major source of hazardous air pollutants (HAP)  
27 that is subject to this Rule shall apply MACT in accordance with the provisions of ~~Rule .1112 of this Section, 15A~~  
28 ~~NCAC 02D .1112,~~ 15A NCAC 02Q .0528, and ~~02Q .0526(e)(2).~~

29 (e) Case-by-case MACT determination. The Director shall determine MACT according to 40 CFR 63.55(a).

30 (f) Monitoring and recordkeeping. The owner or operator of a source subject to this Rule shall install, operate, and  
31 maintain monitoring capable of detecting deviations from each applicable emission limitation or other standards with  
32 sufficient reliability and timeliness to determine continuous compliance over the applicable reporting period. Such  
33 monitoring data may be used as a basis for enforcing emissions limitations established ~~under-pursuant to~~ this Rule.

34  
35 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5), (10);*

36 *Temporary Adoption Eff. March 8, 1994 for a period of 180 days or until the permanent rule is*  
37 *effective, whichever is sooner;*

1  
2  
3  
4  
5

*Eff. July 1, 1994;*

*Amended Eff. February 1, 2004; July 1, 1998; July 1, ~~1996~~ 1996;*

*Readopted Eff.\_\_\_\_\_.*

1 15A NCAC 02D .1110 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02D .1110 NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS**

4 (a) With the exception of Paragraph (b) of this Rule, sources subject to national emission standards for hazardous air  
5 pollutants promulgated in 40 CFR Part 61 shall comply with emission standards, monitoring and reporting  
6 requirements, maintenance requirements, notification and record keeping requirements, performance test  
7 requirements, test method and procedural provisions, and any other provisions, as required therein, rather than with  
8 any otherwise-applicable Rule in ~~Section .0500 of this Subchapter~~ 15A NCAC 02D .0500 that would be in conflict  
9 therewith.

10 (b) Along with the notice appearing in the North Carolina Register for a public hearing to amend this Rule to exclude  
11 a standard from this Rule, the Director shall state whether or not the national emission standards for hazardous air  
12 pollutants promulgated under 40 CFR Part 61, or part thereof, shall be enforced. If the Commission does not adopt  
13 the amendment to this Rule to exclude or amend the standard within 12 months after the close of the comment period  
14 on the proposed amendment, the Director shall begin enforcing that standard when 12 months has elapsed after the  
15 end of the comment period on the proposed amendment.

16 ~~(c) New sources of volatile organic compounds that are located in an area designated in 40 CFR 81.334 as~~  
17 ~~nonattainment for ozone or an area identified in accordance with 15A NCAC 02D .0902 as in violation of the ambient~~  
18 ~~air quality standard for ozone shall comply with the requirements of 40 CFR Part 61 that are not excluded by this~~  
19 ~~Rule, as well as with any applicable requirements in Section .0900 of this Subchapter.~~

20 ~~(d)~~(c) All requests, reports, applications, submittals, and other communications to the administrator required under  
21 Paragraph (a) of this Rule shall be submitted to the Director of the Division of Air Quality rather than to the  
22 Environmental Protection Agency; except that all such reports, applications, submittals, and other communications to  
23 the administrator required by 40 CFR 61.145 shall be submitted to the Director, Division of Epidemiology.

24 ~~(e)~~(d) In the application of this Rule, definitions contained in 40 CFR Part 61 shall apply rather than those of ~~Section~~  
25 ~~.0100 of this Subchapter.~~ in 15A NCAC 02D .0100.

26 ~~(f)~~(e) 15A NCAC 02Q .0102 ~~and .0302~~ are shall not be applicable to any source to which this Rule applies. The  
27 owner or operator of the source shall apply for and receive a permit ~~as if required in pursuant to~~ 15A NCAC 02Q  
28 .0300 or .0500.

29  
30 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107 (a)(5); 150B-21.6;*

31 *Eff. July 1, 1996;*

32 *Amended Eff. June 1, 2008; July 1, ~~1997.~~1997;*

33 *Readopted Eff.*

1 15A NCAC 02D .1111 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02D .1111 MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY**

4 (a) With the exception of Paragraph (b) or (c) of this Rule, sources subject to national emission standards for hazardous  
5 air pollutants for source categories promulgated in 40 CFR Part 63 shall comply with emission standards, monitoring  
6 and reporting requirements, maintenance requirements, notification and record keeping requirements, performance  
7 test requirements, test method and procedural provisions, and any other provisions, as required therein, rather than  
8 with any otherwise-applicable rule in ~~Section .0500 of this Subchapter~~ 15A NCAC 02D .0500 which would be in  
9 conflict therewith.

10 (b) The following are not included under this Rule:

11 (1) approval of state programs and delegation of federal authorities (40 CFR 63.90 to 63.96, Subpart  
12 E); and

13 (2) requirements for control technology determined for major sources in accordance with Clean Air Act  
14 Sections 112(g) and 112(j) (40 CFR 63.50 to 63.57, Subpart B).

15 (c) Along with the notice appearing in the North Carolina Register for a public hearing to amend this Rule to exclude  
16 a standard from this Rule, the Director shall state whether or not the national emission standard for hazardous air  
17 pollutants for source categories promulgated under 40 CFR Part 63, or part thereof, shall be enforced. If the  
18 Commission does not adopt the amendment to this Rule to exclude or amend the standard within 12 months after the  
19 close of the comment period on the proposed amendment, the Director shall begin enforcing that standard when 12  
20 months has elapsed after the end of the comment period on the proposed amendment.

21 ~~(d) New sources of volatile organic compounds that are located in an area designated in 40 CFR 81.334 as~~  
22 ~~nonattainment for ozone or an area identified in accordance with 15A NCAC 02D .0902 as being in violation of the~~  
23 ~~ambient air quality standard for ozone shall comply with the requirements of 40 CFR Part 63 that are not excluded by~~  
24 ~~this Rule as well as with any applicable requirements in Section .0900 of this Subchapter.~~

25 ~~(e)(d)~~ All requests, reports, applications, submittals, and other communications to the administrator required under  
26 Paragraph (a) of this Rule shall be submitted to the Director of the Division of Air Quality rather than to the  
27 Environmental Protection Agency; except that all such reports, applications, submittals, and other communications to  
28 the administrator required by 40 CFR Part 63, Subpart M for dry cleaners covered under Chapter 143, Article 21A,  
29 Part 6 of the General Statutes shall be submitted to the Director of the Division of Waste Management.

30 ~~(f)(e)~~ In the application of this Rule, definitions contained in 40 CFR Part 63 shall apply rather than those of Section  
31 .0100 of this Subchapter when conflict exists.

32 ~~(g)(f)~~ 15A NCAC 02Q .0102 ~~and .0302~~ ~~are~~ is not applicable to any source to which this Rule applies if the source is  
33 required to be permitted under 15A NCAC 02Q .0500, Title V Procedures. The owner or operator of the source shall  
34 apply for and receive a permit ~~as if required in pursuant to~~ 15A NCAC 02Q .0300 or .0500. Sources that have  
35 heretofore been exempted from needing a permit and become subject to requirements promulgated under 40 CFR 63  
36 shall apply for a permit in accordance to 15A NCAC 02Q .0109.

1 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); 150B-21.6;*  
2 *Eff. July 1, 1996;*  
3 *Amended Eff. January 1, 2007; April 1, ~~1997~~.1997;*  
4 *Readopted Eff.\_\_\_\_\_.*  
5  
6

1 15A NCAC 02D .1112 is proposed for reoption without substantive changes as follows:

2  
3 **15A NCAC 02D .1112 112(G) CASE BY CASE MAXIMUM ACHIEVABLE CONTROL TECHNOLOGY**

4 (a) Applicability. This Rule applies to the construction or reconstruction of major sources of hazardous air pollutants  
5 unless:

6 (1) the major source has been specifically regulated or exempted from regulation ~~under~~ pursuant to:

7 (A) ~~Rule .1109 or .1111 of this Section;~~ 15A NCAC 02D .1109 or .1111; or

8 (B) a standard issued pursuant to Section 112(d), 112(h), or 112(j) of the federal Clean Air Act  
9 and incorporated in another Subpart of 40 CFR Part 63; or

10 (2) the owner or operator of such major source has received all necessary air quality permits for such  
11 construction or reconstruction project before July 1, 1998.

12 (b) Exclusions. The requirements of this Rule shall not apply to:

13 (1) electric utility steam generating units unless and until such time as these units are added to the source  
14 category list pursuant to Section 112(c)(5) of the federal Clean Air Act.

15 (2) stationary sources that are within a source category that has been deleted from the source category  
16 list pursuant to Section 112(c)(9) of the federal Clean Air Act.

17 (3) research and development activities.

18 (c) Definitions. For the purposes of this Rule, the following definitions apply:

19 (1) "Affected source" means the stationary source or group of stationary sources that, when fabricated  
20 (on site), erected, or installed meets the definition of "construct a major source" or the definition of  
21 "reconstruct a major source" contained in this Paragraph.

22 (2) "Affected States" means all States or local air pollution agencies whose areas of jurisdiction are:

23 (A) contiguous to North Carolina and located less than  $D=Q/12.5$  from the facility, where:

24 (i)  $Q$  = emissions of the pollutant emitted at the highest permitted rate in tons per  
25 ~~year,~~ year; and

26 (ii)  $D$  = distance from the facility to the contiguous state or local air pollution control  
27 agency in miles; or

28 (B) within 50 miles of the permitted facility.

29 (3) "Available information" means, for purposes of identifying control technology options for the  
30 affected source, information contained in the following information sources as of the date of  
31 approval of the MACT determination by the Division:

32 (A) a relevant proposed regulation, including all supporting information;

33 (B) background information documents for a draft or proposed regulation;

34 (C) data and information available from the Control Technology Center developed pursuant to  
35 Section 113 of the federal Clean Air Act;

36 (D) data and information contained in the Aerometric Informational Retrieval System  
37 including information in the MACT data base;

- 1 (E) any additional information that can be expeditiously provided by the Division and EPA;  
2 and
- 3 (F) for the purpose of determinations by the Division, any additional information provided by  
4 the applicant or others, and any additional information considered available by the  
5 Division.
- 6 (4) "Construct a major source" means:
- 7 (A) To fabricate, erect, or install at any greenfield site a stationary source or group of stationary  
8 sources which is located within a contiguous area and under common control and which  
9 emits or has the potential to emit 10 tons per year of any HAP's or 25 tons per year of any  
10 combination of ~~HAP, HAP~~; or
- 11 (B) To fabricate, erect, or install at any developed site a new process or production unit which  
12 in and of itself emits or has the potential to emit 10 tons per year of any HAP or 25 tons  
13 per year of any combination of HAP, unless the process or production unit satisfies  
14 Subparts (i) through (vi) of this Paragraph:
- 15 (i) All HAP emitted by the process or production unit that would otherwise be  
16 controlled ~~under~~ subject to the requirements of this Rule will be controlled by  
17 emission control equipment which was previously installed at the same site as the  
18 process or production unit;
- 19 (ii) The Division:
- 20 (I) has determined within a period of five years prior to the fabrication,  
21 erection, or installation of the process or production unit that the existing  
22 emission control equipment represented best available control  
23 technology (BACT) ~~under Rule .0530 of this Subchapter pursuant to~~  
24 15A NCAC 02D .0530 or lowest achievable emission rate (LAER) ~~under~~  
25 Rule .0531 of this Subchapter pursuant to 15A NCAC 02D .0531 for the  
26 category of pollutants which includes those HAP's to be emitted by the  
27 process or production unit; or
- 28 (II) determines that the control of HAP emissions provided by the existing  
29 equipment will be equivalent to that level of control currently achieved  
30 by other well-controlled similar sources (i.e., equivalent to the level of  
31 control that would be provided by a current BACT, LAER, or MACT  
32 determination ~~under Rule .1109 of this Section~~; pursuant to 15A NCAC  
33 02D .1109);
- 34 (iii) The Division determines that the percent control efficiency for emissions of HAP  
35 from all sources to be controlled by the existing control equipment will be  
36 equivalent to the percent control efficiency provided by the control equipment  
37 prior to the inclusion of the new process or production unit;

- 1 (iv) The Division has provided notice and an opportunity for public comment  
2 concerning its determination that criteria in Subparts (i), (ii), and (iii) of this  
3 Subparagraph apply and concerning the continued adequacy of any prior LAER,  
4 BACT, or MACT determination ~~under Rule .1109 of this Section; pursuant to 15A~~  
5 NCAC 02D .1109;
- 6 (v) If any commenter has asserted that a prior LAER, BACT, or MACT determination  
7 ~~under Rule .1109 of this Section pursuant to 15A NCAC 02D .1109~~  
8 ~~determination~~ is no longer adequate, the Division has determined that the level of  
9 control required by that prior determination remains adequate; and
- 10 (vi) Any emission limitations, work practice requirements, or other terms and  
11 conditions upon which the above determinations by the Division are predicated  
12 will be construed by the Division as applicable requirements ~~under pursuant to~~  
13 Section 504(a) of the federal Clean Air Act and either have been incorporated into  
14 an existing permit issued ~~under pursuant to~~ 15A NCAC ~~2002Q~~ .0500 for the  
15 affected facility or will be incorporated into such permit upon issuance.
- 16 (5) "Control technology" means measures, processes, methods, systems, or techniques to limit the  
17 emission of hazardous air pollutants including measures that:
- 18 (A) reduce the quantity of, or eliminate emissions of, such pollutants through process changes,  
19 substitution of materials or other modifications;
- 20 (B) enclose systems or processes to eliminate emissions;
- 21 (C) collect, capture or treat such pollutants when released from a process, stack, storage or  
22 fugitive emissions point;
- 23 (D) are design, equipment, work practice, or operational standards (including requirements for  
24 operator training or certification) as provided in 42 U.S.C. 7412(h); or
- 25 (E) are a combination of Parts (A) through (D) of this definition.
- 26 (6) "Electric utility steam generating unit" means any fossil fuel fired combustion unit of more than 25  
27 megawatts that serves a generator that produces electricity for sale. A unit that co-generates steam  
28 and electricity and supplies more than one-third of its potential electric output capacity and more  
29 than 25 megawatts electric output to any utility power distribution system for sale shall be  
30 considered an electric utility steam generating unit.
- 31 (7) "Greenfield site" means a contiguous area under common control that is an undeveloped site.
- 32 (8) "HAP" means hazardous air pollutants.
- 33 (9) "Hazardous air pollutant" means any pollutant listed ~~under pursuant to~~ Section 112(b) of the federal  
34 Clean Air Act.
- 35 (10) "List of source categories" means the source category list required by Section 112(c) of the federal  
36 Clean Air Act.
- 37 (11) "MACT" means maximum achievable control technology.



- 1 (12) "Maximum achievable control technology emission limitation for new sources" means the emission  
2 limitation which is not less stringent than the emission limitation achieved in practice by the best  
3 controlled similar source, and which reflects the maximum degree of reduction in emissions that the  
4 permitting authority, taking into consideration the cost of achieving such emission reduction, and  
5 any non-air quality health and environmental impacts and energy requirements, determines is  
6 achievable by the constructed or reconstructed major source.
- 7 (13) "Process or production unit" means any collection of structures or equipment, that processes,  
8 assembles, applies, or otherwise uses material inputs to produce or store an intermediate or final  
9 product. A single facility may contain more than one process or production unit.
- 10 (14) "Reconstruct a major source" means the replacement of components at an existing process or  
11 production unit that in and of itself emits or has the potential to emit 10 tons per year of any HAP  
12 or 25 tons per year of any combination of HAP, whenever:
- 13 (A) The fixed capital cost of the new components exceeds 50 percent of the fixed capital cost  
14 that would be required to construct a comparable process or production unit; and
- 15 (B) It is technically and economically feasible for the reconstructed major source to meet the  
16 applicable maximum achievable control technology emission limitation for new sources  
17 established ~~under~~ pursuant to this Subpart.
- 18 (15) "Research and development activities" means activities conducted at a research or laboratory facility  
19 whose primary purpose is to conduct research and development into new processes and products,  
20 where such source is operated under the close supervision of technically trained personnel and is  
21 not engaged in the manufacture of products for sale or exchange for commercial profit, except in a  
22 de minimis manner.
- 23 (16) "Similar source" means a stationary source or process that has comparable emissions and is  
24 structurally similar in design and capacity to a constructed or reconstructed major source such that  
25 the source could be controlled using the same control technology.
- 26 (d) Principles of MACT determinations. The following general principles shall be used to make a case-by-case  
27 MACT determination concerning construction or reconstruction of a major source ~~under~~ pursuant to this Rule:
- 28 (1) The MACT emission limitation or MACT requirements recommended by the applicant and  
29 approved by the Division shall not be less stringent than the emission control that is achieved in  
30 practice by the best controlled similar source, as determined by the Division.
- 31 (2) Based upon available information, the MACT emission limitation and control technology (including  
32 any requirements ~~under~~ pursuant to Subparagraph (3) of this Paragraph) recommended by the  
33 applicant and approved by the Division shall achieve the maximum degree of reduction in emissions  
34 of HAP that can be achieved by utilizing those control technologies that can be identified from the  
35 available information, taking into consideration the costs of achieving such emission reduction and  
36 any non-air quality health and environmental impacts and energy requirements associated with the  
37 emission reduction.

1 (3) The owner or operator may recommend a specific design, equipment, work practice, or operational  
2 standard, or a combination thereof, and the Director may approve such a standard if the Division  
3 specifically determines that it is not feasible to prescribe or enforce an emission limitation ~~under~~  
4 pursuant to the criteria set forth in Section 112(h)(2) of the federal Clean Air Act.

5 (4) If the EPA has either proposed a relevant emission standard pursuant to Section 112(d) or 112(h) of  
6 the federal Clean Air Act or adopted a presumptive MACT determination for the source category  
7 that includes the constructed or reconstructed major source, then the MACT requirements applied  
8 to the constructed or reconstructed major source shall have considered those MACT emission  
9 limitations and requirements of the proposed standard or presumptive MACT determination.

10 (e) Effective date of MACT determination. The effective date of a MACT determination shall be the date of issuance  
11 of a permit ~~under~~ pursuant to procedures of 15A NCAC ~~2002Q~~ .0300 or .0500 incorporating a MACT determination.

12 (f) Compliance date. On and after the date of start-up, a constructed or reconstructed major source that is subject to  
13 the requirements of this Rule shall be in compliance with all applicable requirements specified in the MACT  
14 determination.

15 (g) Compliance with MACT determinations. The owner or operator of a constructed or reconstructed major source  
16 that:

17 (1) is subject to a MACT determination shall comply with all requirements set forth in the permit issued  
18 ~~under~~ pursuant to 15A NCAC ~~2002Q~~ .0300 or .0500, including any MACT emission limitation or  
19 MACT work practice standard, and any notification, operation and maintenance, performance  
20 testing, monitoring, reporting, and recordkeeping requirements; or

21 (2) has obtained a MACT determination shall be deemed to be in compliance with Section 112(g)(2)(B)  
22 of the federal Clean Air Act only to the extent that the constructed or reconstructed major source is  
23 in compliance with all requirements set forth in the permit issued ~~under~~ pursuant to 15A NCAC  
24 ~~2002Q~~ .0300 or .0500. Any violation of such requirements by the owner or operator shall be  
25 deemed by the Division and by EPA to be a violation of the prohibition on construction or  
26 reconstruction in Section 112(g)(2)(B) of the federal Clean Air Act for whatever period the owner  
27 or operator is determined to be in violation of such requirements, and shall subject the owner or  
28 operator to appropriate enforcement action ~~under~~ pursuant to the General Statutes and the federal  
29 Clean Air Act.

30 (h) Requirements for constructed or reconstructed major sources subject to a subsequently promulgated MACT  
31 standard or MACT requirement. If EPA promulgates an emission standard ~~under~~ pursuant to Section 112(d) or 112(h)  
32 of the federal Clean Air Act or the Division issues a determination ~~under Rule .1109 of this Section~~ pursuant to 15A  
33 NCAC 02D .1109 that is applicable to a stationary source or group of sources that would be deemed to be a constructed  
34 or reconstructed major source ~~under~~ pursuant to this Rule:

35 (1) before the date that the owner or operator has obtained a final and legally effective MACT  
36 determination ~~under~~ pursuant to 15A NCAC ~~2002Q~~ .0300 or .0500, the owner or operator of the

1 source(s) shall comply with the promulgated standard or determination rather than any MACT  
2 determination ~~under-pursuant to~~ this Rule by the compliance date in the promulgated standard; or

- 3 (2) after the source has been subject to a prior case-by-case MACT ~~under-pursuant to~~ this Rule, and the  
4 owner or operator obtained a final and legally effective case-by-case MACT determination prior to  
5 the promulgation date of such emission standard, the Division shall (if the initial permit has not yet  
6 been issued ~~under-pursuant to~~ 15A NCAC ~~2Q02Q~~ .0500) issue an initial permit that incorporates  
7 the emission standard or determination, or shall (if the initial permit has been issued ~~under-pursuant~~  
8 ~~to~~ 15A NCAC ~~2Q02Q~~ .0500) revise the permit according to the reopening procedures in 15A NCAC  
9 ~~2Q02Q~~ .0517, Reopening for Cause, whichever is relevant, to incorporate the emission standard or  
10 determination.

11 (i) Compliance with subsequent 112(d), 112(h), or 112(j) standards. EPA may include in the emission standard  
12 established ~~under-pursuant to~~ Section 112(d) or 112(h) of the federal Clean Air Act a specific compliance date for  
13 those sources that have obtained a final and legally effective MACT determination ~~under-pursuant to~~ this Rule and  
14 that have submitted the information required by 40 CFR 63.43 to EPA before the close of the public comment period  
15 for the standard established ~~under-pursuant to~~ section 112(d) of the federal Clean Air Act. Such date shall assure that  
16 the owner or operator shall comply with the promulgated standard as expeditiously as practicable, but not longer than  
17 eight years after such standard is promulgated. In that event, the Division shall incorporate the applicable compliance  
18 date in the permit issued ~~under-pursuant to~~ 15A NCAC ~~2Q02Q~~ .0500. If no compliance date has been established in  
19 the promulgated 112(d) or 112(h) standard or determination ~~under Rule .1109 of this Section, pursuant to 15A NCAC~~  
20 ~~02D .1109~~, for those sources that have obtained a final and legally effective MACT determination ~~under-pursuant to~~  
21 this Rule, then the Director shall establish a compliance date in the permit that assures that the owner or operator shall  
22 comply with the promulgated standard or determination as expeditiously as practicable, but not longer than eight years  
23 after such standard is promulgated or a determination is made ~~under Rule .1109 of this Section, pursuant to 15A~~  
24 ~~NCAC 02D .1109~~.

25 (j) Revision of permit to incorporate less stringent control. Notwithstanding the requirements of Paragraph (h) of this  
26 Rule, if the Administrator of EPA promulgates an emission standard ~~under-pursuant to~~ Section 112(d) or Section  
27 112(h) of the federal Clean Air Act or the Division issues a determination ~~under Rule .1109 of this Section pursuant~~  
28 ~~to 15A NCAC 02D .1109~~ that is applicable to a stationary source or group of sources that was deemed to be a  
29 constructed or reconstructed major source ~~under-pursuant to~~ this Rule and that is the subject of a prior case-by-case  
30 MACT determination pursuant to 40 CFR 63.43, and the level of control required by the emission standard issued  
31 ~~under-pursuant to~~ Section 112(d) or 112(h) or the determination issued ~~under Rule .1109 of this Section pursuant to~~  
32 ~~15A NCAC 02D .1109~~ is less stringent than the level of control required by any emission limitation or standard in the  
33 prior MACT determination, the Division is not required to incorporate any less stringent terms of the promulgated  
34 standard in the permit issued ~~under-pursuant to~~ 15A NCAC ~~2Q02Q~~ .0500 applicable to such source(s) and may  
35 consider any more stringent provisions of the prior MACT determination to be applicable legal requirements when  
36 issuing or revising such an operating permit.

37

1 *History Note:* *Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5),(10);*  
2 *Eff. July 1, ~~1998~~ 1998;*  
3 *Readopted Eff.\_\_\_\_\_.*  
4  
5  
6  
7

1 15A NCAC 02D .1201 is proposed for reoption with substantive changes as follows:

2  
3 **SECTION .1200 - CONTROL OF EMISSIONS FROM INCINERATORS AND COMBUSTION UNITS**

4  
5 **15A NCAC 02D .1201 PURPOSE AND SCOPE**

6 ~~(a) This Section sets forth rules for the control of the emissions of air pollutants from incinerators.~~

7 ~~(b)(a) The rules in this Section apply to all types of incinerators as defined by 15A NCAC 02D .0101(21), including~~  
8 ~~incinerators with heat recovery and industrial incinerators. apply to incinerators and combustor units as defined in~~  
9 ~~15A NCAC 02D .1202 or regulated under 15A NCAC 02D .1208.~~

10 ~~(e)(b) The rules in this Section do not apply to:~~

- 11 (1) afterburners, flares, fume incinerators, and other similar devices used to reduce the emissions of air  
12 pollutants from processes, whose emissions shall be regulated as process emissions;
- 13 (2) any boilers or industrial furnaces that burn waste as a fuel, except ~~hazardous waste as defined in 40~~  
14 ~~CFR 260.10;~~ solid waste as defined in 40 CFR 241.2;
- 15 (3) air curtain burners, which shall comply with ~~Section 1900 of this Subchapter;~~ 15A NCAC 02D  
16 .1900; or
- 17 (4) incinerators used to dispose of dead animals or poultry, that meet all the following requirements:
  - 18 (A) the incinerator is located on a farm and is operated by the farm owner or by the farm  
19 operator;
  - 20 (B) the incinerator is used solely to dispose of animals or poultry originating on the farm where  
21 the incinerator is located;
  - 22 (C) the incinerator is not charged at a rate that exceeds its design capacity; and
  - 23 (D) the incinerator complies with Rule 15A NCAC 02D .0521 ~~(visible emissions)~~ and .1806  
24 ~~(odorous emissions) of this Subchapter.~~ (visible emissions).

25 ~~(d) If an incinerator is more than one type of incinerator, then the following order shall be used to determine the~~  
26 ~~standards and requirements to apply:~~

- 27 (1) ~~hazardous waste incinerators;~~
- 28 (2) ~~sewage sludge incinerators;~~
- 29 (3) ~~sludge incinerators;~~
- 30 (4) ~~municipal waste combustors;~~
- 31 (5) ~~commercial and industrial solid waste incinerators;~~
- 32 (6) ~~hospital, medical, or infectious waste incinerators (HMIWIs);~~
- 33 (7) ~~other solid waste incinerators;~~
- 34 (8) ~~conical incinerators;~~
- 35 (9) ~~crematory incinerators; and~~
- 36 (10) ~~other incinerators.~~

1 ~~(e) In addition to any permit that may be required under 15A NCAC 02Q, Air Quality Permits Procedures, a permit~~  
2 ~~may be required by the Division of Waste Management as determined by the permitting rules enforced by the Division~~  
3 ~~of Waste Management.~~

4 ~~(c) Referenced document SW-846 "Test Methods for Evaluating Solid Waste," Third Edition, cited by rules in this~~  
5 ~~Section is hereby incorporated by reference and may be obtained free of charge online at [https://www.epa.gov/hw-](https://www.epa.gov/hw-sw846)~~  
6 ~~[sw846](https://www.epa.gov/hw-sw846), does not include subsequent amendments or editions. A copy of this document is available for inspection at~~  
7 ~~the North Carolina Department of Environment and Natural Resources Library located at 512 North Salisbury Street,~~  
8 ~~Raleigh, NC 27603. Copies of this document may be obtained through the US Government Printing Office,~~  
9 ~~Superintendent of Documents, P.O. Box 371954, Pittsburgh, PA 15250 7954, or by calling (202) 783 3238. The cost~~  
10 ~~of this document is three hundred nineteen dollars (\$319.00).~~

11  
12 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(1), (3), (4), (5);*  
13 *Eff. October 1, 1991;*  
14 *Amended Eff. July 1, 2000; July 1, 1999; July 1, 1998; April 1, 1995; December 1, 1993;*  
15 *Temporary Amendment Eff. March 1, 2002;*  
16 *Amended Eff. July 1, 2007; December 1, 2005; August 1, ~~2002, 2002~~;*  
17 *Readopted Eff. \_\_\_\_\_.*  
18  
19

1 15A NCAC 02D .1202 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02D .1202 DEFINITIONS**

4 (a) For the purposes of this Section, the definitions ~~at G.S. 143-212 and 143-213 and 15A NCAC 02D .0101 in 40~~  
5 CFR 60.5250, 40 CFR 60.2875, and 40 CFR 60.51c shall apply, and apply in addition, addition to the following  
6 definitions shall apply. definitions: If a term in this Rule is also defined at 15A NCAC 02D .0101, then the definition  
7 in this Rule controls.

8 ~~(1) "Class I municipal waste combustor" means a small municipal waste combustor located at a~~  
9 ~~municipal waste combustion plant with an aggregate plant combustion capacity greater than 250~~  
10 ~~tons per day of municipal solid waste.~~

11 ~~(1) "Air curtain incinerator" (also referred to as an "air curtain burner") means an incinerator that~~  
12 ~~operates by forcefully projecting a curtain of air across an open chamber or pit in which combustion~~  
13 ~~occurs as defined in 40 CFR 60.2875.~~

14 ~~(2) "Commercial and industrial solid waste incinerator" (CISWI) or "commercial and industrial solid~~  
15 ~~waste incineration unit" means any distinct operating unit of any commercial or industrial facility~~  
16 ~~that combusts, or has combusted in the preceding 6 months, any solid waste as defined in 40 CFR~~  
17 ~~241. If the operating unit burns materials other than traditional fuels as defined in 40 CFR 241.2 that~~  
18 ~~have been discarded, and the owner or operator does not keep and produce records as required by~~  
19 ~~40 CFR 60.2740(u), the operating unit is a CISWI unit. A CISWI unit includes, but is not limited~~  
20 ~~to, the solid waste feed system, grate system, flue gas system, waste heat recovery equipment, if~~  
21 ~~any, and bottom ash system. The CISWI unit does not include air pollution control equipment or the~~  
22 ~~stack. The CISWI unit boundary starts at the solid waste hopper (if applicable) and extends through~~  
23 ~~two areas: The combustion unit flue gas system, which ends immediately after the last combustion~~  
24 ~~chamber or after the waste heat recovery equipment, if any; and the combustion unit bottom ash~~  
25 ~~system, which ends at the truck loading station or similar equipment that transfers the ash to final~~  
26 ~~disposal. The CISWI unit includes all ash handling systems connected to the bottom ash handling~~  
27 ~~system as defined in 40 CFR 60.2875. any combustion device, except air pollution control devices,~~  
28 ~~that combusts commercial and industrial waste.~~

29 ~~(3) "Commercial and industrial waste" means solid waste combusted in an enclosed device using~~  
30 ~~controlled flame combustion without energy recovery that is a distinct operating unit of any~~  
31 ~~commercial or industrial facility (including field erected, modular, and custom built incineration~~  
32 ~~units operating with starved or excess air).~~

33 ~~(4)~~(3) "Co-fired combustor" means a unit combusting hospital, medical, or infectious waste with other  
34 fuels or wastes (e.g., coal, municipal solid waste) and subject to an enforceable requirement limiting  
35 the unit to combusting a fuel feed stream, 10 percent or less of the weight of which is comprised, in  
36 aggregate, of hospital, medical, or infectious waste as measured on a calendar quarter basis as  
37 defined in 40 CFR 60.51c. For the purposes of this definition, pathological waste, chemotherapeutic

1 waste, and low-level radioactive waste are considered "other" wastes when calculating the  
2 percentage of hospital, medical, or infectious waste combusted.

3 ~~(5)~~(4) "Crematory incinerator" means any incinerator located at a crematory regulated under 21 NCAC  
4 34C that is used solely for the cremation of human remains.

5 ~~(6)~~ "Construction and demolition waste" means wood, paper, and other combustible waste, except for  
6 hazardous waste and asphaltic material, resulting from construction and demolition projects.

7 ~~(7)~~(5) "Dioxin and Furan" (also referred to as "dioxins/furans") means tetra- through octa- chlorinated  
8 dibenzo-p-dioxins and dibenzofurans.

9 ~~(8)~~ "Hazardous waste incinerator" means an incinerator regulated under 15A NCAC 13A .0101 through  
10 .0119, 40 CFR 264.340 to 264.351, Subpart O, or 265.340 to 265.352, Subpart O.

11 ~~(9)~~(6) "Hospital, medical and infectious waste incinerator (HMIWI)" means any device that combusts any  
12 amount of hospital, medical and infectious waste.

13 ~~(10)~~(7) "Large HMIWI" means:

14 (A) a HMIWI whose maximum design waste burning capacity is more than 500 pounds per  
15 hour;

16 (B) a continuous or intermittent HMIWI whose maximum charge rate is more than 500 pounds  
17 per hour; or

18 (C) a batch HMIWI whose maximum charge rate is more than 4,000 pounds per day.

19 ~~(11)~~(8) "Hospital waste" means discards generated at a hospital, except unused items returned to the  
20 manufacturer. The definition of hospital waste does not include human corpses, remains, and  
21 anatomical parts that are intended for interment or cremation.

22 ~~(12)~~ "Institutional facility" means a land-based facility owned or operated by an organization having a  
23 governmental, educational, civic, or religious purpose, such as a school, hospital, prison, military  
24 installation, church, or other similar establishment or facility.

25 ~~(13)~~ "Institutional waste" means solid waste that is combusted at any institutional facility using  
26 controlled flame combustion in an enclosed, distinct operating unit:

27 (A) whose design does not provide for energy recovery and

28 (B) which is operated without energy recovery or operated with only waste heat recovery.

29 Institutional waste also means solid waste combusted on site in an air curtain incinerator that is a  
30 distinct operating unit of any institutional facility.

31 ~~(14)~~ "Institutional waste incineration unit" means any combustion unit that combusts institutional waste  
32 and is a distinct operating unit of the institutional facility that generated the waste.

33 ~~(15)~~ "Large municipal waste combustor" means each municipal waste combustor unit with a combustion  
34 capacity greater than 250 tons per day of municipal solid waste.

35 ~~(16)~~(9) "Medical and Infectious Waste" means any waste generated in the diagnosis, treatment, or  
36 immunization of human beings or animals, in research pertaining thereto, or in the production or  
37 testing of biologicals that is listed in Part (A)(i) through (A)(vii) of this Subparagraph.



- 1 (A) The definition of medical and infectious waste includes:
- 2 (i) cultures and stocks of infectious agents and associated biologicals, including:
- 3 (I) cultures from medical and pathological laboratories;
- 4 (II) cultures and stocks of infectious agents from research and industrial
- 5 laboratories;
- 6 (III) wastes from the production of biologicals;
- 7 (IV) discarded live and attenuated vaccines; and
- 8 (V) culture dishes and devices used to transfer, inoculate, and mix cultures;
- 9 (ii) human pathological waste, including tissues, organs, and body parts and body
- 10 fluids that are removed during surgery or autopsy, or other medical procedures,
- 11 and specimens of body fluids and their containers;
- 12 (iii) human blood and blood products including:
- 13 (I) liquid waste human blood;
- 14 (II) products of blood;
- 15 (III) items saturated or dripping with human blood; or
- 16 (IV) items that were saturated or dripping with human blood that are now
- 17 caked with dried human blood including serum, plasma, and other blood
- 18 components, and their containers, which were used or intended for use
- 19 in either patient care, testing and laboratory analysis or the development
- 20 of pharmaceuticals. Intravenous bags are also included in this category;
- 21 (iv) sharps that have been used in animal or human patient care or treatment or in
- 22 medical, research, or industrial laboratories, including hypodermic needles,
- 23 syringes (with or without the attached needle), pasteur pipettes, scalpel blades,
- 24 blood vials, needles with attached tubing, and culture dishes (regardless of
- 25 presence of infectious agents). Also included are other types of broken or
- 26 unbroken glassware that were in contact with infectious agents, such as used slides
- 27 and cover slips;
- 28 (v) animal waste including contaminated animal carcasses, body parts, and bedding
- 29 of animals that were known to have been exposed to infectious agents during
- 30 research (including research in veterinary hospitals), production of biologicals or
- 31 testing of pharmaceuticals;
- 32 (vi) isolation wastes including biological waste and discarded materials contaminated
- 33 with blood, excretions, exudates, or secretions from humans who are isolated to
- 34 protect others from highly communicable diseases, or isolated animals known to
- 35 be infected with highly communicable diseases; and
- 36 (vii) unused sharps including the following unused or discarded sharps;
- 37 (I) hypodermic needles;

1 (II) suture needles;

2 (III) syringes; and

3 (IV) scalpel blades.

4 (B) The definition of medical and infectious waste does not include:

5 (i) hazardous waste identified or listed under 40 CFR Part 261;

6 (ii) household waste, as defined in 40 CFR 261.4(b)(1);

7 (iii) ash from incineration of medical and infectious waste, once the incineration  
8 process has been completed;

9 (iv) human corpses, remains, and anatomical parts that are intended for interment or  
10 cremation; and

11 (v) domestic sewage materials identified in 40 CFR 261.4(a)(1).

12 ~~(17)~~(10) "Medium HMIWI" means:

13 (A) a HMIWI whose maximum design waste burning capacity is more than 200 pounds per  
14 hour but less than or equal to 500 pounds per hour;

15 (B) a continuous or intermittent HMIWI whose maximum charge rate is more than 200 pounds  
16 per hour but less than or equal to 500 pounds per hour; or

17 (C) a batch HMIWI whose maximum charge rate is more than 1,600 pounds per day but less  
18 than or equal to 4,000 pounds per day.

19 ~~(18)~~—"Municipal waste combustor (MWC) or municipal waste combustor unit" means a municipal waste  
20 combustor as defined in 40 CFR 60.51b.

21 ~~(19)~~—"Municipal waste combustor plant" means one or more designated units at the same location.

22 ~~(20)~~—"Municipal waste combustor unit capacity" means the maximum charging rate of a municipal waste  
23 combustor unit expressed in tons per day of municipal solid waste combusted, calculated according  
24 to the procedures under 40 CFR 60.58b(j). Section 60.58b(j) includes procedures for determining  
25 municipal waste combustor unit capacity for continuous and batch feed municipal waste  
26 combustors.

27 ~~(21)~~—"Municipal type solid waste (MSW) or Municipal Solid Waste" means municipal type solid waste  
28 defined in 40 CFR 60.51b.

29 ~~(22)~~(11) "POTW" means a publicly owned treatment works as defined in 40 CFR 501.2.

30 ~~(23)~~—"Other solid waste incineration unit" or "OSWI unit" means either a very small municipal waste  
31 combustion unit or an institutional waste incineration unit, as defined in this Paragraph.

32 ~~(24)~~—"Same Location" means the same or contiguous property that is under common ownership or control  
33 including properties that are separated only by a street, road, highway, or other public right of way.  
34 Common ownership or control includes properties that are owned, leased, or operated by the same  
35 entity, parent entity, subsidiary, subdivision, or any combination thereof including any municipality  
36 or other governmental unit, or any quasi governmental authority (e.g., a public utility district or  
37 regional waste disposal authority).

1 ~~(25)~~ "Sewage sludge incinerator" means any incinerator regulated under 40 CFR Part 503, Subpart E.

2 ~~(12)~~ "Sewage sludge" means solid, semi-solid, or liquid residue generated during the treatment of  
3 domestic sewage in a treatment works as defined in 40 CFR 60.5250. Sewage sludge includes, but  
4 is not limited to, domestic septage; scum or solids removed in primary, secondary, or advanced  
5 wastewater treatment processes; and a material derived from sewage sludge. Sewage sludge does  
6 not include ash generated during the firing of sewage sludge in a sewage sludge incineration unit or  
7 grit and screenings generated during preliminary treatment of domestic sewage in a treatment works.

8 ~~(13)~~ "Sewage sludge incineration (SSI) unit" means an incineration unit combusting sewage sludge for  
9 the purpose of reducing the volume of the sewage sludge by removing combustible matter as defined  
10 in 40 CFR 60.5250.

11 ~~(26)~~ "Sludge incinerator" means any incinerator regulated under Rule .1110 of this Subchapter but not  
12 under 40 CFR Part 503, Subpart E.

13 ~~(27)~~(14) "Small HMIWI" means:

14 (A) a HMIWI whose maximum design waste burning capacity is less than or equal to 200  
15 pounds per hour;

16 (B) a continuous or intermittent HMIWI whose maximum charge rate is less than or equal to  
17 200 pounds per hour; or

18 (C) a batch HMIWI whose maximum charge rate is less than or equal to 1,600 pounds per day.

19 ~~(28)~~ "Small municipal waste combustor" means each municipal waste combustor unit with a combustion  
20 capacity that is greater than 11 tons per day but not more than 250 tons per day of municipal solid  
21 waste.

22 ~~(29)~~(15) "Small remote HMIWI" means any small HMIWI which is located more than 50 miles from the  
23 boundary of the nearest Standard Metropolitan Statistical Area (SMSA) and which burns less than  
24 2,000 pounds per week of hospital, medical and infectious waste. The 2,000 pound per week  
25 limitation does not apply during performance tests.

26 ~~(16)~~ "Solid waste" means the term solid waste as defined in 40 CFR 241.2.

27 ~~(30)~~(17) "Standard Metropolitan Statistical Area (SMSA)" means any area listed in Office of Management  
28 and Budget (OMB) Bulletin No. 93-17, entitled "Revised Statistical Definitions for Metropolitan  
29 Areas" dated July 30, 1993. The referenced document cited by this Item is hereby incorporated by  
30 reference and does not include subsequent amendments or editions. A copy of this document may  
31 be obtained from the Division of Air Quality, P.O. Box 29580, Raleigh, North Carolina 27626-0580  
32 at a cost of 10 cents (\$0.10) per page or may be obtained through the internet at  
33 <http://www.census.gov/population/estimates/metro-city/93mfips.txt>.

34 ~~(31)~~ "Very small municipal waste combustion unit" means any municipal waste combustion unit that has  
35 the capacity to combust less than 35 tons per day of municipal solid waste or refuse-derived fuel, as  
36 determined by the calculations in 40 CFR 60.3076.

1 (b) Whenever reference is made to the Code of Federal Regulations in this Section, the definition in the Code of  
2 Federal Regulations shall apply unless specifically stated otherwise in a particular rule. The Code of Federal  
3 Regulations is available in electronic form free of charge at <https://www.gpo.gov/fdsys/search/home.action>.  
4

5 *History Note: Authority G.S. 143-213; 143-215.3(a)(1);*  
6 *Eff. October 1, 1991;*  
7 *Amended Eff. July 1, 2000; July 1, 1999; July 1, 1998; July 1, 1996; April 1, 1995;*  
8 *December 1, 1993;*  
9 *Temporary Amendment Eff. March 1, 2002;*  
10 *Amended Eff. July 1, 2007; August 1, ~~2002-2002~~;*  
11 *Readopted Eff. \_\_\_\_\_.*  
12  
13

1 15A NCAC 02D .1203 is proposed for readoption as a repeal as follows:

2  
3 **15A NCAC 02D .1203 HAZARDOUS WASTE INCINERATORS**

4 ~~(a) Applicability. This Rule applies to hazardous waste incinerators.~~

5 ~~(b) Definitions. For the purpose of this Rule, the definitions contained in 40 CFR 260.10, 270.2, and 40 CFR 63.1201 shall apply in addition to the definitions in Rule .1202 of this Section.~~

6  
7 ~~(c) Emission Standards.~~

8 ~~(1) The emission standards in this Paragraph apply to all incinerators subject to this Rule except where~~  
9 ~~Rule .0524, .1110, or .1111 of this Subchapter applies. However, when Subparagraphs (8) or (9) of~~  
10 ~~this Paragraph or Paragraph (h) of this Rule and Rules .0524, .1110, or .1111 of this Subchapter~~  
11 ~~regulate the same pollutant, the more restrictive provision for each pollutant shall apply,~~  
12 ~~notwithstanding provisions of Rules .0524, .1110, or .1111 of this Subchapter to the contrary.~~

13 ~~(2) Particulate Matter. Any incinerator subject to this Rule shall meet the particulate matter emission~~  
14 ~~requirements of 40 CFR 264.343(c).~~

15 ~~(3) Visible Emissions. Any incinerator subject to this Rule shall comply with Rule .0521 of this~~  
16 ~~Subchapter for the control of visible emissions.~~

17 ~~(4) Sulfur Dioxide. Any incinerator subject to this Rule shall comply with Rule .0516 of this Subchapter~~  
18 ~~for the control of sulfur dioxide emissions.~~

19 ~~(5) Odorous Emissions. Any incinerator subject to this Rule shall comply with Rule .1806 of this~~  
20 ~~Subchapter for the control of odorous emissions.~~

21 ~~(6) Hydrogen Chloride. Any incinerator subject to this Rule shall meet the hydrogen chloride emission~~  
22 ~~requirements of 40 CFR 264.343(b). Compliance with this Subparagraph shall be determined by~~  
23 ~~averaging emissions over a one-hour period.~~

24 ~~(7) Mercury Emissions. The emissions of mercury and mercury compounds from the stack or chimney~~  
25 ~~of any incinerator subject to this Rule shall not exceed 0.032 pounds per hour. Compliance with this~~  
26 ~~Subparagraph shall be determined by averaging emissions over a one-hour period.~~

27 ~~(8) Toxic Emissions. The owner or operator of any incinerator subject to this Rule shall demonstrate~~  
28 ~~compliance with Section .1100 of this Subchapter according to 15A NCAC 02Q .0700 for the~~  
29 ~~control of toxic emissions.~~

30 ~~(9) Ambient Standards.~~

31 ~~(A) In addition to the ambient air quality standards in Section .0400 of this Subchapter, the~~  
32 ~~following ambient air quality standards, which are an annual average, in milligrams per~~  
33 ~~cubic meter at 77 degrees F (25 degrees C) and 29.92 inches (760 mm) of mercury pressure~~  
34 ~~and which are increments above background concentrations, shall apply aggregately to all~~  
35 ~~incinerators at a facility subject to this Rule:~~

36 ~~(i) arsenic and its compounds  $2.3 \times 10^{-7}$~~

37 ~~(ii) beryllium and its compounds  $4.1 \times 10^{-6}$~~

1 (iii) ~~cadmium and its compounds~~ ~~5.5x10<sup>-6</sup>~~

2 (iv) ~~chromium (VI) and its compounds~~ ~~8.3x10<sup>-8</sup>~~

3 (B) ~~The owner or operator of a facility with incinerators subject to this Rule shall demonstrate~~  
4 ~~compliance with the ambient standards in Subparts (i) through (iv) of Part (A) of this~~  
5 ~~Subparagraph by following the procedures set out in Rule .1106 of this Subchapter.~~  
6 ~~Modeling demonstrations shall comply with the requirements of Rule .0533 of this~~  
7 ~~Subchapter.~~

8 (C) ~~The emission rates computed or used under Part (B) of this Subparagraph that demonstrate~~  
9 ~~compliance with the ambient standards under Part (A) of this Subparagraph shall be~~  
10 ~~specified as a permit condition for the facility with incinerators subject to this Rule as their~~  
11 ~~allowable emission limits unless Rules .0524, .1110, or .1111 of this Subchapter requires~~  
12 ~~more restrictive rates.~~

13 ~~(d) Operational Standards.~~

14 (1) ~~The operational standards in this Rule do not apply to any incinerator subject to this Rule when~~  
15 ~~applicable operational standards in Rules .0524, .1110, or .1111 of this Subchapter apply.~~

16 (2) ~~Hazardous waste incinerators shall comply with 15A NCAC 13A .0101 through .0119, which are~~  
17 ~~administered and enforced by the Division of Waste Management.~~

18 ~~(e) Test Methods and Procedures.~~

19 (1) ~~The test methods and procedures described in Section .2600 of this Subchapter and in 40 CFR Part~~  
20 ~~60 Appendix A and 40 CFR Part 61 Appendix B shall be used to determine compliance with~~  
21 ~~emission rates. Method 29 of 40 CFR Part 60 shall be used to determine emission rates for metals.~~  
22 ~~However, Method 29 shall be used to sample for chromium (VI), and SW 846 Method 0060 shall~~  
23 ~~be used for the analysis.~~

24 (2) ~~The Director may require the owner or operator to test his incinerator to demonstrate compliance~~  
25 ~~with the emission standards listed in Paragraph (c) of this Rule.~~

26 ~~(f) Monitoring, Recordkeeping, and Reporting.~~

27 (1) ~~The owner or operator of an incinerator subject to the requirements of this Rule shall comply with~~  
28 ~~the monitoring, recordkeeping, and reporting requirements in Section .0600 of this Subchapter, 40~~  
29 ~~CFR 270.31, and 40 CFR 264.347.~~

30 (2) ~~The owner or operator of an incinerator subject to the requirements of this Rule shall maintain and~~  
31 ~~operate a continuous temperature monitoring and recording device for the primary chamber and,~~  
32 ~~where there is a secondary chamber, for the secondary chamber. The owner or operator of an~~  
33 ~~incinerator that has installed air pollution abatement equipment to reduce emissions of hydrogen~~  
34 ~~chloride shall install, operate, and maintain continuous monitoring equipment to measure pH for~~  
35 ~~wet scrubber systems and rate of alkaline injection for dry scrubber systems. The Director shall~~  
36 ~~require the owner or operator of an incinerator with a permitted charge rate of 750 pounds per hour~~  
37 ~~or more to install, operate, and maintain continuous monitors for oxygen or for carbon monoxide or~~

1           ~~both as necessary to determine proper operation of the incinerator. The Director may require the~~  
2           ~~owner or operator of an incinerator with a permitted charge rate of less than 750 pounds per hour to~~  
3           ~~install, operate, and maintain monitors for oxygen or for carbon monoxide or both as necessary to~~  
4           ~~determine proper operation of the incinerator.~~

5           ~~(g) Excess Emissions and Start up and Shut down. All incinerators subject to this Rule shall comply with Rule .0535,~~  
6           ~~Excess Emissions Reporting and Malfunctions, of this Subchapter.~~

7           ~~(h) Incinerators subject to this Rule shall comply with the emission limits, operational specifications, and other~~  
8           ~~restrictions or conditions determined by the Division of Waste Management under 40 CFR 270.32, establishing~~  
9           ~~Resource Conservation and Recovery Act permit conditions, as necessary to protect human health and the~~  
10          ~~environment.~~

11  
12          *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5);*  
13                           *Eff. October 1, 1991;*  
14                           *Amended Eff. June 1, 2008; August 1, 2002; July 1, 2000; July 1, 1999; July 1, 1998; April 1,*  
15                           *1995-1995;*  
16                           *Repealed Eff. \_\_\_\_\_.*

1 15A NCAC 02D .1205 is proposed for readoption as a repeal as follows:

2  
3 **15A NCAC 02D .1205 LARGE MUNICIPAL WASTE COMBUSTORS**

4 ~~(a) Applicability. This Rule applies to large municipal waste combustors as defined in Rule .1202 of this Section.~~

5 ~~(b) Definitions. For the purpose of this Rule, the definitions contained in 40 CFR 60.31b (except administrator means~~  
6 ~~the Director of the Division of Air Quality) apply in addition to the definitions in Rule .1202 of this Section.~~

7 ~~(c) Emission Standards.~~

8 ~~(1) The emission standards in this Paragraph apply to any municipal waste combustor subject to the~~  
9 ~~requirements of this Rule except where Rule .0524, .1110, or .1111 of this Subchapter applies.~~  
10 ~~However, when Subparagraphs (13) or (14) of this Paragraph and Rule .0524, .1110, or .1111 of~~  
11 ~~this Subchapter regulate the same pollutant, the more restrictive provision for each pollutant apply,~~  
12 ~~notwithstanding provisions of Rules .0524, .1110, or .1111 of this Subchapter to the contrary.~~

13 ~~(2) Particulate Matter. Emissions of particulate matter from each municipal waste combustor shall not~~  
14 ~~exceed 25 milligrams per dry standard cubic meter corrected to seven percent oxygen.~~

15 ~~(3) Visible Emissions. The emission limit for opacity from any municipal waste combustor shall not~~  
16 ~~exceed 10 percent (6 minute average).~~

17 ~~(4) Sulfur Dioxide. Emissions of sulfur dioxide from each municipal waste combustor shall be reduced~~  
18 ~~by at least 75 percent by weight or volume or to no more than 29 parts per million by volume,~~  
19 ~~whichever is less stringent. Percent reduction shall be determined from continuous emissions~~  
20 ~~monitoring data and according to Reference Method 19, Section 12.5.4 of 40 CFR Part 60 Appendix~~  
21 ~~A 7. Compliance with either standard is based on a 24 hour daily block geometric average of~~  
22 ~~concentration data corrected to seven percent oxygen (dry basis).~~

23 ~~(5) Nitrogen Oxide. Emissions of nitrogen oxides from each municipal waste combustor shall not~~  
24 ~~exceed the emission limits in Table 1 to Subpart Cb of Part 60 "Nitrogen Oxide Guidelines for~~  
25 ~~Designated Facilities." Nitrogen oxide emissions averaging is allowed as specified in 40 CFR~~  
26 ~~60.33b(d)(1)(i) through (d)(1)(v). If nitrogen oxide emissions averaging is used, the emissions shall~~  
27 ~~not exceed Table 2 to Subpart Cb of Part 60 "Nitrogen Oxides Limits for Existing Designated~~  
28 ~~Facilities Included in an Emission Averaging Plan at a Municipal Waste Combustor Plant."~~

29 ~~(6) Odorous Emissions. Each municipal waste combustor shall comply with Rule .1806 of this~~  
30 ~~Subchapter for the control of odorous emissions.~~

31 ~~(7) Hydrogen Chloride. Emissions of hydrogen chloride from each municipal waste combustor shall~~  
32 ~~be reduced by at least 95 percent (simultaneously at the inlet and outlet data sets with a minimum~~  
33 ~~of three valid test periods, the length of each test period shall be a minimum of one hour); or shall~~  
34 ~~not exceed, as determined by Reference Method 26 or 26A of 40 CFR Part 60 Appendix A 8, more~~  
35 ~~than 29 parts per million volume, whichever is less stringent. Compliance with this Subparagraph~~  
36 ~~shall be determined by averaging emissions over three 1 hour test runs, with paired data sets for~~  
37 ~~percent reduction and correction to seven percent oxygen (dry basis).~~



- 1 ~~(8) Mercury Emissions. Emissions of mercury from each municipal waste combustor shall be reduced~~  
2 ~~by at least 85 percent by weight of potential mercury emissions (simultaneously at the inlet and~~  
3 ~~outlet data sets with a minimum of three valid test periods, the length of each test period shall be a~~  
4 ~~minimum of one hour); or shall not exceed, as determined by Reference Method 29 of 40 CFR Part~~  
5 ~~60 Appendix A 8 or ASTM D6784-02 (Ontario Hydro method), more than 50 micrograms per dry~~  
6 ~~standard cubic meter, whichever is less stringent. Compliance with this Subparagraph shall be~~  
7 ~~determined by averaging emissions over three 1-hour test runs corrected to seven percent oxygen~~  
8 ~~(dry basis).~~
- 9 ~~(9) Lead Emissions. Emissions of lead from each municipal waste combustor shall not exceed, as~~  
10 ~~determined by Reference Method 29 of 40 CFR Part 60 Appendix A 8, 400 micrograms per dry~~  
11 ~~standard cubic meter and corrected to seven percent oxygen.~~
- 12 ~~(10) Cadmium Emissions. Emissions of cadmium from each municipal waste combustor shall not~~  
13 ~~exceed, as determined by Reference Method 29 of 40 CFR Part 60 Appendix A 8, 35 micrograms~~  
14 ~~per dry standard cubic meter and corrected to seven percent oxygen.~~
- 15 ~~(11) Dioxins and Furans. Emissions of dioxins and furans from each municipal waste combustor:~~  
16 ~~(A) that employs an electrostatic precipitator based emission control system, shall not exceed~~  
17 ~~35 nanograms per dry standard cubic meter (total mass dioxins and furans).~~  
18 ~~(B) that does not employ an electrostatic precipitator based emission control system, shall not~~  
19 ~~exceed 30 nanograms per dry standard cubic meter (total mass dioxins and furans).~~  
20 ~~Compliance with this Subparagraph shall be determined by averaging emissions over three~~  
21 ~~test runs with a minimum of four hour duration per test run, performed in accordance with~~  
22 ~~Reference Method 23 of 40 CFR Part 60 Appendix A 7, and corrected to seven percent~~  
23 ~~oxygen.~~
- 24 ~~(12) Fugitive Ash.~~  
25 ~~(A) On or after the date on which the initial performance test is completed, no owner or operator~~  
26 ~~of a municipal waste combustor shall cause to be discharged to the atmosphere visible~~  
27 ~~emissions of combustion ash from an ash conveying system (including conveyor transfer~~  
28 ~~points) in excess of five percent of the observation period (i.e., nine minutes per three hour~~  
29 ~~block period), as determined by visible emission observations using Reference Method 22~~  
30 ~~of 40 CFR 60 Appendix A 7, except as provided in Part (B) of this Subparagraph.~~  
31 ~~Compliance with this Part shall be determined from at least three one-hour observation~~  
32 ~~periods when the facility transfers ash from the municipal waste combustor to the area~~  
33 ~~where the ash is stored or loaded into containers or trucks.~~  
34 ~~(B) The emission limit specified in Part (A) of this Subparagraph covers visible emissions~~  
35 ~~discharged to the atmosphere from buildings or enclosures, not the visible emissions~~  
36 ~~discharged inside of the building or enclosures, of ash conveying systems.~~

1 ~~(13) Toxic Emissions. The owner or operator of a municipal waste combustor shall demonstrate~~  
2 ~~compliance with Section .1100 of this Subchapter according to 15A NCAC 02Q .0700.~~

3 ~~(14) Ambient Standards.~~

4 ~~(A) In addition to the ambient air quality standards in Section .0400 of this Subchapter, the~~  
5 ~~following are annual average ambient air quality standards in milligrams per cubic meter~~  
6 ~~at 77 degrees F (25 degrees C) and 29.92 inches (760 mm) of mercury pressure:~~

7 ~~(i) arsenic and its compounds 2.3x10<sup>-7</sup>~~

8 ~~(ii) beryllium and its compounds 4.1x10<sup>-6</sup>~~

9 ~~(iii) cadmium and its compounds 5.5x10<sup>-6</sup>~~

10 ~~(iv) chromium (VI) and its compounds 8.3x10<sup>-8</sup>~~

11 ~~These are increments above background concentrations and apply aggregately to all~~  
12 ~~municipal waste combustors at a facility subject to this Rule.~~

13 ~~(B) The owner or operator of a facility with municipal waste combustors shall demonstrate~~  
14 ~~compliance with the ambient standards in Subparts (i) through (iv) of Part (A) of this~~  
15 ~~Subparagraph by following the procedures set out in Rule .1106 of this Subchapter.~~  
16 ~~Modeling demonstrations shall comply with the good engineering practice stack height~~  
17 ~~requirements of Rule .0533 of this Subchapter.~~

18 ~~(C) The emission rates computed or used under Part (B) of this Subparagraph that demonstrate~~  
19 ~~compliance with the ambient standards under Part (A) of this Subparagraph shall be~~  
20 ~~specified as a permit condition for the facility with municipal waste combustors as their~~  
21 ~~allowable emission limits unless Rule .0524, .1110, or .1111 of this Subchapter requires~~  
22 ~~more restrictive rates.~~

23 ~~(15) The emission standards of Subparagraphs (1) through (14) of this Paragraph apply at all times except~~  
24 ~~during periods of municipal waste combustor startup, shutdown, or malfunction that last no more~~  
25 ~~than three hours.~~

26 ~~(d) Operational Standards.~~

27 ~~(1) The operational standards in this Rule do not apply to any municipal waste combustor when~~  
28 ~~applicable operational standards in Rule .0524, .1110, or .1111 of this Subchapter apply.~~

29 ~~(2) Each municipal waste combustor shall meet the following operational standards:~~

30 ~~(A) The concentration of carbon monoxide at the municipal waste combustor outlet shall not~~  
31 ~~exceed the applicable emissions level contained in Table 3 to Subpart Cb of Part 60~~  
32 ~~"Municipal Waste Combustor Operating Guidelines."~~

33 ~~(B) The load level shall not exceed 110 percent of the maximum demonstrated municipal waste~~  
34 ~~combustor load determined from the highest 4 hour block arithmetic average achieved~~  
35 ~~during four consecutive hours in the course of the most recent dioxins and furans stack test~~  
36 ~~that demonstrates compliance with the emission limits of Paragraph (c) of this Rule.~~

1 ~~(C) — The combustor operating temperature measured at the particulate matter control device~~  
2 ~~inlet shall not exceed 63 degrees F above the maximum demonstrated particulate matter~~  
3 ~~control device temperature from the highest 4 hour block arithmetic average measured at~~  
4 ~~the inlet of the particulate matter control device during four consecutive hours in the course~~  
5 ~~of the most recent dioxins and furans stack test that demonstrates compliance with the~~  
6 ~~emission limits of Paragraph (c) of this Rule.~~

7 ~~(D) — The owner or operator of a municipal waste combustor with activated carbon control~~  
8 ~~system to control dioxins and furans or mercury emissions shall maintain an eight hour~~  
9 ~~block average carbon feed rate at or above the highest average level established during the~~  
10 ~~most recent dioxins and furans or mercury test.~~

11 ~~(E) — The owner or operator of a municipal waste combustor is exempted from limits on load~~  
12 ~~level, temperature at the inlet of the particular matter control device, and carbon feed rate~~  
13 ~~during:~~

14 ~~(i) — the annual tests for dioxins and furans;~~

15 ~~(ii) — the annual mercury tests for carbon feed requirements only;~~

16 ~~(iii) — the two weeks preceding the annual tests for dioxins and furans;~~

17 ~~(iv) — the two weeks preceding the annual mercury tests (for carbon feed rate~~  
18 ~~requirements only); and~~

19 ~~(v) — any activities to improve the performance of the municipal waste combustor or its~~  
20 ~~emission control including performance evaluations and diagnostic or new~~  
21 ~~technology testing.~~

22 ~~The municipal waste combustor load limit continues to apply and remains enforceable until~~  
23 ~~and unless the Director grants a waiver in writing.~~

24 ~~(F) — The limits on load level for a municipal waste combustor are waived when the Director~~  
25 ~~concludes that the emission control standards would not be exceeded based on test~~  
26 ~~activities to evaluate system performance, test new technology or control technology,~~  
27 ~~perform diagnostic testing, perform other activities to improve the performance; or perform~~  
28 ~~other activities to advance the state of the art for emissions controls.~~

29 ~~(3) — The operational standards of this Paragraph apply at all times except during periods of municipal~~  
30 ~~waste combustor startup, shutdown, or malfunction that last no more than three hours, with the~~  
31 ~~following exception: For the purpose of compliance with the carbon monoxide emission limits in~~  
32 ~~Subparagraph (2) of this Paragraph, if a loss of boiler water level control (e.g., boiler waterwall tube~~  
33 ~~failure) or a loss of combustion air control (e.g., loss of combustion air fan, induced draft fan,~~  
34 ~~combustion grate bar failure) is determined to be a malfunction according to 15A NCAC 02D .0535,~~  
35 ~~the duration of the malfunction period is limited to 15 hours per occurrence. During such periods~~  
36 ~~of malfunction, monitoring data shall be dismissed or excluded from compliance calculations, but~~  
37 ~~shall be recorded and reported in accordance with the provisions of Paragraph (f) of this Rule.~~

1 ~~(e) Test Methods and Procedures.~~

- 2 ~~(1) The test methods and procedures described in Section .2600 of this Subchapter and in Parts (A)~~  
3 ~~through (K) in this Subparagraph shall be used to demonstrate compliance:~~
- 4 ~~(A) 40 CFR 60.58b(b) for continuous emissions monitoring of oxygen or carbon monoxide at~~  
5 ~~each location where carbon monoxide, sulfur dioxide, or nitrogen oxides are monitored;~~
  - 6 ~~(B) 40 CFR 60.58b(c) for determination of compliance with particulate and opacity emission~~  
7 ~~limits. The data from the continuous opacity monitoring system shall not be used to~~  
8 ~~determine compliance with the opacity limit.~~
  - 9 ~~(C) 40 CFR 60.58b(d) for determination of compliance with emission limits for cadmium, lead~~  
10 ~~and mercury;~~
  - 11 ~~(D) 40 CFR 60.58b(e) for determination of compliance with sulfur dioxide emission limits~~  
12 ~~from continuous emissions monitoring data;~~
  - 13 ~~(E) 40 CFR 60.58b(f) for determination of compliance with hydrogen chloride emission limits;~~
  - 14 ~~(F) 40 CFR 60.58b(g) for determination of compliance with dioxin/furan emission limits;~~
  - 15 ~~(G) 40 CFR 60.58b(h) for determination of compliance with nitrogen oxides limits from~~  
16 ~~continuous emission monitoring data;~~
  - 17 ~~(H) 40 CFR 60.58b(i) for determination of compliance with operating requirements under~~  
18 ~~Paragraph (d);~~
  - 19 ~~(I) 40 CFR 60.58b(j) for determination of municipal waste combustor capacity;~~
  - 20 ~~(J) 40 CFR 60.58b(k) for determination of compliance with the fugitive ash emission limit;~~  
21 ~~and~~
  - 22 ~~(K) 40 CFR 60.58b(m)(1) to determine parametric monitoring for carbon injection control~~  
23 ~~systems.~~
- 24 ~~(2) Method 29 of 40 CFR Part 60 Appendix A 8 shall be used to determine emission rates for metals.~~  
25 ~~However, Method 29 shall be used only to collect sample for chromium (VI), and SW 846 Method~~  
26 ~~0060 shall be used for the analysis.~~
- 27 ~~(3) The owner or operator shall conduct initial stack tests to measure the emission levels of dioxins and~~  
28 ~~furans, cadmium, lead, mercury, beryllium, arsenic, chromium (VI), particulate matter, opacity,~~  
29 ~~hydrogen chloride, and fugitive ash. Annual stack tests for the same pollutants except beryllium,~~  
30 ~~arsenic, and chromium (VI) shall be conducted no less than 9 months and no more than 15 months~~  
31 ~~since the previous test and must complete five performance tests in each 5 year calendar period.~~
- 32 ~~(4) The testing frequency for dioxin and furan may be reduced to the alternative testing schedule~~  
33 ~~specified in 40 CFR 60.58b(g)(5)(iii) if the owner or operator notifies the Director of the intent to~~  
34 ~~begin the reduced dioxin and furan performance testing schedule during the following calendar year.~~
- 35 ~~(5) The owner or operator of an affected facility may request that compliance with the dioxin and furan~~  
36 ~~emission limit be determined using carbon dioxide measurements corrected to an equivalent of~~  
37 ~~seven percent oxygen. The relationship between oxygen and carbon dioxide levels for the affected~~

1 facility shall be established as specified in 40 CFR 60.58b(b)(6). The Director will approve the  
2 request after verification of the correct calculations that provides the relationship between oxygen  
3 and carbon dioxide levels and of the completeness of stack test data used to establish the relationship  
4 between oxygen and carbon dioxide levels.

5 (6) The Director may require the owner or operator of any municipal waste combustor subject to this  
6 Rule to test his municipal waste combustor to demonstrate compliance with the emission standards  
7 in Paragraph (c) of this Rule.

8 ~~(f) Monitoring, Recordkeeping, and Reporting.~~

9 (1) The owner or operator of a municipal waste combustor shall comply with the monitoring,  
10 recordkeeping, and reporting requirements in Section .0600 of this Subchapter.

11 (2) The owner or operator of a municipal waste combustor that has installed air pollution abatement  
12 equipment to reduce emissions of hydrogen chloride shall install, operate, and maintain continuous  
13 monitoring equipment to measure pH for wet scrubber systems and rate of alkaline injection for dry  
14 scrubber systems.

15 (3) The owner or operator of a municipal waste combustor shall:

16 (A) install, calibrate, operate, and maintain, for each municipal waste combustor, continuous  
17 emission monitors to determine:

18 (i) sulfur dioxide concentration;

19 (ii) nitrogen oxides concentration;

20 (iii) oxygen or carbon dioxide concentration;

21 (iv) opacity according to 40 CFR 60.58b(c); and

22 (v) carbon monoxide at the combustor outlet and record the output of the system and  
23 shall follow the procedures and methods specified in 40 CFR 60.58b(i)(3);

24 (B) monitor the load level of each municipal waste combustor according to 40 CFR  
25 60.58b(i)(6);

26 (C) monitor the temperature of each municipal waste combustor flue gases at the inlet of the  
27 particulate matter air pollution control device according to 40 CFR 60.58b(i)(7);

28 (D) monitor carbon feed rate of each municipal waste combustor carbon delivery system and  
29 total plant predicted quarterly usage if activated carbon is used to abate dioxins and furans  
30 or mercury emissions according to 40 CFR 60.58b(m)(2) and (m)(3);

31 (E) maintain records of the information listed in 40 CFR 60.59b(d)(1) through (d)(15) for a  
32 period of at least five years;

33 (F) following the first year of municipal combustor operation, submit an annual report  
34 specified in 40 CFR 60.59b(g) for municipal waste combustors no later than February 1 of  
35 each year following the calendar year in which the data were collected. Once the municipal  
36 waste combustor is subject to permitting requirements under 15A NCAC 02Q .0500, Title

1 ~~V Procedures, the owner or operator of an affected facility shall submit these reports~~  
2 ~~semiannually; and~~

3 ~~(G) — submit a semiannual report specified in 40 CFR 60.59b(h) for each municipal waste~~  
4 ~~combustor for any recorded pollutant or parameter that does not comply with the pollutant~~  
5 ~~or parameter limit specified in this Section, according to the schedule specified in 40 CFR~~  
6 ~~60.59b(h)(6).~~

7 ~~(g) Excess Emissions and Start up and Shut down. All municipal waste combustors shall comply with Rule .0535,~~  
8 ~~Excess Emissions Reporting and Malfunctions, of this Subchapter.~~

9 ~~(h) Operator Certification.~~

10 ~~(1) — Each facility operator and shift supervisor shall have completed full certification or scheduled a full~~  
11 ~~certification exam with the American Society of Mechanical Engineers (ASME QRO 1 1994).~~

12 ~~(2) — The requirement to complete full certification or schedule a full certification exam with the~~  
13 ~~American Society of Mechanical Engineers (ASME QRO 1 1994) does not apply to chief facility~~  
14 ~~operators, shift supervisors, and control room operators who have obtained full certification from~~  
15 ~~the American Society of Mechanical Engineers on or before July 1, 1998.~~

16 ~~(3) — No owner or operator of an affected facility shall allow the facility to be operated at any time unless~~  
17 ~~one of the following persons is on duty and at the affected facility;~~

18 ~~(A) — a fully certified chief facility operator;~~

19 ~~(B) — a provisionally certified chief facility operator who is scheduled to take the full certification~~  
20 ~~exam within six months;~~

21 ~~(C) — a fully certified shift supervisor; or~~

22 ~~(D) — a provisionally certified shift supervisor who is scheduled to take the full certification exam~~  
23 ~~within six months.~~

24 ~~(4) — Operator Substitution~~

25 ~~(A) — A provisionally certified control room operator may perform the duties of the certified~~  
26 ~~chief facility operator or certified shift supervisor if both are off site for 12 hours or less~~  
27 ~~and no other certified operator is on site.~~

28 ~~(B) — If the certified chief facility operator and certified shift supervisor are both off site for~~  
29 ~~longer than 12 hours but for two weeks or less, then the owner or operator of the affected~~  
30 ~~facility must record the period when the certified chief facility operator and certified shift~~  
31 ~~supervisor are off site and include that information in the annual report as specified under~~  
32 ~~60.59b(g)(5).~~

33 ~~(C) — If the certified chief facility operator and certified shift supervisor are off site for more than~~  
34 ~~two weeks, and no other certified operator is on site, the provisionally certified control~~  
35 ~~room operator may perform the duties of the certified chief facility operator or certified~~  
36 ~~shift supervisor. However, the owner or operator of the affected facility must notify the~~  
37 ~~Director in writing and state what caused the absence and actions are being taken to ensure~~

1                   that a certified chief facility operator or certified shift supervisor is on site as expeditiously  
2                   as practicable. The notice shall be delivered within 30 days of the start date of when the  
3                   provisionally certified control room operator takes over the duties of the certified chief  
4                   facility operator or certified shift supervisor. A status report and corrective action summary  
5                   shall be submitted to the Director every four weeks following the initial notification.

6                   (D) — If the Director provides notice that the status report or corrective action summary is  
7                   disapproved, the municipal waste combustor may continue operation for 90 days, but then  
8                   must cease operation. If corrective actions are taken in the 90 day period such that the  
9                   Director withdraws the disapproval, municipal waste combustor operation may continue.

10                  (E) — The Director shall disapprove the status report or corrective action summary report,  
11                  described in Part (C) of this Subparagraph, if operating permit requirements are not being  
12                  met, the status and corrective action reports indicate that the effort to have a certified chief  
13                  facility operator or certified shift supervisor on site as expeditiously as practicable is not  
14                  being met, or the reports are not delivered in a timely manner.

15                  (5) — A provisionally certified operator who is newly promoted or recently transferred to a shift supervisor  
16                  position or a chief facility operator position at the municipal waste combustion facility may perform  
17                  the duties of the certified chief facility operator or certified shift supervisor without notice to, or  
18                  approval by, the Director for up to six months before taking the ASME QRO Certification for  
19                  Municipal Solid Waste Combustion Facilities Operators.

20                  (6) — If the certified chief facility operator and certified shift supervisor are both unavailable, a  
21                  provisionally certified control room operator who is scheduled to take the full certification exam,  
22                  may fulfill the requirements of this Subparagraph.

23                  The referenced ASME exam (ASME QRO 1 1994), "Standard for the Qualification and Certification of Resource  
24                  Recovery Facility Operators," in this Paragraph is hereby incorporated by reference and includes subsequent  
25                  amendments and editions. Copies of the referenced ASME exam may be obtained from the American Society of  
26                  Mechanical Engineers (ASME), 22 Law Drive, Fairfield, NJ 07007, at a cost of forty nine dollars (\$49.00).

27                  (i) Training.

28                  (1) — The owner or operator of each municipal waste combustor shall develop and update on a yearly  
29                  basis a site specific operating manual that shall address the elements of municipal waste combustor  
30                  operation specified in 40 CFR 60.54b(e)(1) through (e)(11). The operating manual shall be kept in  
31                  a readily accessible location for all persons required to undergo training under Subparagraph (2) of  
32                  this Paragraph. The operating manual and records of training shall be available for inspection by the  
33                  personnel of the Division on request.

34                  (2) — The owner or operator of the municipal waste combustor plant shall establish a training program to  
35                  review the operating manual according to the schedule specified in Parts (A) and (B) of this  
36                  Subparagraph with each person who has responsibilities affecting the operation of the facility

1 including chief facility operators, shift supervisors, control room operators, ash handlers,  
2 maintenance personnel, and crane and load handlers:

3 (A) — A date prior to the day when the person assumes responsibilities affecting municipal waste  
4 combustor operation; and

5 (B) — Annually, following the initial training required by Part (A) of this Subparagraph.

6  
7 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3),(4),(5); 40 CFR 60.35b; 40 CFR 60.34e; 40  
8 CFR 60.1515;  
9 Eff. October 1, 1991;  
10 Amended Eff. July 1, 2000; July 1, 1999; July 1, 1998; July 1, 1996; April 1, 1995;  
11 Temporary Amendment Eff. March 1, 2002;  
12 Amended Eff. August 1, 2002;  
13 Temporary Amendment Eff. March 1, 2003;  
14 Temporary Amendment Expired December 12, 2003;  
15 Amended Eff. July 1, 2010; April 1, ~~2004~~.2004;  
16 Repealed Eff. \_\_\_\_\_.



1 15A NCAC 02D .1206 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02D .1206 HOSPITAL, MEDICAL, AND INFECTIOUS WASTE INCINERATORS**

4 (a) Applicability. This Rule applies to any hospital, medical, and infectious waste incinerator (HMIWI), except:

- 5 (1) any HMIWI required to have a permit ~~under~~ pursuant to Section 3005 of the Solid Waste Disposal  
6 Act;
- 7 (2) any pyrolysis unit;
- 8 (3) any cement kiln firing hospital waste or medical and infectious waste;
- 9 (4) any physical or operational change made to an existing HMIWI solely for the purpose of complying  
10 with the emission standards for HMIWIs in this Rule. These physical or operational changes are not  
11 considered a modification and do not result in an existing HMIWI becoming subject to the  
12 provisions of 40 CFR Part 60, Subpart Ec;
- 13 (5) any HMIWI during periods when only pathological waste, low-level radioactive waste, or  
14 chemotherapeutic waste is burned, provided that the owner or operator of the HMIWI:
- 15 (A) notifies the Director of an exemption claim; and
- 16 (B) keeps records on a calendar quarter basis of the periods of time when only pathological  
17 waste, low-level radioactive waste, or chemotherapeutic waste is burned; or
- 18 (6) any co-fired HMIWI, if the owner or operator of the co-fired HMIWI:
- 19 (A) notifies the Director of an exemption claim;
- 20 (B) provides an estimate of the relative weight of hospital, medical and infectious waste, and  
21 other fuels or wastes to be combusted; and
- 22 (C) keeps records on a calendar quarter basis of the weight of hospital, medical and infectious  
23 waste combusted, and the weight of all other fuels and wastes combusted at the co-fired  
24 HMIWI.

25 (b) Definitions. For the purpose of this Rule, the definitions contained in 40 CFR 60.51c shall apply in addition to  
26 the definitions in ~~Rule .1202 of this Section.~~ 15A NCAC 02D .1202.

27 (c) Emission Standards.

- 28 (1) The emission standards in this Paragraph apply to all HMIWIs ~~subject to this Rule~~ except where  
29 ~~Rules 15A NCAC 02D .0524, .1110, or .1111 of this Subchapter~~ applies. However, when  
30 Subparagraphs ~~(7)(6) or (8)(7)~~ of this Paragraph and Rules 15A NCAC 02D .0524, .1110, or .1111  
31 ~~of this Subchapter~~ regulate the same pollutant, the more restrictive provision for each pollutant shall  
32 apply, notwithstanding provisions of ~~Rules 15A NCAC 02D .0524, .1110, or .1111 of this~~  
33 ~~Subchapter~~ to the contrary;
- 34 ~~(2) Prior to July 1, 2013, each HMIWI for which construction was commenced on or before June 20,~~  
35 ~~1996, or for which modification is commenced on or before March 16, 1998, shall not exceed the~~  
36 ~~requirements listed in Table 1A of Subpart Ce of 40 CFR Part 60;~~

1 ~~(3)(2)~~ ~~On or after July 1, 2013, each~~ Each HMIWI for which construction was commenced on or before  
2 June 20, 1996, or for which modification is commenced on or before March 16, 1998, shall not  
3 exceed the requirements listed in Table 1B of Subpart Ce of 40 CFR Part 60;

4 ~~(4)(3)~~ Each HMIWI for which construction was commenced after June 20, 1996 but no later than  
5 December 1, 2008, or for which modification is commenced after March 16, 1998 but no later than  
6 April 6, 2010, shall not exceed the more stringent of the requirements listed in Table 1B of Subpart  
7 Ce and Table 1A of Subpart Ec of 40 CFR Part 60;

8 ~~(5)(4)~~ ~~Each small remote HMIWI for which construction was commenced on or before June 20, 1996, or~~  
9 ~~for which modification was commenced on or before March 16, 1998, and which burns less than~~  
10 ~~2,000 pounds per week of hospital waste and medical or infectious waste shall not exceed emission~~  
11 ~~standards listed in Table 2A of Subpart Ce of 40 CFR Part 60 before July 1, 2013. On or after July~~  
12 ~~1, 2013, each~~ Each small remote HMIWI shall not exceed emission standards listed in Table 2B of  
13 Subpart Ce of 40 CFR Part 60;

14 ~~(6)(5)~~ Visible Emissions. ~~Prior to July 1, 2013, the owner or operator of any HMIWI shall not cause to be~~  
15 ~~discharged into the atmosphere from the stack of the HMIWI any gases that exhibit greater than 10~~  
16 ~~percent opacity (6 minute block average). On or after July 1, 2013, the~~ The owner or operator of  
17 any HMIWI shall not cause to be discharged into the atmosphere from the stack of the HMIWI any  
18 gases that exhibit greater than six percent opacity ~~six minute~~ (six-minute block average);

19 ~~(7)(6)~~ Toxic Emissions. ~~Air Pollutants.~~ The owner or operator of any HMIWI subject to this Rule shall  
20 demonstrate compliance with ~~Section 15A NCAC 02D .1100 of this Subchapter~~ according to 15A  
21 NCAC 02Q .0700; and .0700.

22 ~~(7)~~ Ambient Standards.

23 ~~(A)~~ In addition to the ambient air quality standards in Section .0400 of this Subchapter, the  
24 following ambient air quality standards, which are an annual average, in milligrams per  
25 cubic meter at 77 degrees F (25 degrees C) and 29.92 inches (760 mm) of mercury pressure,  
26 and which are increments above background concentrations, shall apply aggregately to all  
27 HMIWIs at a facility subject to this Rule:

28 (i) ~~arsenic and its compounds~~ \_\_\_\_\_  $2.3 \times 10^{-7}$

29 (ii) ~~beryllium and its compounds~~ \_\_\_\_\_  $4.1 \times 10^{-6}$

30 (iii) ~~cadmium and its compounds~~ \_\_\_\_\_  $5.5 \times 10^{-6}$

31 (iv) ~~chromium (VI) and its compounds~~ \_\_\_\_\_  $8.3 \times 10^{-8}$ ;

32 ~~(B)~~ The owner or operator of a facility with HMIWIs subject to this Rule shall demonstrate  
33 compliance with the ambient standards in Subparts (i) through (iv) of Part (A) of this  
34 Subparagraph by following the procedures set out in Rule .1106 of this Subchapter.  
35 Modeling demonstrations shall comply with the requirements of Rule .0533 of this  
36 Subchapter; and

1 ~~(C) The emission rates computed or used under Part (B) of this Subparagraph that demonstrate~~  
2 ~~compliance with the ambient standards under Part (A) of this Subparagraph shall be~~  
3 ~~specified as a permit condition for the facility with HMIWIs subject to this Rule as their~~  
4 ~~allowable emission limits unless Rules .0524, .1110, or .1111 of this Subchapter requires~~  
5 ~~more restrictive rates.~~

6 (d) Operational Standards.

7 (1) The operational standards in this Rule do not apply to any HMIWI ~~subject to this Rule~~ when  
8 applicable operational standards in ~~Rule 15A NCAC 02D .0524, .1110, or .1111 of this Subchapter~~  
9 apply;

10 (2) Annual Equipment Inspection.

11 (A) Each HMIWI shall undergo ~~an equipment inspection initially within 6 months upon this~~  
12 ~~Rule's effective date and~~ an annual equipment inspection (no more than 12 months  
13 following the previous annual equipment inspection);

14 (B) The equipment inspection shall include all the elements listed in 40 CFR 60.36e(a)(1)(i)  
15 through (xvii);

16 (C) Any necessary repairs found during the inspection shall be completed within 10 operating  
17 days of the inspection unless the owner or operator submits a written request to the Director  
18 for an extension of the 10 operating day period; and

19 (D) The Director shall grant the extension if the owner or operator submits a written request to  
20 the Director for an extension of the 10 operating day period if the owner or operator of the  
21 small remote HMIWI demonstrates that achieving compliance by the time allowed under  
22 this Part is not feasible, the Director does not extend the time allowed for compliance by  
23 more than 30 days following the receipt of the written request, and the Director concludes  
24 that the emission control standards would not be exceeded if the repairs were delayed;

25 (3) Air Pollution Control Device Inspection.

26 (A) Each HMIWI shall undergo air pollution control device ~~inspections, as applicable, initially~~  
27 ~~within six months upon this Rule's effective date and~~ inspections annually (no more than  
28 12 months following the previous annual air pollution control device inspection) to inspect  
29 air pollution control device(s) for proper operation, if applicable: ensure proper calibration  
30 of thermocouples, sorbent feed systems, and any other monitoring equipment; and  
31 generally observe that the equipment is maintained in good operating condition. Any  
32 necessary repairs found during the inspection shall be completed within 10 operating days  
33 of the inspection unless the owner or operator submits a written request to the Director for  
34 an extension of the 10 operating day period; and

35 (B) The Director shall grant the extension if the owner or operator of the HMIWI demonstrates  
36 that achieving compliance by the 10 operating day period is not feasible, the Director does  
37 not extend the time allowed for compliance by more than 30 days following the receipt of

1 the written request, and the Director concludes that the emission control standards would  
2 not be exceeded if the repairs were delayed;

3 (4) Any HMIWI, except for a small HMIWI for which construction was commenced on or before June  
4 20, 1996, or for which modification was commenced on or before March 16, 1998, and subject to  
5 the requirements listed in Table 1B of Subpart Ce of 40 CFR Part 60, shall comply with 40 CFR  
6 60.56c except ~~for~~ for

7 (A) ~~Before July 1, 2013, the test methods listed in Paragraphs 60.56c(b)(7) and (8), the fugitive~~  
8 ~~emissions testing requirements under 40 CFR 60.56c(b)(14) and (c)(3), the CO CEMS~~  
9 ~~requirements under 40 CFR 60.56c(e)(4), and the compliance requirements for monitoring~~  
10 ~~listed in 40 CFR 60.56c(e)(5)(ii) through (v), (c)(6), (c)(7), (e)(6) through (10), (f)(7)~~  
11 ~~through (10), (g)(6) through (10), and (h); and~~

12 (B) ~~On or after July 1, 2013, sources subject to the emissions limits under pursuant to Table~~  
13 ~~1B of Subject Ce of 40 CFR Part 60 or more stringent of the requirements listed in Table~~  
14 ~~1B of Subpart 1B of Subpart Ce of 40 CFR Part 60 and Table 1A of Subpart Ec of 40 CFR~~  
15 ~~Part 60 may, however, elect to use CO CEMS as specified under in 40 CFR 60.56c(c)(4)~~  
16 ~~or bag detection systems as specified under in 40 CFR 60.57c(h);~~

17 (5) ~~Prior to July 1, 2013, the owner or operator of any small remote HMIWI shall comply with the~~  
18 ~~following compliance and performance testing requirements:~~

19 (A) ~~conduct the performance testing requirements in 40 CFR 60.56c(a), (b)(1) through (b)(9),~~  
20 ~~(b)(11)(mercury only), and (c)(1). The 2,000 pound per week limitation does not apply~~  
21 ~~during performance tests;~~

22 (B) ~~establish maximum charge rate and minimum secondary chamber temperature as site-~~  
23 ~~specific operating parameters during the initial performance test to determine compliance~~  
24 ~~with applicable emission limits; and~~

25 (C) ~~following the date on which the initial performance test is completed, ensure that the~~  
26 ~~HMIWI does not operate above the maximum charge rate or below the minimum secondary~~  
27 ~~chamber temperature measured as three hour rolling averages, calculated each hour as the~~  
28 ~~average of all previous three operating hours, at all times except during periods of start up,~~  
29 ~~shut down and malfunction. Operating parameter limits do not apply during performance~~  
30 ~~tests. Operation above the maximum charge rate or below the minimum secondary chamber~~  
31 ~~temperature shall constitute a violation of the established operating parameters;~~

32 (6)(5) ~~On or after July 1, 2013, any~~ Any small remote HMIWI constructed on or before June 20, 1996, or  
33 for which modification was commenced on or before March 16, 1998, is subject to the requirements  
34 listed in Table 2B of Subpart Ce of 40 CFR Part 60. The owner or operator shall comply with the  
35 compliance and performance testing requirements of 40 CFR 60.56c, excluding test methods listed  
36 in 40 CFR 60.56c(b)(7), (8), (12), (13) (Pb and Cd), and (14), the annual PM, CO, and HCl emissions  
37 testing requirements ~~under pursuant to~~ 40 CFR 60.56c(c)(2), the annual fugitive emissions testing

1 requirements ~~under~~ pursuant to 40 CFR 60.56c(c)(3), the CO CEMS requirements ~~under~~ pursuant  
2 to 40 CFR 60.56c(c)(4), and the compliance requirements for monitoring listed in 40 CFR  
3 60.56c(c)(5) through (7), and (d) through (k);

4 ~~(7)(6)~~ On or after July 1, 2013, any Any small remote HMIWI ~~For~~ for which construction was commenced  
5 on or before June 20, 1996, or for which modification was commenced on or before March 16, 1998,  
6 subject to the requirements listed in Table 2A or 2B of Subpart Ce of 40 CFR Part 60, and not  
7 equipped with an air pollution control device shall meet the following compliance and performance  
8 testing requirements:

9 (A) Establish maximum charge rate and minimum secondary chamber temperature as site-  
10 specific operating parameters during the initial performance test to determine compliance  
11 with applicable emission limits. The 2,000 pounds per week limitation ~~does~~ shall not apply  
12 during performance tests;

13 (B) The owner or operator shall not operate the HMIWI above the maximum charge rate or  
14 below the minimum secondary chamber temperature measured as ~~3-hour~~ three-hour  
15 rolling averages (calculated each hour as the average of the previous three operating hours)  
16 at all times. Operating parameter limits shall not apply during performance tests. Operation  
17 above the maximum charge rate or below the minimum secondary chamber temperature  
18 shall constitute a violation of the established operating parameter(s); and

19 (C) Operation of an HMIWI above the maximum charge rate and below the minimum  
20 secondary chamber temperature (each measured on a three-hour rolling average)  
21 simultaneously shall constitute a violation of the PM, CO, and dioxin/furan emissions  
22 limits. The owner or operator of an HMIWI may conduct a repeat performance test within  
23 30 days of violation of applicable operating ~~parameter(s)~~ parameters to demonstrate that  
24 the designated facility is not in violation of the applicable emissions ~~limit(s)~~ limits. Repeat  
25 performance tests conducted shall be conducted under process and control device operating  
26 conditions duplicating as nearly as possible those that indicated during the violation;

27 ~~(8)(7)~~ On or after July 1, 2013, any Any small HMIWI ~~constructed~~ commenced ~~emissions guidelines as~~  
28 ~~promulgated on September 15, 1997, meeting all requirements listed in Table 2B of Subpart Ce of~~  
29 ~~40 CFR Part 60, which is located more than 50 miles from the boundary of the nearest Standard~~  
30 ~~Metropolitan Statistical Area and which burns less than 2,000 pounds per week of hospital, medical~~  
31 ~~and infectious waste and is subject to the requirements listed in Table 2B of Subpart Ce of 40 CFR~~  
32 ~~Part 60. The 2,000 pounds per week limitation does not apply during performance tests. The owner~~  
33 ~~or operator~~ for which construction was commenced after June 20, 1996 but no later than December  
34 1, 2008, or for which modification is commenced after March 16, 1998 but no later than April 6,  
35 2010, shall comply with the compliance and performance testing requirements of 40 CFR 60.56c,  
36 excluding the annual fugitive emissions testing requirements ~~under~~ pursuant to 40 CFR  
37 60.56c(c)(3), the CO CEMS requirements ~~under~~ pursuant to 40 CFR 60.56c(c)(4), and the

1 compliance requirements for monitoring listed in 40 CFR 60.56c(c)(5)(ii) through (v), (c)(6), (c)(7),  
2 (e)(6) through (10), (f)(7) through (10), and (g)(6) through (10). The owner or operator may elect  
3 to use CO CEMS as specified ~~under in~~ 40 CFR 60.56c(c)(4) or bag leak detection systems as  
4 specified ~~under in~~ 40 CFR 60.57c(h); and

5 ~~(9)(8)~~ ~~On or after July 1, 2013, the~~ The owner or operator of any HMIWI equipped with selective  
6 noncatalytic reduction technology shall:

7 (A) Establish the maximum charge rate, the minimum secondary chamber temperature, and the  
8 minimum reagent flow rate as site specific operating parameters during the initial  
9 performance test to determine compliance with the emissions limits;

10 (B) Ensure that the affected facility does not operate above the maximum charge rate, or below  
11 the minimum secondary chamber temperature or the minimum reagent flow rate measured  
12 as three-hour rolling averages (calculated each hour as the average of the previous three  
13 operating hours) at all times. Operating parameter limits shall not apply during  
14 performance tests; and

15 (C) Operation of any HMIWI above the maximum charge rate, below the minimum secondary  
16 chamber temperature, and below the minimum reagent flow rate simultaneously shall  
17 constitute a violation of the NO<sub>x</sub> emissions limit. The owner or operator may conduct a  
18 repeat performance test within 30 days of violation of applicable operating  
19 ~~parameter(s) parameters~~ to demonstrate that the affected facility is not in violation of the  
20 applicable emissions ~~limit(s) limits~~. Repeat performance tests conducted pursuant to this  
21 paragraph shall be conducted using the identical operating parameters that indicated a  
22 violation.

23 (e) Test Methods and Procedures.

24 (1) The test methods and procedures described in ~~Section .2600 of this Subchapter~~ 15A NCAC 02D  
25 .2600 and in 40 CFR Part 60 Appendix A and 40 CFR Part 61 Appendix B shall be used to determine  
26 compliance with emission rates. Method 29 of 40 CFR Part 60 shall be used to determine emission  
27 rates for metals. However, Method 29 shall be used to sample for chromium (VI), and SW 846  
28 Method 0060 shall be used for the analysis; and

29 (2) The Director may require the owner or operator to test the HMIWI to demonstrate compliance with  
30 the emission standards listed in Paragraph (c) of this Rule.

31 (f) Monitoring, Recordkeeping, and Reporting.

32 (1) The owner or operator of an HMIWI subject to the requirements of this Rule shall comply with the  
33 monitoring, recordkeeping, and reporting requirements in ~~Section .0600 of this Subchapter~~ 15A  
34 NCAC 02D .0600.

35 (2) The owner or operator of an HMIWI subject to the requirements of this Rule shall maintain and  
36 operate a continuous temperature monitoring and recording device for the primary chamber and,  
37 where there is a secondary chamber, for the secondary chamber. The owner or operator of an

1 HMIWI that has installed air pollution abatement equipment to reduce emissions of hydrogen  
2 chloride shall install, operate, and maintain continuous monitoring equipment to measure pH for  
3 wet scrubber systems and rate of alkaline injection for dry scrubber systems. The Director shall  
4 require the owner or operator of an HMIWI with a permitted charge rate of 750 pounds per hour or  
5 more to install, operate, and maintain continuous monitors for oxygen or for carbon monoxide or  
6 both as necessary to determine proper operation of the HMIWI. The Director may require the owner  
7 or operator of an HMIWI with a permitted charge rate of less than 750 pounds per hour to install,  
8 operate, and maintain monitors for oxygen or for carbon monoxide or both as necessary to determine  
9 proper operation of the HMIWI;

10 (3) In addition to the requirements of Subparagraphs (1) and (2) of this Paragraph, the owner or operator  
11 of a HMIWI shall comply with the reporting and recordkeeping requirements listed in 40 CFR  
12 60.58c~~(b), (c), (d), (e), and (f)~~, (b) through (g), excluding 40 CFR 60.58c(b)(2)(ii) and (b)(7);

13 (4) In addition to the requirements of Subparagraphs (1), (2) and (3) of this Paragraph, the owner or  
14 operator of a small remote HMIWI shall:

15 (A) maintain records of the annual equipment inspections, any required maintenance, and any  
16 repairs not completed within 10 days of an inspection;

17 (B) submit an annual report containing information recorded in Part (A) of this Subparagraph  
18 to the Director no later than 60 days following the year in which data were collected.  
19 Subsequent reports shall be sent no later than 12 calendar months following the previous  
20 report. The report shall be signed by the HMIWI manager; and

21 (C) submit the reports required by Parts (A) and (B) of this Subparagraph to the Director  
22 semiannually once the HMIWI is subject to the permitting procedures of 15A NCAC 02Q  
23 .0500, Title V Procedures;

24 (5) Waste Management Guidelines. The owner or operator of a HMIWI shall comply with the  
25 requirements of 40 CFR 60.55c for the preparation and submittal of a waste management plan;

26 (6) Except as provided in Subparagraph (7) of this Paragraph, the owner or operator of any HMIWI  
27 shall comply with the monitoring requirements in 40 CFR 60.57c;

28 (7) The owner or operator of any small remote HMIWI shall:

29 (A) install, calibrate, maintain, and operate a device for measuring and recording the  
30 temperature of the secondary chamber on a continuous basis, the output of which shall be  
31 recorded, at a minimum, once every minute throughout operation;

32 (B) install, calibrate, maintain, and operate a device which automatically measures and records  
33 the date, time, and weight of each charge fed into the HMIWI; and

34 (C) obtain monitoring data at all times during HMIWI operation except during periods of  
35 monitoring equipment malfunction, calibration, or repair. At a minimum, valid monitoring  
36 data shall be obtained for 75 percent of the operating hours per day and for 90 percent of

1 the operating hours per calendar quarter that the HMIWI is combusting hospital, medical,  
2 and infectious waste;

3 (8) ~~On or after July 1, 2013, any~~ Any HMIWI, except for small remote HMIWI not equipped with an  
4 air pollution control device, subject to the emissions requirements in Table 1B or Table 2B of  
5 Subpart Ce of 40 CFR Part 60, or the more stringent of the requirements listed in Table 1B of  
6 Subpart Ce of 40 CFR Part 60 and Table 1A of Subpart Ec of 40 CFR Part 60, shall perform the  
7 monitoring requirements listed in 40 CFR 60.57c;

8 (9) ~~On or after July 1, 2013, the~~ The owner or operator of a small remote HMIWI, not equipped with  
9 an air pollution control device and subject to the emissions requirements in Table 2B of Subpart Ce  
10 of 40 CFR Part 60 shall:

11 (A) install, calibrate (~~to manufacturers' specifications~~), to manufacturers' specifications,  
12 maintain, and operate a device for measuring and recording the temperature of the  
13 secondary chamber on a continuous basis, the output of which shall be recorded, at a  
14 minimum, once every minute throughout operation;

15 (B) install, calibrate (~~to manufacturers' specifications~~), to manufacturers' specifications,  
16 maintain, and operate a device which automatically measures and records the date, time,  
17 and weight of each charge fed into the HMIWI; and

18 (C) obtain monitoring data at all times during HMIWI operation except during periods of  
19 monitoring equipment malfunction, calibration, or repair. At a minimum, valid monitoring  
20 data shall be obtained for 75 percent of the operating hours per day for 90 percent of the  
21 operating hours per calendar quarter that the designated facility is combusting hospital,  
22 medical and infectious waste;

23 (10) ~~On or after July 1, 2013, any~~ Any HMIWI for which construction commenced on or before June 20,  
24 1996, or for which modification was commenced on or before March 16, 1998, and is subject to  
25 requirements listed in Table 1B of Subpart Ce of 40 CFR Part 60; or any HMIWI which construction  
26 was commenced after June 20, 1996 but no later than December 1, 2008, or for which modification  
27 is commenced after March 16, 1998 but no later than April 6, 2010, and subject to the requirements  
28 of Table 1B of this Subpart and Table 1A of Subpart Ec of 40 CFR Part 60, may use the results of  
29 previous emissions tests to demonstrate compliance with the emissions limits, provided that:

30 (A) Previous emissions tests had been conducted using the applicable procedures and test  
31 methods listed in 40 CFR 60.56c(b);

32 (B) The HMIWI is currently operated in a manner that would be expected to result in the same  
33 or lower emissions than observed during the previous emissions test and not modified such  
34 that emissions would be expected to exceed; and

35 (C) The previous emissions ~~test(s)~~ tests had been conducted in 1996 or later;

36 (11) ~~On or after July 1, 2013, any~~ Any HMIWI, (with the exception of small remote HMIWI and  
37 HMIWIs for which construction was commenced no later than December 1, 2008, or for which



1 modification is commenced no later than April 6, 2010, and subject to the requirements listed in  
2 Table 1B of Subpart Ce of 40 CFR Part 60 or the more stringent of the requirements listed in Table  
3 1B of Subpart Ce of 40 CFR Part 60 and Table 1A of Subpart Ec), shall include the reporting and  
4 recordkeeping requirements listed in 40 CFR 60.58c(b); (b) through (g) in Subpart Ec; and

- 5 (12) ~~On or after July 1, 2013, any~~ Any HMIWI for which construction was commenced no later than  
6 December 1, 2008, or for which modification is commenced no later than April 6, 2010, and subject  
7 to the requirements listed in Table 1B or the more stringent of the requirements listed in Table 1B  
8 of Subpart Ce of 40 CFR Part 60 and Table 1A of Subpart Ec of 40 CFR Part 60, ~~is~~ shall not be  
9 required to maintain records required in 40 CFR 60.58c(b)(2)(xviii) (bag leak detection system  
10 alarms), (b)(2)(xix) (CO CEMS data), and (b)(7) (siting documentation).

11 ~~(g) Excess Emissions and Start up and Shut down. All HMIWIs subject to this Rule shall comply with Rule .0535,~~  
12 ~~Excess Emissions Reporting and Malfunctions, of this Subchapter. Emissions from bypass conditions shall not be~~  
13 ~~exempted as provided under Paragraphs (e) and (g) of Rule 0.535 of this Subchapter.~~

14 ~~(h)(g)~~ Operator Training and Certification.

- 15 (1) The owner or operator of a HMIWI shall not allow the HMIWI to operate at any time unless a fully  
16 trained and qualified HMIWI operator is accessible, either at the facility or available within one  
17 hour. The trained and qualified HMIWI operator may operate the HMIWI directly or be the direct  
18 supervisor of one or more HMIWI operators;
- 19 (2) Operator training and qualification shall be obtained by completing the requirements of 40 CFR  
20 60.53c(c) through (g);
- 21 (3) The owner or operator of a HMIWI shall maintain, at the facility, all items required by 40 CFR  
22 60.53c(h)(1) through (h)(10);
- 23 (4) The owner or operator of a HMIWI shall establish a program for reviewing the information required  
24 by Subparagraph (3) of this Paragraph annually with each HMIWI operator. The reviews of the  
25 information shall be conducted annually; and
- 26 (5) The information required by Subparagraph (3) of this Paragraph shall be kept in a readily accessible  
27 location for all HMIWI operators. This information, along with records of training shall be available  
28 for inspection by Division personnel upon request.

29  
30 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(5); 40 CFR 60.34e;*

31 *Eff. October 1, 1991;*

32 *Amended Eff. January 1, 2011; June 1, 2008; August 1, 2002; July 1, 2000; July 1, 1999; July 1,*  
33 *1998; July 1, 1996; April 1, 1995; December 1, ~~1993.~~1993;*

34 *Readopted Eff.*

1 15A NCAC 02D .1207 is proposed for readoption as a repeal as follows:

2  
3 **15A NCAC 02D .1207 CONICAL INCINERATORS**

4 ~~(a) Purpose. The purpose of this Rule is to set forth the requirements of the Commission relating to the use of conical~~  
5 ~~incinerators in the burning of wood and agricultural waste.~~

6 ~~(b) Scope. This Rule shall apply to all conical incinerators which are designed to incinerate wood and agricultural~~  
7 ~~waste.~~

8 ~~(c) Each conical incinerator subject to this Rule shall be equipped and maintained with:~~

9 (1) ~~an underfire and an overfire forced air system and variable damper which is automatically controlled~~  
10 ~~to ensure the optimum temperature range for the complete combustion of the amount and type of~~  
11 ~~material waste being charged into the incinerator;~~

12 (2) ~~a temperature recorder for continuously recording the temperature of the exit gas;~~

13 (3) ~~a feed system capable of delivering the waste to be burned at a sufficiently uniform rate to prevent~~  
14 ~~temperature from dropping below 800 °F during normal operation, with the exception of one startup~~  
15 ~~and one shutdown per day.~~

16 ~~(d) The owner of the conical incinerator shall monitor and report ambient particulate concentrations using the~~  
17 ~~appropriate method specified in 40 CFR Part 50 with the frequency specified in 40 CFR Part 58. The Director may~~  
18 ~~require more frequent monitoring if measured particulate concentrations exceed the 24 hour concentration allowed~~  
19 ~~under 15A NCAC 2D .0400. The owner or operator shall report the monitoring data quarterly to the Division.~~

20 ~~(e) In no case shall the ambient air quality standards as defined in Section .0400 of this Subchapter be exceeded.~~

21 ~~(f) The conical incinerator shall not violate the opacity standards in Rule .0521 of this Subchapter.~~

22 ~~(g) The distance a conical incinerator is located and operated from the nearest structure(s) in which people live or~~  
23 ~~work shall be optimized to prevent air quality impact and shall be subject to approval by the Commission.~~

24 ~~(h) New conical incinerators shall be in compliance with this Rule on startup.~~

25  
26 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(4),(5);*

27 *Eff. October 1, 1991;*

28 *Amended Eff. July 1, 2000; July 1, ~~1998~~.1998;*

29 *Repealed Eff. \_\_\_\_\_.*

1 15A NCAC 02D .1208 is proposed for readoption without substantive changes as follows:

2  
3 **15A NCAC 02D .1208 OTHER INCINERATORS**

4 (a) Applicability.

5 (1) This Rule applies to any incinerator not covered under ~~Rules 15A NCAC 02D .1203, .1204, through~~  
6 ~~.1207, .1206, or .1210 through .1212 of this Section. 1210.~~

7 (2) If any incinerator subject to this Rule:

8 (A) is used solely to cremate pets; or

9 (B) if the emissions of all toxic air pollutants from an incinerator subject to this Rule and  
10 associated waste handling and storage are less than the levels listed in 15A NCAC 02Q  
11 ~~.0711; .0711. the incinerator is exempt from Subparagraphs (b)(6) through (b)(9) and~~  
12 ~~Paragraph (c) of this Rule.~~

13 The incinerator shall be exempt from Subparagraphs (b)(6) through (b)(9) and Paragraph (c) of this  
14 Rule.

15 (b) Emission Standards.

16 (1) The emission standards in this Rule apply to any incinerator subject to this Rule except where ~~Rules~~  
17 ~~15A NCAC 02D .0524, 1110, or .1111 of this Subchapter~~ apply. However, when Subparagraphs  
18 (8) or (9) of this Paragraph and ~~Rules 15A NCAC 02D .0524, .1110, or .1111 of this Subchapter~~  
19 regulate the same pollutant, the more restrictive provision for each pollutant applies notwithstanding  
20 provisions of ~~Rules 15A NCAC 02D .0524, .1110, or .1111 of this Subchapter~~ to the contrary.

21 (2) Particulate Matter. Any incinerator subject to this Rule shall comply with one of the following  
22 emission standards for particulate matter:

23 (A) For refuse charge rates between 100 and 2000 pounds per hour, the allowable emissions  
24 rate for particulate matter from any stack or chimney of any incinerator subject to this Rule  
25 shall not exceed the level calculated with the equation  $E=0.002P$  calculated to two  
26 significant figures, where "E" equals the allowable emission rate for particulate matter in  
27 pounds per hour and "P" equals the refuse charge rate in pounds per hour. For refuse charge  
28 rates of 0 to 100 pounds per hour the allowable emission rate in 0.2 pounds per hour. For  
29 refuse charge rates of 2000 pounds per hour or greater the allowable emission rate shall be  
30 4.0 pounds per hour. Compliance with this Part shall be determined by averaging  
31 emissions over a three-hour block period.

32 (B) Instead of meeting the standards in Part (A) of this Subparagraph, the owner or operator of  
33 any incinerator subject to this Rule may choose to limit particulate emissions from the  
34 incinerator to 0.08 grains per dry standard cubic foot corrected to 12 percent carbon  
35 dioxide. In order to choose this option, the owner or operator of the incinerator shall  
36 demonstrate that the particulate ambient air quality standards will not be violated. To  
37 correct to 12 percent carbon dioxide, the measured concentration of particulate matter is

1                   ~~shall be~~ multiplied by 12 and divided by the measured percent carbon dioxide. Compliance  
2                   with this Part shall be determined by averaging emissions over a three-hour block period.

3           (3)   Visible Emissions. Any incinerator subject to this Rule shall comply with ~~Rule 15A NCAC 02D~~  
4                   ~~.0521 of this Subchapter~~ for the control of visible emissions.

5           (4)   Sulfur Dioxide. Any incinerator subject to this Rule shall comply with ~~Rule 15A NCAC 02D~~ .0516  
6                   ~~of this Subchapter~~ for the control of sulfur dioxide emissions.

7           (5)   Odorous Emissions. Any incinerator subject to this Rule shall comply with ~~Rule 15A NCAC 02D~~  
8                   ~~.1806 of this Subchapter~~ for the control of odorous emissions.

9           (6)   Hydrogen Chloride. Any incinerator subject to this Rule shall control emissions of hydrogen  
10                   chloride such that they do not exceed four pounds per hour unless they are reduced by at least 90  
11                   percent by weight or to no more than 50 parts per million by volume corrected to seven percent  
12                   oxygen (dry basis). Compliance with this Subparagraph shall be determined by averaging emissions  
13                   over a one-hour period.

14          (7)   Mercury Emissions. Emissions of mercury and mercury compounds from the stack or chimney of  
15                   any incinerator subject to this Rule shall not exceed 0.032 pounds per hour. Compliance with this  
16                   Subparagraph shall be determined by averaging emissions over a one-hour period.

17          (8)   Toxic Emissions. The owner or operator of any incinerator subject to this Rule shall demonstrate  
18                   compliance with ~~Section 15A NCAC 02D .1100 of this Subchapter~~ according to 15A NCAC 02Q  
19                   .0700.

20          (9)   Ambient Standards.

21           (A)   In addition to the ambient air quality standards in ~~Section 15A NCAC 02D .0400 .0400,~~  
22                   ~~of this Subchapter,~~ the following ambient air quality standards, which are an annual  
23                   average, in milligrams per cubic meter at 77 degrees ~~F-Fahrenheit~~ (25 degrees ~~C-Celsius~~)  
24                   and 29.92 inches (760 mm) of mercury pressure, and which are increments above  
25                   background concentrations, apply aggregately to all incinerators at a facility subject to this  
26                   Rule:

- |                    |                                 |   |
|--------------------|---------------------------------|---|
| 27           (i)   | arsenic and its compounds       | <del>2.3x10<sup>-7</sup></del> <u>2.1x10<sup>-6</sup></u> |
| 28           (ii)  | beryllium and its compounds     | 4.1x10 <sup>-6</sup>                                      |
| 29           (iii) | cadmium and its compounds       | 5.5x10 <sup>-6</sup>                                      |
| 30           (iv)  | chromium (VI) and its compounds | 8.3x10 <sup>-8</sup>                                      |

31           (B)   The owner or operator of a facility with incinerators subject to this Rule shall demonstrate  
32                   compliance with the ambient standards in Subparts (i) through (iv) of Part (A) of this  
33                   Subparagraph by following the procedures set out in ~~Rule .1106 of this Subchapter.~~ 15A  
34                   NCAC 02D .1106. Modeling demonstrations shall comply with the requirements of  
35                   ~~Rule 15A NCAC 02D .0533 of this Subchapter.~~ .0533.

36           (C)   The emission rates computed or used under Part (B) of this Subparagraph that demonstrate  
37                   compliance with the ambient standards under Part (A) of this Subparagraph shall be

1 specified as a permit condition for the facility with incinerators subject to this Rule as their  
2 allowable emission limits unless ~~Rule 15A NCAC 02D .0524, .1110 or .1111 of this~~  
3 ~~Subchapter~~ requires more restrictive rates.

4 (c) Operational Standards.

- 5 (1) The operational standards in this Rule do not apply to any incinerator subject to this Rule when  
6 applicable operational standards in ~~Rule 15A NCAC 02D .0524, .1110, or .1111 of this Subchapter~~  
7 apply.
- 8 (2) Crematory Incinerators. Gases generated by the combustion shall be subjected to a minimum  
9 temperature of 1600 degrees ~~F-Fahrenheit~~ for a period of not less than one second.
- 10 (3) Other Incinerators. All incinerators not subject to any other rule in this Section shall meet the  
11 following requirement: Gases generated by the combustion shall be subjected to a minimum  
12 temperature of 1800 degrees ~~F-Fahrenheit~~ for a period of not less than one second. The temperature  
13 of 1800 degrees ~~F-Fahrenheit~~ shall be maintained at least 55 minutes out of each 60-minute period,  
14 but at no time shall the temperature go below 1600 degrees ~~F-Fahrenheit~~.
- 15 (4) Except during start-up where the procedure has been approved according to ~~Rule 15A NCAC 02D~~  
16 ~~.0535(g) of this Subchapter, .0535(g)~~, waste material shall not be loaded into any incinerator subject  
17 to this Rule when the temperature is below the minimum required temperature. Start-up procedures  
18 may be determined on a case-by-case basis according to ~~Rule 15A NCAC 02D-.0535(g) of this~~  
19 ~~Subchapter, .0535(g)~~. Any incinerator subject to this Rule shall have automatic auxiliary burners  
20 that are capable of maintaining the required minimum temperature in the secondary chamber  
21 excluding the heat content of the wastes.

22 (d) Test Methods and Procedures.

- 23 (1) The test methods and procedures described in ~~Section 15A NCAC 02D .2600 of this Subchapter~~  
24 and in 40 CFR Part 60 Appendix A and 40 CFR Part 61 Appendix B shall be used to determine  
25 compliance with emission rates. Method 29 of 40 CFR Part 60 shall be used to determine emission  
26 rates for metals. However, Method 29 shall be used to sample for chromium (VI), and SW 846  
27 Method 0060 shall be used for the analysis.
- 28 (2) The Director shall require the owner or operator to test his incinerator to demonstrate compliance  
29 with the emission standards listed in Paragraph (b) of this Rule if necessary to determine compliance  
30 with the emission standards of Paragraph (b) of this Rule.

31 (e) Monitoring, Recordkeeping, and Reporting.

- 32 (1) The owner or operator of an incinerator subject to the requirements of this Rule shall comply with  
33 the monitoring, recordkeeping, and reporting requirements in ~~Section 15A NCAC 02D .0600 of this~~  
34 ~~Subchapter, .0600~~.
- 35 (2) The owner or operator of an incinerator, except an incinerator meeting the requirements of ~~Parts~~  
36 ~~.1201(e)(4)(A) through (D) of this Section, 15A NCAC 02D .1201(b)(4)(A) through (D)~~, shall  
37 maintain and operate a continuous temperature monitoring and recording device for the primary

1 chamber and, where there is a secondary chamber, for the secondary chamber. The Director shall  
2 require a temperature monitoring device for incinerators meeting the requirements of ~~Parts~~  
3 ~~.1201(e)(4)(A) through (D) of this Section~~ 15A NCAC 02D .1201(b)(4)(A) through (D) if the  
4 incinerator is in violation of the requirements of ~~Part 15A NCAC 02D .1201(e)(4)(D)~~  
5 ~~.1201(b)(4)(D) of this Section~~. The owner or operator of an incinerator that has installed air  
6 pollution abatement equipment to reduce emissions of hydrogen chloride shall install, operate, and  
7 maintain continuous monitoring equipment to measure pH for wet scrubber systems and rate of  
8 alkaline injection for dry scrubber systems. The Director shall require the owner or operator of an  
9 incinerator with a permitted charge rate of 750 pounds per hour or more to install, operate, and  
10 maintain continuous monitors for oxygen or for carbon monoxide or both as necessary to determine  
11 proper operation of the incinerator. The Director shall require the owner or operator of an incinerator  
12 with a permitted charge rate of less than 750 pounds per hour to install, operate, and maintain  
13 monitors for oxygen or for carbon monoxide or both if necessary to determine proper operation of  
14 the incinerator.

15 (f) Excess Emissions and Start-up and Shut-down. Any incinerator subject to this Rule shall comply with ~~Rule 15A~~  
16 ~~NCAC 02D .0535, Excess Emissions Reporting and Malfunctions, of this Subchapter.0535.~~

17  
18 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(10);*  
19 *Eff. July 1, 1998;*  
20 *Amended Eff. August 1, 2008; June 1, 2008; July 1, 2007; January 1, 2005; August 1, 2002; July 1,*  
21 *2000; July 1, ~~1999~~. 1999;*  
22 *Readopted Eff. \_\_\_\_\_.*  
23  
24

1 15A NCAC 02D .1211 is proposed for readoption as a repeal as follows:

2  
3 **15A NCAC 02D .1211 OTHER SOLID WASTE INCINERATION UNITS**

4 ~~(a) Applicability. With the exceptions in Paragraph (b), this Rule applies to other solid waste incineration (OSWI)~~  
5 ~~units.~~

6 ~~(b) Exemptions. The following types of incineration units are exempted from this Rule:~~

7 ~~(1) incineration units covered under Rules .1203 through .1206 and .1210 of this Section;~~

8 ~~(2) units, burning 90 percent or more by weight on a calendar quarter basis, excluding the weight of~~  
9 ~~auxiliary fuel and combustion air, pathological waste, low level radioactive waste, or~~  
10 ~~chemotherapeutic waste, if the owner or operator of the unit:~~

11 ~~(A) notifies the Director that the unit qualifies for this exemption; and~~

12 ~~(B) keeps records on a calendar quarter basis of the weight, pathological waste, low level~~  
13 ~~radioactive waste, or chemotherapeutic waste burned, and the weight of all other fuels and~~  
14 ~~wastes burned in the unit;~~

15 ~~(3) Cogeneration units if:~~

16 ~~(A) The unit qualifies as a cogeneration facility under section 3(18)(B) of the Federal Power~~  
17 ~~Act (16 U.S.C. 796(18)(B));~~

18 ~~(B) The unit burns homogeneous waste (not including refuse derived fuel) to produce~~  
19 ~~electricity and steam or other forms of energy used for industrial, commercial, heating, or~~  
20 ~~cooling purposes; and~~

21 ~~(C) The owner or operator of the unit notifies the Director that the unit qualifies for this~~  
22 ~~exemption;~~

23 ~~(4) Small power production unit if:~~

24 ~~(A) The unit qualifies as a small power production facility under section 3(17)(C) of the~~  
25 ~~Federal Power Act (16 U.S.C. 796(17)(C));~~

26 ~~(B) The unit burns homogeneous waste (not including refuse derived fuel) to produce~~  
27 ~~electricity; and~~

28 ~~(C) The owner or operator of the unit notifies the Director that the unit qualifies for this~~  
29 ~~exemption.~~

30 ~~(5) units that combust waste for the primary purpose of recovering metals;~~

31 ~~(6) rack, part, and drum reclamation units that burn the coatings off racks used to hold items for~~  
32 ~~application of a coating;~~

33 ~~(7) cement kilns;~~

34 ~~(8) laboratory analysis units that burn samples of materials for the purpose of chemical or physical~~  
35 ~~analysis;~~

36 ~~(9) air curtain burners covered under Rule .1904 of this Subchapter;~~

1 ~~(10) institutional boilers and process heaters regulated under 40 CFR Part 63, Subpart DDDDD (National~~  
2 ~~Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional~~  
3 ~~Boilers and Process Heaters);~~

4 ~~(11) rural institutional waste incinerators that meet the conditions in 40 CFR 60.2993(h);~~

5 ~~(12) incinerators that combust contraband or prohibited goods if owned or operated by a government~~  
6 ~~agency, such as police, customs, agricultural inspection, or a similar agency, to destroy only illegal~~  
7 ~~or prohibited goods, such as illegal drugs, or agricultural food products that cannot be transported~~  
8 ~~into the country or across state lines to prevent biocontamination. The exclusion does not apply to~~  
9 ~~items either confiscated or incinerated by private, industrial, or commercial entities; or~~

10 ~~(13) Incinerators used for national security and is used solely:~~

11 ~~(A) to destroy national security materials integral to the field exercises during military training~~  
12 ~~field exercises; or~~

13 ~~(B) to incinerate national security materials when necessary to safeguard national security if~~  
14 ~~the owner or operator follows to procedures in 40 CFR 60.2993(q)(2) to receive this~~  
15 ~~exemption.~~

16 ~~(c) Definitions. For the purpose of this Rule, the definitions contained in 40 CFR 60.3078 shall apply in addition to~~  
17 ~~the definitions in Rule .1202 of this Section.~~

18 ~~(d) Emission Standards. The emission standards in this Rule apply to all incinerators subject to this Rule except~~  
19 ~~where Rule .0524, .1110, or .1111 of this Subchapter applies. When Subparagraphs (12) or (13) of this Paragraph and~~  
20 ~~Rules .0524, .1110, or .1111 of this Subchapter regulate the same pollutant, the more restrictive provision for each~~  
21 ~~pollutant shall apply, notwithstanding provisions of Rules .0524, .1110, or .1111 of this Subchapter to the contrary.~~

22 ~~(1) Particulate Matter. Emissions of particulate matter from an OSWI unit shall not exceed 0.013 grains~~  
23 ~~per dry standard cubic foot corrected to seven percent oxygen, dry basis (3 run average with 1 hour~~  
24 ~~minimum sample time per run).~~

25 ~~(2) Opacity. Visible emissions from the stack of an OSWI unit shall not exceed 10 percent opacity (6-~~  
26 ~~minute block average with 1 hour minimum sample time per run).~~

27 ~~(3) Sulfur Dioxide. Emissions of sulfur dioxide from an OSWI unit subject to the requirements of this~~  
28 ~~Rule shall not exceed 3.1 parts per million by volume corrected to seven percent oxygen, dry basis~~  
29 ~~(3 run average with 1 hour minimum sample time per run).~~

30 ~~(4) Nitrogen Oxides. Emissions of nitrogen oxides from an OSWI unit shall not exceed 103 parts per~~  
31 ~~million by dry volume corrected to seven percent oxygen, dry basis (3 run average with 1 hour~~  
32 ~~minimum sample time per run).~~

33 ~~(5) Carbon Monoxide. Emissions of carbon monoxide from an OSWI unit shall not exceed 40 parts per~~  
34 ~~million by dry volume, corrected to seven percent oxygen, dry basis (3 run average with 1 hour~~  
35 ~~minimum sample time per run) and 12-hour rolling averages measured using continuous emissions~~  
36 ~~monitoring system (CEMS).~~



1 ~~(6) Odorous Emissions. An OSWI unit shall comply with Rule .1806 of this Subchapter for the control~~  
2 ~~of odorous emissions.~~

3 ~~(7) Hydrogen Chloride. Emissions of hydrogen chloride from an OSWI unit shall not exceed 15 parts~~  
4 ~~per million by dry volume, corrected to seven percent oxygen, dry basis (3 run average with 1 hour~~  
5 ~~minimum sample time per run).~~

6 ~~(8) Mercury Emissions. Emissions of mercury from an OSWI unit shall not exceed 74 micrograms per~~  
7 ~~dry standard cubic meter, corrected to seven percent oxygen, dry basis (3 run average with 1 hour~~  
8 ~~minimum sample time per run).~~

9 ~~(9) Lead Emissions. Emissions of lead from an OSWI unit shall not exceed 226 micrograms per dry~~  
10 ~~standard cubic meter, corrected to seven percent oxygen, dry basis (3 run average with 1 hour~~  
11 ~~minimum sample time per run).~~

12 ~~(10) Cadmium Emissions. Emissions of cadmium from an OSWI unit shall not exceed 18 micrograms~~  
13 ~~per dry standard cubic meter, corrected to seven percent oxygen, dry basis (3 run average with 1~~  
14 ~~hour minimum sample time per run).~~

15 ~~(11) Dioxins and Furans. Emissions of dioxins and furans from an OSWI unit shall not exceed 33~~  
16 ~~nanograms per dry standard cubic meter, corrected to seven percent oxygen, dry basis (3 run average~~  
17 ~~with 1 hour minimum sample time per run).~~

18 ~~(12) Toxic Emissions. The owner or operator of any incinerator subject to the requirements of this Rule~~  
19 ~~shall demonstrate compliance with Section .1100 of this Subchapter according to Section 15A~~  
20 ~~NCAC 02Q .0700.~~

21 ~~(13) Ambient Standards.~~

22 ~~(A) In addition to the ambient air quality standards in Section .0400 of this Subchapter, the~~  
23 ~~following ambient air quality standards, which are an annual average, in milligrams per~~  
24 ~~cubic meter at 77°F (25°C) and 29.92 inches (760 mm) of mercury pressure, and which~~  
25 ~~are increments above background concentrations, shall apply aggregately to all incinerators~~  
26 ~~at a facility subject to this Rule:~~

POLLUTANT	STANDARD
arsenic and its compounds	2.3x10 <sup>-7</sup>
beryllium and its compounds	4.1x10 <sup>-6</sup>
cadmium and its compounds	5.5x10 <sup>-6</sup>
chromium (VI) and its compounds	8.3x10 <sup>-8</sup>

28  
29 ~~(B) The owner or operator of a facility with OSWI units subject to this Rule shall demonstrate~~  
30 ~~compliance with the ambient standards in Part (A) of this Subparagraph by following the~~  
31 ~~procedures set out in Rule .1106 of this Subchapter. Modeling demonstrations shall comply~~  
32 ~~with the requirements of Rule .0533 of this Subchapter.~~

33 ~~(C) The emission rates computed or used under Part (B) of this Subparagraph that demonstrate~~  
34 ~~compliance with the ambient standards under Part (A) of this Subparagraph shall be~~

1 specified as a permit condition for the facility with incinerators as their allowable emission  
2 limits unless Rule .0524, .1110, or .1111 of this Subchapter requires more restrictive rates.

3 ~~(e) Operational Standards.~~

4 ~~(1) The operational standards in this Rule do not apply to an OSWI unit when applicable operational  
5 standards in Rule .0524, .1110, or .1111 of this Subchapter apply.~~

6 ~~(2) The owner or operator of the OSWI shall meet the emission standards in Paragraph (d) of this Rule  
7 by July 1, 2010.~~

8 ~~(3) If a wet scrubber is used to comply with emission limitations, then the owner or operator of the  
9 OSWI unit:~~

10 ~~(A) shall establish operating limits for the four operating parameters as specified in the Table  
11 3 of 40 CFR 60, Subpart FFFF and as described in Paragraphs 40 CFR 60.3023(a) during  
12 the initial performance test, and;~~

13 ~~(B) shall meet the operating limits established during the initial performance test beginning on  
14 July 1, 2010.~~

15 ~~(4) If an air pollution control device other than a wet scrubber is used or if emissions are limited in some  
16 other manner to comply with the emission standards of Paragraph (d) of this Rule, the owner or  
17 operator of the OSWI unit subject to the requirements of this Rule shall petition the US  
18 Environmental Protection Agency (EPA) for specific operating limits that shall be established  
19 during the initial performance test and continuously monitored thereafter. The initial performance  
20 test shall not be conducted until after the EPA approves the petition. The petition shall include the  
21 five items listed in the Paragraph 40 CFR 60.3024(a) through (e).~~

22 ~~(f) Periods of Startup, Shutdown, and Malfunction. The emission and operating standards apply at all times except  
23 during OSWI unit startups, shutdowns, or malfunctions.~~

24 ~~(g) Test Methods and Procedures.~~

25 ~~(1) The test methods and procedures described in Rule .0501 of this Subchapter, 40 CFR Part 60,  
26 Appendix A, 40 CFR Part 61, Appendix B, and 40 CFR 60.3027 shall be used to determine  
27 compliance with the emission standards in Paragraph (d) this Rule.~~

28 ~~(2) The owner or operator of OSWI unit shall conduct:~~

29 ~~(A) an initial performance test as required under 40 CFR 60.8 and according to 40 CFR  
30 60.3027, no later than July 1, 2010; and after that;~~

31 ~~(B) annual performance tests according to 40 CFR 60.3027 and 40 CFR 60.3033, within 12  
32 months following the initial performance test and within each 12 months thereafter.~~

33 ~~(3) The owner or operator of OSWI unit shall use the results of these tests:~~

34 ~~(A) to demonstrate compliance with the emission standards in Paragraph (d) of this Rule, and;~~

35 ~~(B) to establish operating standards using the procedures in Subparagraphs (e)(3) and (e)(4) of  
36 this Rule.~~

1           ~~(4) — The owner or operator of OSWI unit may conduct annual performance testing less often if the~~  
2           ~~requirements of 40 CFR 60.3035 are met.~~

3           ~~(5) — The owner or operator of OSWI unit may conduct a repeat performance test at any time to establish~~  
4           ~~new values for the operating limits. The Director may request a repeat performance test at any time~~  
5           ~~if he finds that the current operating limits are no longer appropriate.~~

6 ~~(h) Monitoring.~~

7           ~~(1) — The owner or operator of OSWI unit shall comply with the monitoring, recordkeeping, and reporting~~  
8           ~~requirements in Section .0600 of this Subchapter and in 40 CFR 60.13, Monitoring Requirements.~~

9           ~~(2) — The owner or operator of OSWI unit shall:~~

10           ~~(A) — install, calibrate to manufacturers specifications, maintain, and operate continuous~~  
11           ~~emission monitoring systems for carbon monoxide and for oxygen. The oxygen~~  
12           ~~concentration shall be monitored at each location where the carbon monoxide~~  
13           ~~concentrations are monitored;~~

14           ~~(B) — operate the continuous monitoring system according to 40 CFR 60.3039;~~

15           ~~(C) — conduct daily, quarterly, and annual evaluations of the continuous emission monitoring~~  
16           ~~systems according to 40 CFR 60.3040;~~

17           ~~(D) — collect the minimum amount of monitoring data using the procedures in 40 CFR 60.3041(a)~~  
18           ~~through (e) if the continuous emission monitoring system is operating or the procedures in~~  
19           ~~40 CFR 60.3041(f) if the continuous emissions monitoring system is temporarily~~  
20           ~~unavailable; and~~

21           ~~(E) — convert the one hour arithmetic averages into the appropriate averaging times and units as~~  
22           ~~specified in 40 CFR 60.3042 to monitor compliance with the emission standards in~~  
23           ~~Paragraph (d) of this Rule.~~

24           ~~(3) — The owner or operator of OSWI unit shall:~~

25           ~~(A) — install, calibrate to manufacturers specifications, maintain, and operate devices or establish~~  
26           ~~methods for monitoring or measuring the operating parameters as specified in 40 CFR~~  
27           ~~60.3043; and~~

28           ~~(B) — obtain operating parameter monitoring data as specified in 40 CFR 60.3044 to monitor~~  
29           ~~compliance with the operational standards in Paragraph (e) of this Rule.~~

30 ~~(i) Recordkeeping and Reporting. The owner or operators of an OSWI unit:~~

31           ~~(1) — shall maintain all records required specified in 40 CFR 60.3046;~~

32           ~~(2) — shall keep and submit records according to 40 CFR 60.3047;~~

33           ~~(3) — shall submit, as specified in 40 CFR 60.3048, the following reports:~~

34           ~~(A) — an initial test report and operating limits, as specified in 40 CFR 60.3049(a) and (b);~~

35           ~~(B) — a waste management plan as specified in 40 CFR 60.3049(c); and~~

36           ~~(C) — an annual report as specified in 40 CFR 60.3050 and 40 CFR 60.3051;~~

1 ~~(D) — a deviation report as specified in 40 CFR 60.3053 if a deviation from the operating limits~~  
2 ~~or the emission limitations occurs according to 40 CFR 60.3052(a); the deviation report~~  
3 ~~shall be submitted following 40 CFR 60.3052(b);~~

4 ~~(E) — a deviation report according to 40 CFR 60.3054(a) if a deviation from the requirement to~~  
5 ~~have a qualified operator accessible occurs;~~

6 ~~(4) — shall keep records and submit reports and notifications as required by 40 CFR 60.7;~~

7 ~~(5) — may request changing semiannual or annual reporting dates as specified in this Paragraph; the~~  
8 ~~Director may approve the request change using the procedures in 40 CFR 60.19(f).~~

9 ~~(6) — shall submit reports in electronic or paper format postmarked on or before the submittal due dates.~~

10 ~~(j) Excess Emissions and Start up and Shut down. All OSWI units shall comply with Rule .0535, Excess Emissions~~  
11 ~~Reporting and Malfunctions, of this Subchapter.~~

12 ~~(k) Operator Training and Certification.~~

13 ~~(1) — No OSWI unit shall be operated unless a fully trained and qualified OSWI unit operator is~~  
14 ~~accessible, either at the facility or available within one hour. The trained and qualified OSWI unit~~  
15 ~~operator may operate the OSWI unit directly or be the direct supervisor of one or more other plant~~  
16 ~~personnel who operate OSWI unit.~~

17 ~~(2) — Operator training and qualification shall be obtained by completing the requirements of 40 CFR~~  
18 ~~60.3014(e) by the latest of:~~

19 ~~(A) — January 1, 2010,~~

20 ~~(B) — six month after OSWI unit startup, or~~

21 ~~(C) — six month after an employee assumes responsibility for operating the OSWI unit or~~  
22 ~~assumes responsibility for supervising the operation of the OSWI unit.~~

23 ~~(3) — Operator qualification shall be valid from the date on which the training course is completed and~~  
24 ~~the operator successfully passes the examination required in 40 CFR 60.3014 (e)(2).~~

25 ~~(4) — Operator qualification shall be maintained by completing an annual review or refresher course~~  
26 ~~covering:~~

27 ~~(A) — update of regulations;~~

28 ~~(B) — incinerator operation, including startup and shutdown procedures, waste charging, and ash~~  
29 ~~handling;~~

30 ~~(C) — inspection and maintenance;~~

31 ~~(D) — responses to malfunctions or conditions that may lead to malfunction; and~~

32 ~~(E) — discussion of operating problems encountered by attendees.~~

33 ~~(5) — Lapsed operator qualification shall be renewed by:~~

34 ~~(A) — Completing a standard annual refresher course as specified in Subparagraph (4) of this~~  
35 ~~Paragraph for a lapse less than three years, and~~

36 ~~(B) — Repeating the initial qualification requirements as specified in Subparagraph (3) of this~~  
37 ~~Paragraph for a lapse of three years or more.~~

1 ~~(6) The owner or operator of the OSWI unit subject to the requirements of this Rule shall:~~

2 ~~(A) have documentation specified in 40 CFR 60.3019(a) and (c) available at the facility and~~  
3 ~~readily accessible for all OSWI unit operators and are suitable for inspection upon request;~~

4 ~~(B) establish a program for reviewing the documentation specified in Part (A) of this~~  
5 ~~Subparagraph with each OSWI unit operator in a manner that the initial review of the~~  
6 ~~information listed in Part (A) of this Subparagraph shall be conducted by the later of the~~  
7 ~~three dates: January 1, 2010, six month after OSWI unit startup, or six month after an~~  
8 ~~employee assumes responsibility for operating the OSWI unit or assumes responsibility for~~  
9 ~~supervising the operation of the OSWI unit; and subsequent annual reviews of the~~  
10 ~~information listed in Part (A) of this Subparagraph shall be conducted no later than twelve~~  
11 ~~month following the previous review.~~

12 ~~(7) The owner or operator of the OSWI unit shall follow the procedures in 40 CFR 60.3020 if all~~  
13 ~~qualified OSWI unit operators are temporarily not at the facility and not able to be at the facility~~  
14 ~~within one hour.~~

15 ~~(l) Waste Management Plan.~~

16 ~~(1) The owner or operator of the OSWI unit shall submit a waste management plan that identifies in~~  
17 ~~writing the feasibility and the methods used to reduce or separate components of solid waste from~~  
18 ~~the waste stream in order to reduce or eliminate toxic emissions from incinerated waste. A waste~~  
19 ~~management plan shall be submitted to the Director before September 1, 2010.~~

20 ~~(2) The waste management plan shall include:~~

21 ~~(A) consideration of the reduction or separation of waste stream elements such as paper,~~  
22 ~~cardboard, plastics, glass, batteries, or metals; and the use of recyclable materials;~~

23 ~~(B) identification of any additional waste management measures;~~

24 ~~(C) implementation of those measures considered practical and feasible, based on the~~  
25 ~~effectiveness of waste management measures already in place;~~

26 ~~(D) the costs of additional measures and the emissions reductions expected to be achieved; and~~

27 ~~(E) any other environmental or energy impacts.~~

28 ~~(m) Compliance Schedule.~~

29 ~~(1) This Paragraph applies only to OSWI that commenced construction on or before December 9, 2004.~~

30 ~~(2) The owner or operator of an OSWI unit shall submit a permit application, including a compliance~~  
31 ~~schedule, to the Director before January 1, 2008.~~

32 ~~(3) All OSWI shall be in compliance with this Rule no later than January 1, 2010.~~

33 ~~(4) The owner or operator of an CISWI unit shall notify the Director within 10 business days after the~~  
34 ~~OSWI unit is to be in final compliance whether the final compliance has been achieved. The final~~  
35 ~~compliance is achieved by completing all process changes and retrofitting construction of control~~  
36 ~~devices, as specified in the permit application and required by its permit, so that, if the affected~~  
37 ~~OSWI unit is brought on line, all necessary process changes and air pollution control devices would~~

1           ~~operate as designed and permitted. If the final compliance has not been achieved the owner or~~  
2           ~~operator of the OSWI unit, shall submit a notification informing the Director that the final~~  
3           ~~compliance has not been met and submit reports each subsequent calendar month until the final~~  
4           ~~compliance is achieved.~~

5           ~~(5) The owner or operator of an OSWI unit who closes the OSWI unit and restarts it before January 1,~~  
6           ~~2010 shall submit a permit application, including a compliance schedule, to the Director. Final~~  
7           ~~compliance shall be achieved by January 1, 2010.~~

8           ~~(6) The owner or operator of an OSWI unit who closes the OSWI unit and restarts it after January 1,~~  
9           ~~2010, shall submit a permit application to the Director and shall complete the emission control~~  
10           ~~retrofit and meet the emission limitations of this Rule by the date that the OSWI unit restarts~~  
11           ~~operation. The initial performance test shall be conducted within 30 days of restarting the OSWI~~  
12           ~~unit.~~

13           ~~(7) The permit applications for OSWI units shall be processed under 15A NCAC 02Q .0500, Title V~~  
14           ~~Procedures.~~

15           ~~(8) The owner or operator of an OSWI unit who plans to close it rather than comply with the~~  
16           ~~requirements of this Rule shall submit a closure notification including the date of closure to the~~  
17           ~~Director by January 1, 2008, and shall cease operation by January 1, 2010.~~

18  
19    *History Note:*    Authority *G.S. 143-215.3(a)(1); 143-215.65; 143-215.66; 143-215.107(a)(4), (5), (10); 40 CFR*  
20                    *60.3014 through 60.3020;*  
21                    *Eff. August 1, 2007, 2007;*  
22                    *Repealed Eff. \_\_\_\_\_.*  
23  
24

1 15A NCAC 02D .1212 is proposed for reoption as a repeal as follows:

2  
3 **15A NCAC 02D .1212 SMALL MUNICIPAL WASTE COMBUSTORS**

4 ~~(a) Applicability. This Rule applies to Class I municipal waste combustors, as defined in Rule .1202 of this Section.~~

5 ~~(b) Definitions. For the purpose of this Rule, the definitions contained in 40 CFR 60.1940 (except administrator means the Director of the Division of Air Quality) apply in addition to the definitions in Rule .1202 of this Section.~~

6 ~~(c) Emission Standards.~~

7  
8 ~~(1) The emission standards in this Paragraph apply to any municipal waste combustor subject to the~~  
9 ~~requirements of this Rule except where Rule .0524, .1110, or .1111 of this Subchapter applies.~~  
10 ~~However, when Subparagraphs (13) or (14) of this Paragraph and Rule .0524, .1110, or .1111 of~~  
11 ~~this Subchapter regulate the same pollutant, the more restrictive provision for each pollutant applies,~~  
12 ~~notwithstanding provisions of Rules .0524, .1110, or .1111 of this Subchapter to the contrary.~~

13 ~~(2) Particulate Matter. Emissions of particulate matter from each municipal waste combustor shall not~~  
14 ~~exceed 27 milligrams per dry standard cubic meter corrected to seven percent oxygen.~~

15 ~~(3) Visible Emissions. The emission limit for opacity from each municipal waste combustor shall not~~  
16 ~~exceed 10 percent average during any six minute period.~~

17 ~~(4) Sulfur Dioxide. Emissions of sulfur dioxide from each municipal waste combustor shall not exceed~~  
18 ~~31 parts per million by volume, dry basis, or potential sulfur dioxide emissions shall be reduced by~~  
19 ~~at least 75 percent volume, dry basis, whichever is less stringent. Percent reduction shall be~~  
20 ~~determined from continuous emissions monitoring data and in accordance with Reference Method~~  
21 ~~19, Section 12.5.4 of 40 CFR Part 60, Appendix A 7. Compliance with either standard is based on~~  
22 ~~a 24 hour daily block geometric average of concentration data corrected to seven percent oxygen.~~

23 ~~(5) Nitrogen Oxide. Emissions of nitrogen oxide from each municipal waste combustor shall not exceed~~  
24 ~~the emission limits in Table 3 of 40 CFR Part 60, Subpart BBBB.~~

25 ~~(6) Odorous Emissions. Each municipal waste combustor shall comply with Rule .1806 of this~~  
26 ~~Subchapter for the control of odorous emissions.~~

27 ~~(7) Hydrogen Chloride. Emissions of hydrogen chloride from each municipal waste combustor shall~~  
28 ~~not exceed 31 milligrams per dry standard cubic meter (31 parts per million by weight as determined~~  
29 ~~by Reference Method 26 or 26A of 40 CFR Part 60, Appendix A 8) or potential hydrogen chloride~~  
30 ~~emissions shall be reduced by at least 95 percent of the mass concentration, dry basis, whichever is~~  
31 ~~less stringent. Compliance with this Part shall be determined by averaging emissions over three one-~~  
32 ~~hour test runs, with paired data sets for percent reduction and correction to seven percent oxygen.~~

33 ~~(8) Mercury Emissions. Emissions of mercury from each municipal waste combustor shall not exceed~~  
34 ~~0.080 milligrams per dry standard cubic meter (as determined by Reference Method 29 of 40 CFR~~  
35 ~~Part 60, Appendix A 8) or potential mercury emissions shall be reduced by at least 85 percent of the~~  
36 ~~mass concentration, basis, whichever is less stringent. Compliance with this Subparagraph shall be~~

1 determined by averaging emissions over three one hour test runs, with paired data sets for percent  
2 reduction and correction to seven percent oxygen.

3 (9) ~~Lead Emissions. Emissions of lead from each municipal waste combustor shall not exceed 0.490~~  
4 ~~milligrams per dry standard cubic meter and corrected to seven percent oxygen (as determined by~~  
5 ~~Reference Method 29 of 40 CFR Part 60, Appendix A 8).~~

6 (10) ~~Cadmium Emissions. Emissions of cadmium from each municipal waste combustor shall not~~  
7 ~~exceed 0.040 milligrams per dry standard cubic meter, corrected to seven percent oxygen (as~~  
8 ~~determined by Reference Method 29 of 40 CFR Part 60, Appendix A 8).~~

9 (11) ~~Dioxins and Furans. Emissions of dioxins and furans from each municipal waste combustor shall~~  
10 ~~not exceed:~~

11 (A) ~~60 nanograms per dry standard cubic meter (total mass) for facilities that employ an~~  
12 ~~electrostatic precipitator based emission control system, or~~

13 (B) ~~30 nanograms per dry standard cubic meter (total mass) for facilities that do not employ an~~  
14 ~~electrostatic precipitator based emission control system.~~

15 Compliance with this Subparagraph shall be determined by averaging emissions over three test runs  
16 with a minimum four hour run duration, performed in accordance with Reference Method 23 of 40  
17 CFR Part 60, Appendix A 7, and corrected to seven percent oxygen.

18 (12) ~~Fugitive Ash.~~

19 (A) ~~On or after the date on which the initial performance test is completed, no owner or operator~~  
20 ~~of a municipal waste combustor shall cause to be discharged to the atmosphere visible~~  
21 ~~emissions of combustion ash from an ash conveying system (including conveyor transfer~~  
22 ~~points) in excess of five percent of the observation period as determined by Reference~~  
23 ~~Method 22 (40 CFR Part 60, Appendix A 7), except as provided in Part (B) of this~~  
24 ~~Subparagraph. Compliance with this Part shall be determined from at least three 1 hour~~  
25 ~~observation periods when the facility transfers ash from the municipal waste combustor to~~  
26 ~~the area where the ash is stored or loaded into containers or trucks.~~

27 (B) ~~The emission limit specified in Part (A) of this Subparagraph covers visible emissions~~  
28 ~~discharged to the atmosphere from buildings or enclosures, not the visible emissions~~  
29 ~~discharged inside of the building or enclosures, of ash conveying systems.~~

30 (13) ~~Toxic Emissions. The owner or operator of a municipal waste combustor shall demonstrate~~  
31 ~~compliance with Section .1100 of this Subchapter in accordance with 15A NCAC 02Q .0700.~~

32 (14) ~~Ambient Standards.~~

33 (A) ~~In addition to the ambient air quality standards in Section .0400 of this Subchapter, the~~  
34 ~~following annual average ambient air quality standards in milligrams per cubic meter (77~~  
35 ~~degrees Fahrenheit, 25 degrees Celsius, and 29.92 inches, 760 millimeters of mercury~~  
36 ~~pressure) are arsenic and its compounds ( $2.3 \times 10^{-7}$ ), beryllium and its compounds ( $4.1 \times 10^{-7}$~~   
37 ~~), cadmium and its compounds ( $5.5 \times 10^{-6}$ ), and chromium (VI) and its compounds~~



1 ~~( $8.3 \times 10^{-8}$ ). These are increments above background concentrations and apply aggregately~~  
2 ~~to all municipal waste combustors at a facility.~~

3 ~~(B) — The owner or operator of a facility with municipal waste combustors shall demonstrate~~  
4 ~~compliance with the ambient standards in Part (A) of this Subparagraph by following the~~  
5 ~~procedures set out in Rule .1106 of this Subchapter. Modeling demonstrations shall~~  
6 ~~comply with the good engineering practice stack height requirements of Rule .0533 of this~~  
7 ~~Subchapter.~~

8 ~~(C) — The emission rates computed or used under Part (B) of this Subparagraph that demonstrate~~  
9 ~~compliance with the ambient standards under Part (A) of this Subparagraph shall be~~  
10 ~~specified as a permit condition for the facility with municipal waste combustors as their~~  
11 ~~allowable emission limits unless Rule .0524, .1110, or .1111 of this Subchapter requires~~  
12 ~~more restrictive rates.~~

13 ~~(15) — The emission standards of Subparagraphs (1) through (14) of this Paragraph apply at all times except~~  
14 ~~during periods of municipal waste combustor startup, shutdown, or malfunction that last no more~~  
15 ~~than three hours.~~

16 ~~(d) Operational Standards.~~

17 ~~(1) — The operational standards in this Rule do not apply to any municipal waste combustors subject to~~  
18 ~~this Rule when applicable operational standards in Rule .0524, .1110, or .1111 of this Subchapter~~  
19 ~~apply.~~

20 ~~(2) — Each municipal waste combustor shall meet the following operational standards:~~

21 ~~(A) — The concentration of carbon monoxide at the municipal waste combustor outlet shall not~~  
22 ~~exceed the concentration in Table 5 of 40 CFR Part 60, Subpart BBBB for each municipal~~  
23 ~~waste combustor. The municipal waste combustor technology named in this table is~~  
24 ~~defined in 40 CFR 60.1940.~~

25 ~~(B) — The load level shall not exceed 110 percent of the maximum demonstrated municipal waste~~  
26 ~~combustor load determined from the highest four hour block arithmetic average achieved~~  
27 ~~during four consecutive hours in the course of the most recent dioxins and furans stack test~~  
28 ~~that demonstrates compliance with the emission limits of Paragraph (c) of this Rule.~~

29 ~~(C) — The temperature at which the combustor operates measured at the particulate matter control~~  
30 ~~device inlet shall not exceed 63 degrees F (17 degrees C) above the maximum~~  
31 ~~demonstrated particulate matter control device temperature determined from the highest 4-~~  
32 ~~hour block arithmetic average measured at the inlet of the particulate matter control device~~  
33 ~~during four consecutive hours in the course of the most recent dioxins and furans stack test~~  
34 ~~that demonstrates compliance with the emission limits of Paragraph (c) of this Rule.~~

35 ~~(D) — The owner or operator of a municipal waste combustor with activated carbon control~~  
36 ~~system to control dioxins and furans or mercury emissions shall maintain an eight hour~~  
37 ~~block average carbon feed rate at or above the highest average level established during the~~

1 most recent dioxins and furans or mercury test. The owner or operator of a municipal waste  
2 combustor shall calculate the required quarterly usage of carbon using the equation in 40  
3 CFR 60.1935(f).

4 ~~(E) — The owner or operator of a municipal waste combustor is exempted from limits on load  
5 level, temperature at the inlet of the particular matter control device, and carbon feed rate  
6 during the annual tests for dioxins and furans, the annual mercury tests (for carbon feed  
7 requirements only), the two weeks preceding the annual tests for dioxins and furans, and  
8 the two weeks preceding the annual mercury tests (for carbon feed rate requirements only).~~

9 ~~(F) — The limits on load level for a municipal waste combustor are waived when the Director  
10 concludes that the emission control standards would not be exceeded based on test  
11 activities to evaluate system performance, test new technology or control technology,  
12 perform diagnostic testing, perform other activities to improve the performance; or perform  
13 other activities to advance the state of the art for emissions controls.~~

14 ~~(3) — The operational standards of this Paragraph apply at all times except during periods of municipal  
15 waste combustor startup, shutdown, or malfunction that last no more than three hours. For periods  
16 of municipal waste combustor startup, shutdown, or malfunction that last more than three hours  
17 emission data shall not be discarded from compliance calculations and all provisions of 40 CFR  
18 60.11(d) apply. During all periods of municipal waste combustor startup, shutdown, or malfunction,  
19 data shall be recorded and reported in accordance with the provisions of Paragraphs (f) and (g) of  
20 this Rule.~~

21 ~~(e) Test Methods and Procedures.~~

22 ~~(1) — References contained in Table 8 of 40 CFR Part 60, Subpart BBBBB shall be used to determine the  
23 sampling location, pollutant concentrations, number of traverse points, individual test methods, and  
24 other testing requirements for the different pollutants.~~

25 ~~(2) — Stack tests for all the pollutants shall consist of at least three test runs, as specified in 40 CFR 60.8  
26 and use the average of the pollutant emission concentrations from the three test runs to determine  
27 compliance with the applicable emission limits of Paragraph (e).~~

28 ~~(3) — An oxygen (or carbon dioxide) measurement shall be obtained at the same time as pollutant  
29 measurements to determine diluent gas levels, as specified in 40 CFR 60.1720.~~

30 ~~(4) — The equations in 40 CFR 60.1935 shall be used to calculate emission levels at seven percent oxygen  
31 (or an equivalent carbon dioxide basis), the percent reduction in potential hydrogen chloride  
32 emissions, and the reduction efficiency for mercury emissions. Other required equations are  
33 contained in individual test methods specified in Table 6 of 40 CFR Part 60, Subpart BBBBB.~~

34 ~~(5) — The owner or operator may apply to the Director for approval under 40 CFR 60.8(b) to use a  
35 reference method with minor changes in methodology, use an equivalent method, use an alternative  
36 method the results of which the Director has determined are adequate for demonstrating compliance,~~

1 waive the requirement for a performance test because the owner or operator have demonstrated  
2 compliance by other means, or use a shorter sampling time or smaller sampling volume.

3 (6) — The test methods and procedures described in Section 15A NCAC 02D .2600 of this Subchapter, 40  
4 CFR Part 60, Appendix A and 40 CFR Part 61, Appendix B shall be used to determine compliance  
5 with emission standards in Paragraph (c) according to table 8 of 40 CFR Part 60, Subpart BBBB.

6 (7) — Method 29 of 40 CFR Part 60, Appendix A 8 shall be used to determine emission rates for metals  
7 for toxic evaluations except for chromium (VI). Method 29 shall be used only to collect samples  
8 and SW 846 Method 0060 shall be used to analyze the samples of chromium (VI).

9 (8) — The owner or operator shall conduct initial stack tests to measure the emission levels of dioxins and  
10 furans, cadmium, lead, mercury, beryllium, arsenic, chromium (VI), particulate matter, opacity,  
11 hydrogen chloride, and fugitive ash. Annual stack tests for the same pollutants except beryllium,  
12 arsenic, and chromium (VI) shall be conducted no less than 9 months and no more than 15 months  
13 since the previous test and must complete five performance tests in each five year calendar period.

14 (9) — The owner or operator must use results of stack tests for dioxins and furans, cadmium, lead, mercury,  
15 particulate matter, opacity, hydrogen chloride, and fugitive ash to demonstrate compliance with the  
16 applicable emission limits in this rule except for carbon monoxide, nitrogen oxides, and sulfur  
17 dioxide.

18 (10) — The owner or operator must use results of continuous emissions monitoring of carbon monoxide,  
19 nitrogen oxides, and sulfur dioxide to demonstrate compliance with the applicable emission limits  
20 in this rule. The data from the continuous opacity monitoring system shall not be used to determine  
21 compliance with the opacity limit.

22 (11) — The testing frequency for dioxin and furan may be reduced if the conditions under 40 CFR  
23 60.1795(b) are met.

24 (12) — The Director may require the owner or operator of any municipal waste combustor subject to this  
25 Rule to test his municipal waste combustor to demonstrate compliance with the emission standards  
26 in Paragraph (c) of this Rule.

27 (f) Monitoring, Recordkeeping, and Reporting.

28 (1) — The owner or operator shall comply with the monitoring, recordkeeping, and reporting requirements  
29 developed pursuant to Section .0600 of this Subchapter.

30 (2) — The owner or operator that has installed air pollution abatement equipment to reduce emissions of  
31 hydrogen chloride shall install, operate, and maintain continuous parametric monitoring equipment  
32 to measure pH for wet scrubber systems and rate of alkaline injection for dry scrubber systems.

33 (3) — The owner or operator shall:

34 (A) — install, calibrate, operate, and maintain, for each municipal waste combustor, continuous  
35 emission monitors to determine opacity, sulfur dioxide emissions, nitrogen oxides  
36 emissions, carbon monoxide, and oxygen (or carbon dioxide) according to 40 CFR 60.1715  
37 through 60.1770;

1 ~~(B) — monitor load level of each municipal waste combustor according to 40 CFR 60.1810 and~~  
2 ~~60.1825;~~

3 ~~(C) — monitor temperature of the flue gases at the inlet of the particulate matter air pollution~~  
4 ~~control device according to 40 CFR 60.1815 and 60.1825;~~

5 ~~(D) — monitor carbon feed rate if activated carbon is used to abate dioxins and furans or mercury~~  
6 ~~emissions according to 40 CFR 60.1820 and 60.1825;~~

7 ~~(E) — maintain records of the information listed in 40 CFR 60.1830 through 60.1855 for a period~~  
8 ~~of at least five years;~~

9 ~~(F) — submit a semiannual report specified in 40 CFR 60.1885, no later than February 1 and~~  
10 ~~August 1 each year; and~~

11 ~~(G) — submit semiannual reports specified in 40 CFR 60.1900 of any recorded pollutant or~~  
12 ~~parameter that does not comply with the pollutant or parameter limit specified in this~~  
13 ~~Section using the schedule specified in 40 CFR 60.1895.~~

14 ~~(g) Excess Emissions and Start up and Shut down. All municipal waste combustors subject to this Rule shall comply~~  
15 ~~with Rule .0535, Excess Emissions Reporting and Malfunctions, of this Subchapter.~~

16 ~~(h) Operator Certification.~~

17 ~~(1) — Each chief facility operator and shift supervisor shall obtain and keep a current provisional~~  
18 ~~certification within six months after he transfers to the municipal waste combustion facility or six~~  
19 ~~months after he is hired to work at the municipal waste combustor facility.~~

20 ~~(2) — Each chief facility operator and shift supervisor shall have obtained a full certification or have~~  
21 ~~scheduled a full certification exam with the American Society of Mechanical Engineers (ASME~~  
22 ~~QRO 1 1994) after he transfers to the municipal waste combustor facility or six months after he is~~  
23 ~~hired to work at the municipal waste combustor facility.~~

24 ~~(3) — The owner or operator of a municipal waste combustor facility shall not allow the facility to be~~  
25 ~~operated at any time unless one of the following persons is on duty at the affected facility:~~

26 ~~(A) — a fully certified chief facility operator;~~

27 ~~(B) — a provisionally certified chief facility operator who is scheduled to take the full certification~~  
28 ~~exam;~~

29 ~~(C) — a fully certified shift supervisor; or~~

30 ~~(D) — a provisionally certified shift supervisor who is scheduled to take the full certification~~  
31 ~~exam.~~

32 ~~(4) — If the certified chief facility operator and certified shift supervisor both are unavailable, a~~  
33 ~~provisionally certified control room operator at the municipal waste combustor may fulfill the~~  
34 ~~certified operator requirement. Depending on the length of time that a certified chief facility~~  
35 ~~operator and certified shift supervisor are away, one of three criteria shall be met:~~

1 ~~(A) — When the certified chief facility operator and certified shift supervisor are both offsite for~~  
2 ~~12 hours or less and no other certified operator is on site, the provisionally certified control~~  
3 ~~room operator may perform those duties without notice to or approval by the Director.~~

4 ~~(B) — When the certified chief facility operator and certified shift supervisor are offsite for more~~  
5 ~~than 12 hours, but for two weeks or less, and no other certified operator is on site, the~~  
6 ~~provisionally certified control room operator may perform those duties without notice to~~  
7 ~~or approval by the Director. However, the owner or operator must record the periods when~~  
8 ~~the certified chief facility operator and certified shift supervisor are offsite and include the~~  
9 ~~information in the annual report as specified under 40 CFR 60.1885(l).~~

10 ~~(C) — When the certified chief facility operator and certified shift supervisor are offsite for more~~  
11 ~~than two weeks and no other certified operator is on site, the provisionally certified control~~  
12 ~~room operator may perform those duties without notice to or approval by the Director.~~  
13 ~~However, the owner or operator shall notify the Director in writing and submit a status~~  
14 ~~report and corrective action summary to the Director every four weeks. In the notice, the~~  
15 ~~owner or operator shall state what caused the absence and what is being done to ensure that~~  
16 ~~a certified chief facility operator or certified shift supervisor is on site. If the Director~~  
17 ~~notifies the owner or operator that the status report or corrective action summary is~~  
18 ~~disapproved, the municipal waste combustor may continue operation for 90 days, but then~~  
19 ~~shall cease operation. If corrective actions are taken in the 90 day period such that the~~  
20 ~~Director withdraws the disapproval, municipal waste combustor operations may continue.~~

21 ~~(D) — The Director shall disapprove the status report and corrective action summary report,~~  
22 ~~described in Part (C) of this Subparagraph, if operating permit requirements are not being~~  
23 ~~met, the status or corrective action reports indicate that the effort to have a certified chief~~  
24 ~~facility operator or certified shift supervisor on site as expeditiously as practicable is not~~  
25 ~~being met, or the reports are not delivered in a timely manner.~~

26 ~~The referenced ASME exam (ASME QRO 1 1994), "Standard for the Qualification and Certification of Resource~~  
27 ~~Recovery Facility Operators," in this Paragraph is hereby incorporated by reference and includes subsequent~~  
28 ~~amendments and editions. Copies of the referenced ASME exam may be obtained from the American Society of~~  
29 ~~Mechanical Engineers (ASME), 22 Law Drive, Fairfield, NJ 07007, at a cost of forty nine dollars (\$49.00).~~

30 ~~(i) Training.~~

31 ~~(1) — The owner or operator of each municipal waste combustor shall develop and update on a yearly~~  
32 ~~basis a site specific operating manual that shall address:~~

33 ~~(A) — a summary of all applicable requirements in this Rule;~~

34 ~~(B) — a description of the basic combustion principles that apply to municipal waste combustors;~~

35 ~~(C) — procedures for receiving, handling, and feeding municipal solid waste;~~

36 ~~(D) — procedures to be followed during periods of startup, shutdown, and malfunction of the~~  
37 ~~municipal waste combustor;~~

- ~~(E) — procedures for maintaining a proper level of combustion air supply;~~
- ~~(F) — procedures for operating the municipal waste combustor in compliance with the requirements contained in 40 CFR 60 Subpart JJJ;~~
- ~~(G) — procedures for responding to periodic upset or off specification conditions;~~
- ~~(H) — procedures for minimizing carryover of particulate matter;~~
- ~~(I) — procedures for handling ash;~~
- ~~(J) — procedures for monitoring emissions from the municipal waste combustor; and~~
- ~~(K) — procedures for recordkeeping and reporting.~~

~~The operating manual shall be updated continually and be kept in a readily accessible location for all persons required to undergo training under Subparagraph (2) of this Paragraph. The operating manual and records of training shall be available for inspection by the personnel of the Division on request.~~

- ~~(2) — The owner or operator of the municipal waste combustor plant shall establish a training program to review the operating manual according to the schedule specified in Parts (A) and (B) of this Subparagraph with each person who has responsibilities affecting the operation of the facility including chief facility operators, shift supervisors, control room operators, ash handlers, maintenance personnel, and crane and load handlers:~~

~~(A) — A date prior to the day when the person assumes responsibilities affecting municipal waste combustor operation; and~~

~~(B) — Annually, following the initial training required by Part (A) of this Subparagraph.~~

*History Note: Authority G.S. 143-215.3(a)(1); 143-215.107(a)(3),(4),(5); 40 CFR 60.35b; 40 CFR 60.34e; 40 CFR 60.1515;  
Eff. July 1, 2010-2010;  
Repealed Eff. \_\_\_\_\_.*

1 15A NCAC 02Q .0701 is proposed for readoption without substantive changes as follows:

2

3

**SECTION .0700 – TOXIC AIR POLLUTANT PROCEDURES**

4

**15A NCAC 02Q .0701 APPLICABILITY**

6 With the exceptions in ~~Rule .0702 of this Section,~~ 15A NCAC 02Q .0702, no person shall cause or allow any toxic air  
7 pollutant named in 15A NCAC 02D .1104 to be emitted from any facility into the atmosphere at a rate that exceeds  
8 the applicable rate(s) in ~~Rule .0711 of this Section,~~ 15A NCAC 02Q .0711 without having received a permit to emit  
9 toxic air pollutants as follows:

10 (1) new facilities according to ~~Rule .0704 of this Section,~~ 15A NCAC 02Q .0704; or

11 (2) modifications according to ~~Rule .0706 of this Section,~~ 15A NCAC 02Q .0706.

12

13 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107; 143-215.108; 143B-282;*

14 *Rule originally codified as part of 15A NCAC 2H .0610;*

15 *Eff. July 1, 1998;*

16 *Amended Eff. May 1, 2014; July 10, 2010; February 1, ~~2005,~~ 2005;*

17 *Readopted Eff.*

18

19

1 15A NCAC 02Q .0702 is proposed for reoption with substantive changes as follows:  
2

3 **15A NCAC 02Q .0702 EXEMPTIONS**

4 (a) A permit to emit toxic air pollutants shall not be required under this Section for:

- 5 (1) residential wood stoves, heaters, or fireplaces;
- 6 (2) ~~hot~~ water heaters that are used for domestic purposes only and are not used to heat process water;
- 7 (3) maintenance, structural changes, or repairs that do not change capacity of that process, fuel-burning,  
8 refuse-burning, or control equipment, and do not involve any change in quality or nature or increase  
9 in quantity of emission of any regulated air pollutant or toxic air pollutant;
- 10 (4) housekeeping activities or building maintenance procedures, including painting buildings,  
11 resurfacing floors, roof repair, washing, portable vacuum cleaners, sweeping, use and associated  
12 storage of janitorial products, or non-asbestos bearing insulation removal;
- 13 (5) use of office supplies, supplies to maintain copying equipment, or blueprint machines;
- 14 (6) paving parking lots;
- 15 (7) replacement of existing equipment with equipment of the same size, type, and function if the new  
16 equipment:
  - 17 (A) does not result in an increase to the actual or potential emissions of any regulated air  
18 pollutant or toxic air pollutant;
  - 19 (B) does not affect compliance status; and
  - 20 (C) fits the description of the existing equipment in the permit, including the application, such  
21 that the replacement equipment can be operated under that permit without any changes to  
22 the permit;
- 23 (8) comfort air conditioning or comfort ventilation systems that do not transport, remove, or exhaust  
24 regulated air pollutants to the atmosphere;
- 25 (9) equipment used for the preparation of food for direct on-site human consumption;
- 26 (10) non-self-propelled non-road ~~engines, except generators, engines~~ regulated by rules adopted by the  
27 Environmental Protection Agency under Title II of the federal Clean Air ~~Act, Act, except generators~~;
- 28 (11) stacks or vents to prevent escape of sewer gases from domestic waste through plumbing traps;
- 29 (12) use of fire fighting equipment;
- 30 (13) the use for agricultural operations by a farmer of fertilizers, pesticides, or other agricultural  
31 chemicals containing one or more of the compounds listed in 15A NCAC 02D .1104 if such  
32 compounds are applied according to agronomic practices for agricultural operations acceptable to  
33 the North Carolina Department of Agriculture;
- 34 (14) asbestos demolition and renovation projects that comply with 15A NCAC 02D .1110 and that are  
35 being done by persons accredited by the Department of Health and Human Services under the  
36 Asbestos Hazard Emergency Response Act;



- 1 (15) incinerators used only to dispose of dead animals or poultry as identified in 15A NCAC 02D  
2 ~~.1201(e)(4), 1201(b)(4)~~ or incinerators used only to dispose of dead pets as identified in 15A NCAC  
3 02D .1208(a)(2)(A);
- 4 (16) refrigeration equipment that is consistent with Section 601 through 618 of Title VI (Stratospheric  
5 Ozone Protection) of the federal Clean Air Act, 40 CFR Part 82, and any other regulations  
6 promulgated by EPA under Title VI for stratospheric ozone protection, except those units used as  
7 or with air pollution control equipment;
- 8 (17) laboratory activities:
- 9 (A) bench-scale, on-site equipment used exclusively for chemical or physical analysis for  
10 quality control purposes, staff instruction, water or wastewater analyses, or non-production  
11 environmental compliance assessments;
- 12 (B) bench scale experimentation, chemical or physical analyses, training or instruction from  
13 nonprofit, non-production educational laboratories;
- 14 (C) bench scale experimentation, chemical or physical analyses, training or instruction from  
15 hospital or health laboratories pursuant to the determination or diagnoses of illnesses; and
- 16 (D) research and development laboratory activities that are not required to be permitted under  
17 ~~Section .0500 of this Subchapter~~ 15A NCAC 02Q .0500 provided the activity produces no  
18 commercial product or feedstock material;
- 19 (18) combustion sources as defined in ~~Rule .0703 of this Section~~ 15A NCAC 02Q .0703, ~~except new or~~  
20 ~~modified combustion sources permitted on or after July 10, 2010;~~ that are not exempt pursuant to  
21 Subparagraph (a)(27) of this Rule;
- 22 (19) storage tanks used only to store:
- 23 (A) inorganic liquids with a true vapor pressure less than 1.5 pounds per square inch absolute;
- 24 (B) fuel oils, kerosene, diesel, crude oil, used motor oil, lubricants, cooling oils, natural gas,  
25 liquefied petroleum gas, or petroleum products with a true vapor pressure less than 1.5  
26 pounds per square inch absolute;
- 27 (20) dispensing equipment used solely to dispense diesel fuel, kerosene, lubricants or cooling oils;
- 28 (21) portable solvent distillation systems that are ~~exempted under Rule .0102(e)(1)(I) of this Subchapter;~~  
29 used for on-site solvent recycling if:
- 30 (A) the portable solvent distillation system is not owned by the facility;
- 31 (B) the portable solvent distillation system is not operated for more than seven consecutive  
32 days; and
- 33 (C) the material recycled is recycled at the site of origin;
- 34 (22) processes:
- 35 (A) electric motor burn-out ovens with secondary combustion chambers or afterburners;
- 36 (B) electric motor bake-on ovens;
- 37 (C) burn-off ovens for paint-line hangers with afterburners;

- 1 (D) hosiery knitting machines and associated lint screens, hosiery dryers and associated lint  
2 screens, and hosiery dyeing processes where bleach or solvent dyes are not used;
- 3 (E) blade wood planers planing only green wood;
- 4 (F) saw mills that saw no more than 2,000,000 board feet per year, provided only green wood  
5 is sawed;
- 6 ~~(G) perchloroethylene drycleaning processes with 12 month rolling total consumption of:~~  
7 ~~(i) less than 1366 gallons of perchloroethylene per year for facilities with dry to dry~~  
8 ~~machines only;~~  
9 ~~(ii) less than 1171 gallons of perchloroethylene per year for facilities with transfer~~  
10 ~~machines only; or~~  
11 ~~(iii) less than 1171 gallons of perchloroethylene per year for facilities with both~~  
12 ~~transfer and dry to dry machines;~~
- 13 (23) wood furniture manufacturing operations as defined in 40 CFR 63.801(a) that comply with the  
14 emission limitations and other requirements of 40 CFR Part 63 Subpart JJ, provided that the terms  
15 of this exclusion shall not affect the authority of the Director under ~~Rule .0712 of this Section;~~ 15A  
16 NCAC 02Q .0712;
- 17 (24) wastewater treatment systems at pulp and paper mills for hydrogen sulfide and methyl mercaptan  
18 only;
- 19 (25) natural gas and propane fired combustion sources with an aggregate allowable heat input value less  
20 than 450 million Btu per hour that are the only source of benzene at the facility;
- 21 (26) emergency engines with an aggregate total horsepower less than 4843 horsepower that are the only  
22 source of formaldehyde at the facility;
- 23 (27) an air emission source that is any of the following:  
24 (A) subject to an applicable requirement under 40 CFR Part 61, as amended;  
25 (B) an affected source under 40 CFR Part 63, as amended; or  
26 (C) subject to a case-by-case MACT permit requirement issued by the Division pursuant to  
27 Paragraph (j) of 42 U.S.C. Section 7412, as amended;
- 28 (28) gasoline dispensing facilities or gasoline service station operations that comply with 15A NCAC  
29 02D .0928 and .0932 and that receive gasoline from bulk gasoline plants or bulk gasoline terminals  
30 that comply with 15A NCAC 02D .0524, .0925, .0926, .0927, .0932, and .0933 via tank trucks that  
31 comply with 15A NCAC 02D .0932;
- 32 (29) the use of ethylene oxide as a sterilant in the production and subsequent storage of medical devices  
33 or the packaging and subsequent storage of medical devices for sale if the emissions from all new  
34 and existing sources at the facility described in 15A NCAC 02D .0538(d) are controlled to the degree  
35 described in 15A NCAC 02D .0538(d) and the facility complies with 15A NCAC 02D .0538(e) and  
36 (f);

1 (30) bulk gasoline plants, including the storage and handling of fuel oils, kerosenes, and jet fuels but  
2 excluding the storage and handling of other organic liquids, that comply with 15A NCAC 02D  
3 .0524, .0925, .0926, .0932, and .0933; unless the Director finds that a permit to emit toxic air  
4 pollutants is required under Paragraph (b) of this Rule or ~~Rule .0712 of this Section~~ 15A NCAC 02Q  
5 .0712 for a particular bulk gasoline plant; or

6 (31) bulk gasoline terminals, including the storage and handling of fuel oils, kerosenes, and jet fuels but  
7 excluding the storage and handling of other organic liquids, that comply with 15A NCAC 02D  
8 .0524, .0925, .0927, .0932, and .0933 if the bulk gasoline terminal existed before November 1, 1992,  
9 unless:

10 (A) the Director finds that a permit to emit toxic air pollutants is required under Paragraph (b)  
11 of this Rule or ~~Rule .0712 of this Section~~ 15A NCAC 02Q .0712 for a particular bulk  
12 gasoline terminal; or

13 (B) the owner or operator of the bulk gasoline terminal meets the requirements of 15A NCAC  
14 02D .0927(i).

15 (b) Emissions from the activities identified in Subparagraphs (a)(28) through (a)(31) of this Rule shall be included in  
16 determining compliance with the toxic air pollutant requirements in this Section and shall be included in the permit if  
17 necessary to assure compliance. Emissions from the activities identified in Subparagraphs (a)(1) through (a)(27) of  
18 this Rule shall not be included in determining compliance with the toxic air pollutant requirements in this Section  
19 provided that the terms of this exclusion shall not affect the authority of the Director under ~~Rule .0712 of this~~  
20 ~~Section~~ 15A NCAC 02Q .0712.

21 (c) The addition or modification of an activity identified in Paragraph (a) of this Rule shall not cause the source or  
22 facility to be evaluated for emissions of toxic air pollutants.

23 (d) ~~An activity~~ A source that is exempt from being permitted under this Section ~~is shall~~ not be exempt from any  
24 applicable requirement other than those pursuant to 15A NCAC 02Q .0700 and 02D .1100. ~~or that the~~ Additionally,  
25 the owner or operator of the source is shall not be exempted from demonstrating compliance with any applicable  
26 ~~requirement.~~ requirement other than those exempted under 15A NCAC 02Q .0700 and 02D .1100.

27  
28 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107; 143-215.108; 143B-282;*

29 *Rule originally codified as part of 15A NCAC 02H .0610;*

30 *Eff. July 1, 1998;*

31 *Amended Eff. May 1, 2014; July 10, 2010; April 1, 2005; July 1, 2002; July 1, ~~2000~~, 2000;*

32 *Readopted Eff. \_\_\_\_\_.*

1 15A NCAC 02Q .0703 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02Q .0703 DEFINITIONS**

4 For the purposes of this Section, the following definitions apply:

5 (1) "Actual rate of emissions" means:

6 (a) for existing sources:

7 (i) for toxic air pollutants with an annual averaging period, the average rate or rates  
8 at which the source actually emitted the pollutant during the two-year period  
9 preceding the date of the particular modification and that represents normal  
10 operation of the source. If this period does not represent normal operation, the  
11 Director may allow the use of a different, more representative, period.

12 (ii) for toxic air pollutants with a 24-hour or one-hour averaging period, the maximum  
13 actual emission rate at which the source actually emitted for the applicable  
14 averaging period during the two-year period preceding the date of the particular  
15 modification and that represents normal operation of the source. If this period  
16 does not represent normal operation, the Director may require or allow the use of  
17 a different, more representative, period.

18 (b) for new or modified sources, the average rate or rates, determined for the applicable  
19 averaging period(s), that the proposed source will actually emit the pollutant as determined  
20 by engineering evaluation.

21 (2) "Applicable averaging period" means the averaging period for which an acceptable ambient limit  
22 has been established by the Commission in ~~Rule 15A NCAC 02D .1104.~~ .1104, including the  
23 provisions in 15A NCAC 02D .1106(d).

24 (3) "Bioavailable chromate pigments" means the group of chromium (VI) compounds consisting of  
25 calcium chromate (CAS No.13765-19-0), calcium dichromate (CAS No. 14307-33-6), strontium  
26 chromate (CAS No. 7789-06-2), strontium dichromate (CAS No. 7789-06-2), zinc chromate (CAS  
27 No. 13530-65-9), and zinc dichromate (CAS No. 7789-12-0).

28 (4) "CAS Number" means the Chemical Abstract Service registry number identifying a particular  
29 substance.

30 (5) "Chromium (VI) equivalent" means the molecular weight ratio of the chromium (VI) portion of a  
31 compound to the total molecular weight of the compound multiplied by the associated compound  
32 emission rate or concentration at the facility.

33 (6) "Combustion sources" means boilers, space heaters, process heaters, internal combustion engines,  
34 and combustion turbines, which ~~burn only wood or unadulterated fossil fuel.~~ combusts wood,  
35 unadulterated fossil fuels, or non-hazardous secondary materials that are not solid wastes pursuant  
36 to 40 CFR Part 241. It does not include incinerators, waste combustors, kilns, dryers, or direct heat  
37 exchange industrial processes.

- 1 (7) "Creditable emissions" means actual ~~decreased emissions~~ emission decreases that have not been  
2 previously relied on to comply with Subchapter 15A NCAC 02D. All credible emissions shall be  
3 enforceable by permit condition.
- 4 (8) "Cresol" means o-cresol, p-cresol, m-cresol, or any combination of these compounds.
- 5 (9) "Evaluation" means:
- 6 (a) a determination that the emissions from the facility, including emissions from sources  
7 exempted by Rule 15A NCAC 02Q .0702(a)(28) through ~~(31) of this Section, (31)~~, are  
8 less than the rate listed in ~~Rule .0711 of this Section;~~ 15A NCAC 02Q .0711; or
- 9 (b) a determination of ambient air concentrations as described under 15A NCAC 02D .1106,  
10 including emissions from sources exempted by Rule 15A NCAC 02Q .0702(a)(28) through  
11 ~~(31) of this Section. (31)~~.
- 12 (10) "GACT" means any generally available control technology emission standard applied to an area  
13 source or facility pursuant to Section 112 of the federal Clean Air Act.
- 14 (11) "Hexane isomers except n-hexane" means 2-methyl pentane, 3-methyl pentane, 2,2-dimethyl  
15 butane, 2,3-dimethyl butane, or any combination of these compounds.
- 16 (12) "MACT" means any maximum achievable control technology emission standard applied to a source  
17 or facility pursuant to Section 112 federal Clean Air Act.
- 18 (13) "Maximum feasible control" means the maximum degree of reduction for each pollutant subject to  
19 regulation under this Section using the best technology that is available taking into account, on a  
20 case-by-case basis, human health, energy, environmental, and economic impacts and other costs.
- 21 (14) "Modification" means any physical changes or changes in the methods of operation that result in a  
22 net increase in emissions or ambient concentration of any pollutant listed in ~~Rule .0711 of this~~  
23 ~~Section~~ 15A NCAC 02Q .0711 or that result in the emission of any pollutant listed in ~~Rule .0711~~  
24 ~~of this Section~~ 15A NCAC 02Q .0711 not previously emitted.
- 25 (15) "Net increase in emissions" means for a modification the sum of any increases in permitted  
26 allowable and decreases in the actual rates of emissions from the proposed modification from the  
27 sources at the facility for which the air permit application is being filed. If the net increase in  
28 emissions from the proposed modification is greater than zero, all other increases in permitted  
29 allowable and decreases in the actual rates of emissions at the facility within five years immediately  
30 preceding the filing of the air permit application for the proposed modification that are otherwise  
31 creditable emissions may be included.
- 32 (16) "Nickel, soluble compounds" means the soluble nickel salts of chloride ( $\text{NiCl}_2$ , CAS No. 7718-54-  
33 9), sulfate ( $\text{NiSO}_4$ , CAS No. 7786-81-4), and nitrate ( $\text{Ni}(\text{NO}_3)_2$ , CAS No. 13138-45-9).
- 34 (17) "Non-specific chromium (VI) compounds" means the group of compounds consisting of any  
35 chromium (VI) compounds not specified in this Section as a bioavailable chromate pigment or a  
36 soluble chromate compound.

1 (18) "Polychlorinated biphenyls" means any chlorinated biphenyl compound or mixture of chlorinated  
2 biphenyl compounds.

3 (19) "Pollution prevention plan" means a written description of current and projected plans to reduce,  
4 prevent, or minimize the generation of pollutants by source reduction and recycling and includes a  
5 site-wide assessment of pollution prevention opportunities at a facility that addresses sources of air  
6 pollution, water pollution, and solid and hazardous waste generation.

7 ~~(20) "SIC" means standard industrial classification code.~~

8 ~~(21)~~(20) "Soluble chromate compounds" means the group of chromium (VI) compounds consisting of  
9 ammonium chromate (CAS No. 7788-98-9), ammonium dichromate (CAS No. 7789-09-5), chromic  
10 acid (CAS No. 7738-94-5), potassium chromate (CAS No. 7789-00-6), potassium dichromate (CAS  
11 No. 7778-50-9), sodium chromate (CAS No. 7775-11-3), and sodium dichromate (CAS No. 10588-  
12 01-9).

13 ~~(22) "Toxic air pollutant" means any of those carcinogens, chronic toxicants, acute systemic toxicants,  
14 or acute irritants listed in 15A NCAC 02D .1104.~~

15  
16 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107; 143-215.108; 143B-282;*  
17 *Rule originally codified as part of 15A NCAC 02H .0610;*  
18 *Eff. July 1, 1998;*  
19 *Amended Eff. May 1, 2014; April 1, ~~2001~~, 2001;*  
20 *Readopted Eff. \_\_\_\_\_.*  
21  
22

1 15A NCAC 02Q .0704 is proposed for reoption with substantive changes as follows:

2

3 **15A NCAC 02Q .0704 NEW FACILITIES**

4 (a) This Rule applies only to new facilities.

5 (b) The owner or operator of a facility required to have a permit ~~because of applicability of~~ pursuant to 15A NCAC  
6 02Q .0300 or .0500 and is subject to a Section in 15A NCAC 02D, other than 15A NCAC 02D .1100, are is required  
7 to receive a permit to emit toxic air pollutants before beginning construction, and shall comply with the permit when  
8 beginning operation. This ~~Paragraph Rule~~ does not apply to facilities whose emissions of toxic air pollutants result  
9 only from sources exempted under ~~Rule .0102 of this Subchapter~~ 15A NCAC 02Q .0102.

10 (c) The owner or operator of the facility shall submit a permit application to comply with 15A NCAC 02D .1100 if  
11 emissions of any toxic air ~~pollutant~~ pollutant, excluding sources exempt from evaluation in 15A NCAC 02Q .0702,  
12 exceed the levels contained in Rule .0711 of this Section. 15A NCAC 02Q .0711. Sources meeting the exemption in  
13 15A NCAC 02Q .0702(a)(27) shall be reviewed by the Division pursuant to G.S. 143-215.107(a)(5)b.

14 (d) The permit application filed pursuant to this Rule shall include an evaluation for all toxic air ~~pollutants listed in~~  
15 15A NCAC 02D .1104, pollutants. All sources at the facility, excluding sources exempt from evaluation in ~~Rule .0702~~  
16 of this Section, 15A NCAC 0702, emitting these toxic air pollutants shall be included in the evaluation.

17

18 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.107; 143-215.108; 143B-282;*

19 *Rule originally codified as part of 15A NCAC 2H .0610;*

20 *Eff. July 1, 1998;*

21 *Amended Eff. May 1, ~~2014, 2014~~;*

22 *Repealed Eff. \_\_\_\_\_.*

23

24

1 15A NCAC 02Q .0706 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02Q .0706 MODIFICATIONS**

4 (a) The owner or operator shall comply with Paragraphs (b) and (c) of this Rule for a modification of any facility  
5 required to have a permit because of applicability of that is subject to a Section in 15A NCAC 02D, other than 15A  
6 NCAC 02D ~~.1100~~ .1100 and that:

7 (1) requires a permit pursuant to 15A NCAC 02Q .0300; or

8 (2) occurs at a facility with a permit pursuant to 15A NCAC 02Q .0500 and emits a pollutant that is part  
9 of the facility's previous modeling demonstration conducted pursuant to 02D .1104 and 02Q .0709,  
10 if that modification is not exempted pursuant to 15A NCAC 02Q .0702.

11 This ~~Paragraph~~ Rule does not apply to facilities whose emissions of toxic air pollutants result only from insignificant  
12 activities, as defined in ~~Rule .0103(20) of this Subchapter,~~ 15A NCAC 02Q .0103(20), or result only from sources  
13 exempted under Rule .0102 of this Subchapter. 15A NCAC 02Q .0102.

14 (b) The owner or operator of the facility shall submit a permit application to comply with 15A NCAC 02D .1100 if  
15 the modification results in:

16 (1) a net increase in emissions or ambient concentration as previously determined pursuant to 15A  
17 NCAC 02D 1106 and 02Q .0709 of any toxic air pollutant that the facility was emitting before the  
18 modification; or

19 (2) emissions of any toxic air pollutant that the facility was not emitting before the modification if such  
20 emissions exceed the levels contained in ~~Rule .0711 of this Section,~~ 15A NCAC 02Q .0711.

21 (c) The permit application filed pursuant to this Rule shall include an evaluation for all toxic air pollutants identified  
22 pursuant to Paragraph (b) of this Rule, covered under 15A NCAC 02D .1104 for which there is:

23 (1) ~~a net increase in emissions of any toxic air pollutant that the facility was emitting before the~~  
24 ~~modification; and~~

25 (2) ~~emission of any toxic air pollutant that the facility was not emitting before the modification if such~~  
26 ~~emissions exceed the levels contained in Rule .0711 of this Section.~~

27 All sources at the facility, excluding sources exempt from evaluation in ~~Rule .0702 of this Section,~~ 15A NCAC 02Q  
28 .0702, emitting these toxic air pollutants shall be included in the evaluation. Sources meeting the exemption in 15A  
29 NCAC 02Q .0702(a)(27) shall be reviewed by the Division pursuant to G.S. 143-215.107(a)(5)b.

30 (d) If a source is included in an air toxic evaluation, but is not the source that is being added or modified at the facility,  
31 and if the emissions from this source must be reduced in order for the facility to comply with the rules in this Section  
32 and 15A NCAC 02D .1100, then the emissions from this source shall be reduced by the time that the new or modified  
33 source begins operating such that the facility shall be in compliance with the rules in this Section and 15A NCAC 02D  
34 .1100.

35  
36 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107; 143-215.108; 143B-282;

37 Rule originally codified as part of 15A NCAC 2H .0610;



1  
2  
3  
4  
5

*Eff. July 1, 1998;*  
*Amended Eff. May 1, 2014; July 10, 2010; December 1, 2005; April 1, ~~2005~~, 2005;*  
*Readopted Eff. \_\_\_\_\_.*

1 15A NCAC 02Q .0707 is proposed for readoption without substantial changes as follows:

2

3 **15A NCAC 02Q .0707 PREVIOUSLY PERMITTED FACILITIES**

4 Any facility with a permit that contains a restriction based on the evaluation of a source exempted under ~~Rule 0702~~  
5 ~~of this Section~~ 15A NCAC 02Q .0702 may request a permit modification to adjust the restriction by removing from  
6 consideration the portion of emissions resulting from the exempt source unless the Director determines that the  
7 removal of the exempt source will result in an acceptable ambient level in 15A NCAC 2D .1104 being exceeded. The  
8 Director shall modify the permit to remove the applicability of the air toxic rules to the exempt source. No fee shall  
9 be charged solely for such permit modification.

10

11 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.108; 143B-282; S.L. 1989, c. 168, s. 45;

12 Rule originally codified as part of 15A NCAC 2H .0610;

13 Eff. July 1, ~~1998~~ 1998;

14 Readopted Eff. \_\_\_\_\_.

15

16

17

1 15A NCAC 02Q .0708 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02Q .0708 COMPLIANCE SCHEDULE FOR PREVIOUSLY UNKNOWN TOXIC AIR**  
4 **POLLUTANT EMISSIONS**

5 (a) The owner or operator of a facility permitted to emit toxic air pollutants shall submit a permit application within  
6 six months after the owner or operator learns of an emission of a previously unknown toxic air pollutant from a  
7 ~~permitted~~ source at the facility that would have been included in the permit when it was issued. The application shall  
8 include the information required by Paragraph (b) of this Rule.

9 (b) When an application to revise a permit is submitted under this Rule, the owner or operator shall in addition to the  
10 application, submit to the Director:

11 (1) an evaluation for the pollutant according to this Section and 15 NCAC ~~2D02D~~ .1100 that  
12 demonstrates compliance with the acceptable ambient level in 15A NCAC ~~2D02D~~ .1104; or

13 (2) a compliance schedule containing the information required under Paragraph (c) of this Rule for the  
14 proposed modifications to the facility required to comply with the acceptable ambient level  
15 according to this Section and Section 15A NCAC ~~2Q02Q~~ .1100.

16 (c) The compliance schedule required under Subparagraph (b)(2) of this Rule shall contain the following increments  
17 of progress as applicable:

18 (1) a date by which contracts for emission control and process equipment shall be awarded or orders  
19 shall be issued for the purchase of component parts;

20 (2) a date by which on-site construction or installation of the emission control and process equipment  
21 shall begin;

22 (3) a date by which on-site construction or installation of the emission control and process equipment  
23 shall be completed; and

24 (4) the date by which final compliance shall be achieved.

25 (d) Final compliance shall be achieved no later than:

26 (1) six months after the permit modification or renewal is issued if construction or installation of  
27 emission control or process equipment is not required;

28 (2) one year after the permit modification or renewal is issued if construction or installation of emission  
29 control or process equipment is required; or

30 (3) the time that is normally required to construct a stack or install other dispersion enhancement  
31 modifications but not more than one year after the permit modification or renewal is issued.

32 (e) The owner or operator shall certify to the Director within 10 days after each applicable deadline for each increment  
33 of progress required under Paragraph (c) of this Rule whether the required increment of progress has been met.

34 *History Note:* Authority G.S. 143-215.3(a)(1); 43-215.107(a)(3),(5); 143B-282; S.L. 1989, c. 168, s. 45;

36 *Eff. July 1, ~~1998~~ 1998;*

37 *Readopted Eff.*

1 15A NCAC 02Q .0709 is proposed for readoption with substantive changes as follows:

2  
3 **15A NCAC 02Q .0709 DEMONSTRATIONS**

4 (a) Demonstrations. The owner or operator of a source who is applying for a permit or permit modification to emit  
5 toxic air pollutants shall:

6 (1) demonstrate to the satisfaction of the Director through dispersion modeling conducted pursuant to  
7 15A NCAC 02D .1106 that the emissions of toxic air pollutants from the facility ~~will~~ shall not cause  
8 any acceptable ambient level listed in 15A NCAC 02D .1104 to be exceeded beyond the facility's  
9 premises (adjacent property boundary); with such exceptions as may be allowed under 15A NCAC  
10 2Q .0700; or

11 (2) demonstrate to the satisfaction of the Commission or its delegate that the ambient concentration  
12 beyond the premises (adjacent property boundary) for the subject toxic air pollutant shall not  
13 adversely affect human health (*e.g.*, a risk assessment specific to the facility) though the  
14 concentration is higher than the acceptable ambient level in 15A NCAC 02D .1104 by providing  
15 one of the following demonstrations:

16 (A) the area where the ambient concentrations are expected to exceed the acceptable ambient  
17 levels in 15A NCAC 02D .1104 is not inhabitable or occupied for the duration of the  
18 averaging time of the pollutant of concern; or

19 (B) new toxicological data that show that the acceptable ambient level in 15A NCAC 02D  
20 .1104 for the pollutant of concern is too low and the facility's ambient impact is below the  
21 level indicated by the new toxicological data.

22 (b) Technical Infeasibility and Economic Hardship. This Paragraph shall not apply to any incinerator covered ~~under~~  
23 pursuant to 15A NCAC 02D .1200. The owner or operator of any source constructed before May 1, 1990, ~~or a~~  
24 ~~perchloroethylene dry cleaning facility subject to a GACT standard under 40 CFR 63.320 through 63.325,~~ or a  
25 combustion source as defined in ~~Rule .0703 of this Section~~ 15A NCAC 02Q .0703 permitted before July 10, 2010,  
26 who cannot supply a demonstration described in Paragraph (a) of this Rule shall:

27 (1) demonstrate to the satisfaction of the Commission or its delegate that complying with the guidelines  
28 in 15A NCAC 02D .1104 is technically infeasible, as the technology necessary to reduce emissions  
29 to a level to prevent the acceptable ambient levels in 15A NCAC 02D .1104 from being exceeded  
30 does not exist; or

31 (2) demonstrate to the satisfaction of the Commission or its delegate that complying with the guidelines  
32 in 15A NCAC 02D .1104 would result in serious economic hardship. In deciding if a serious  
33 economic hardship exists, the Commission or its delegate shall consider market impact; impacts on  
34 local, regional and state economy; risk of closure; capital cost of compliance; annual incremental  
35 compliance cost; and environmental and health impacts.

36 If the owner or operator makes a demonstration to the satisfaction of the Commission or its delegate pursuant to  
37 Subparagraphs (1) or (2) of this Paragraph, the Director shall require the owner or operator of the source to apply

1 maximum feasible control. Maximum feasible control shall be in place and operating within three years from the date  
2 that the permit is issued for the maximum feasible control.

3 (c) Pollution Prevention Plan. The owner or operator of any facility using the provisions of Part (a)(2)(A) or Paragraph  
4 (b) of this Rule shall develop and implement a pollution prevention plan consisting of the following elements:

- 5 (1) statement of corporate and facility commitment to pollution prevention;
- 6 (2) identification of current and past pollution prevention activities;
- 7 (3) timeline and strategy for implementation;
- 8 (4) description of ongoing and planned employee education efforts; and
- 9 (5) identification of internal pollution prevention goal selected by the facility and expressed in either  
10 qualitative or quantitative terms.

11 The facility shall submit the pollution plan along with the permit application. The pollution prevention plan shall be  
12 maintained on site. A progress report on implementation of the plan shall be prepared by the facility annually and be  
13 made available to Division personnel for review upon request.

14 (d) Modeling Demonstration. If the owner or operator of a facility demonstrates by modeling that no toxic air  
15 pollutant emitted from the facility exceeds the acceptable ambient level values set out in 15A NCAC 02D .1104  
16 beyond the facility's premises, further modeling demonstration is not required with the permit application. However,  
17 the Commission may still require more stringent emission levels according to its analysis under 15A NCAC 02D  
18 .1107.

19 (e) Change in Acceptable Ambient Level. When an acceptable ambient level for a toxic air pollutant in 15A NCAC  
20 02D .1104 is changed, any condition that has previously been put in a permit to protect the previous acceptable ambient  
21 level for that toxic air pollutant shall not be changed until:

- 22 (1) The permit is renewed, at which time the owner or operator of the facility shall submit an air toxic  
23 evaluation, excluding sources exempt from evaluation in ~~Rule .0702 of this Section, 15A NCAC~~  
24 02Q .0702, showing that the new acceptable ambient level will not be exceeded. If additional time  
25 is needed to bring the facility into compliance with the new acceptable ambient level, the owner or  
26 operator shall negotiate a compliance schedule with the Director. The compliance schedule shall be  
27 written into the facility's permit and final compliance shall not exceed two years from the effective  
28 date of the change in the acceptable ambient level; or
- 29 (2) The owner or operator of the facility requests that the condition be changed and submits along with  
30 that request an air toxic evaluation, excluding sources exempt from evaluation in ~~Rule .0702 of this~~  
31 Section, 15A NCAC 02Q .0702, showing that the new acceptable ambient level shall not be  
32 exceeded.

33  
34 *History Note:* Authority G.S. 143-215.3(a)(1); 143-215.107; 143-215.108; 143B-282;  
35 Rule originally codified as part of 15A NCAC 2H .0610;  
36 Eff. July 1, 1998;  
37 Amended Eff. May 1, 2014; July 10, 2010; February 1, ~~2005-2005~~;



1 15A NCAC 02Q .0710 is proposed for readoption without substantive changes as follows:

2  
3 **15A NCAC 02Q .0710 PUBLIC NOTICE AND OPPORTUNITY FOR PUBLIC HEARING**

4 (a) If the owner or operator of a facility chooses to make a demonstration pursuant to ~~Rule .0709 (a)(2) or (b) of this~~  
5 ~~Section, 15A NCAC 02Q .0709(a)(2) or (b),~~ the Commission or its delegate shall approve or disapprove the permit  
6 after a public notice with an opportunity for a public hearing.

7 (b) The public notice shall be given by publication in a newspaper of general circulation in the area where the facility  
8 is located and shall be mailed to persons who are on the Division's mailing list for air quality permit notices.

9 (c) The public notice shall identify:

- 10 (1) the affected facility;
- 11 (2) the name and address of the permittee;
- 12 (3) the name and address of the person to whom to send comments and requests for public hearing;
- 13 (4) the name, address, and telephone number of a Divisional staff person from whom interested persons  
14 may obtain additional information, including copies of the draft permit, the application, compliance  
15 plan, pollution prevention plan, monitoring and compliance reports, all other relevant supporting  
16 materials, and all other materials available to the Division that are relevant to the permit decision;
- 17 (5) the activity or activities involved in the permit action;
- 18 (6) any emissions change involved in any permit modification;
- 19 (7) a brief description of the public comment procedures;
- 20 (8) the procedures to follow to request a public hearing unless a public hearing has already been  
21 scheduled; and
- 22 (9) the time and place of any hearing that has already been scheduled.

23 (d) The notice shall allow at least 30 days for public comments.

24 (e) If the Director determines that significant public interest exists or that the public interest will be served, the  
25 Director shall require a ~~pubic-public~~ hearing to be held on a draft permit. Notice of a public hearing shall be given at  
26 least 30 days before the public hearing.

27 (f) The Director shall make available for public inspection in at least one location in the region affected, the  
28 information submitted by the permit applicant and the ~~Division's~~Division's analysis of that application.

29 (g) Any persons requesting copies of material identified in Subparagraph ~~(b)(4)(c)(4)~~(c)(4) of this Rule shall pay ten cents  
30 (\$0.10) a page for each page copied. Confidential material shall be handled in accordance with ~~Rule .0107 of this~~  
31 ~~Subchapter, 15A NCAC 02Q .0107.~~

32  
33 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.108; 143B-282; S.L. 1989, c. 168, s. 45;*

34 *Rule originally codified as part of 15A NCAC 2H .0610;*

35 *Eff. July 1, 1998. 1998;*

36 *Readopted Eff. \_\_\_\_\_.*

1 15A NCAC 02Q .0711 is proposed for readoption with substantive changes as follows:

2  
3  
4  
5  
6  
7  
8

**15A NCAC 02Q .0711 EMISSION RATES REQUIRING A PERMIT**

(a) A permit to emit toxic air pollutants shall be required for any ~~facility~~ facility, excluding sources exempt from evaluation in 15A NCAC 02Q .0702, where one or more emission release points are obstructed or non-vertically oriented whose actual rate of emissions by pollutant from all sources are greater than any one of the following toxic air pollutant permitting emissions rates:

<u>Obstructed or Non-Vertical Oriented Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
acetaldehyde (75-07-0)				6.8
acetic acid (64-19-7)				0.96
acrolein (107-02-8)				0.02
acrylonitrile (107-13-1)		0.4	0.22	
ammonia (7664-41-7)				0.68
aniline (62-53-3)			0.25	
arsenic and inorganic arsenic compounds	0.053			
asbestos (1332-21-4)	5.7 X 10 <sup>-3</sup>			
aziridine (151-56-4)		0.13		
benzene (71-43-2)	8.1			
benzidine and salts (92-87-5)	0.0010			
benzo(a)pyrene (50-32-8)	2.2			
benzyl chloride (100-44-7)			0.13	
beryllium (7440-41-7)	0.28			
beryllium chloride (7787-47-5)	0.28			
beryllium fluoride (7787-49-7)	0.28			
beryllium nitrate (13597-99-4)	0.28			
bioavailable chromate pigments, as chromium (VI) equivalent	0.0056			
bis-chloromethyl ether (542-88-1)	0.025			
bromine (7726-95-6)				0.052
1,3-butadiene (106-99-0)	.11			
cadmium (7440-43-9)	0.37			



<u>Obstructed or Non-Vertical Oriented Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
cadmium acetate (543-90-8)	0.37			
cadmium bromide (7789-42-6)	0.37			
carbon disulfide (75-15-0)		3.9		
carbon tetrachloride (56-23-5)	460			
chlorine (7782-50-5)		0.79		0.23
chlorobenzene (108-90-7)		46		
chloroform (67-66-3)	290			
chloroprene (126-99-8)		9.2	0.89	
cresol (1319-77-3)			0.56	
p-dichlorobenzene (106-46-7)				16.8
<del>dichlorodifluoromethane (75-71-8)</del>		<del>5200</del>		
<del>dichlorofluoromethane (75-43-4)</del>		<del>10</del>		
di(2-ethylhexyl)phthalate (117-81-7)		0.63		
dimethyl sulfate (77-78-1)		0.063		
1,4-dioxane (123-91-1)		12		
epichlorohydrin (106-89-8)	5600			
ethyl acetate (141-78-6)			36	
ethylenediamine (107-15-3)		6.3	0.64	
ethylene dibromide (106-93-4)	27			
ethylene dichloride (107-06-2)	260			
ethylene glycol monoethyl ether (110-80-5)		2.5	0.48	
ethylene oxide (75-21-8)	1.8			
ethyl mercaptan (75-08-1)			0.025	
fluorides		0.34	0.064	
formaldehyde (50-00-0)				0.04
hexachlorocyclopentadiene (77-47-4)		0.013	0.0025	
hexachlorodibenzo-p-dioxin (57653-85-7)	0.0051			
n-hexane (110-54-3)		23		
hexane isomers except n-hexane				92
hydrazine (302-01-2)		0.013		
hydrogen chloride (7647-01-0)				0.18

<u>Obstructed or Non-Vertical Oriented Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
hydrogen cyanide (74-90-8)		2.9	.028	
hydrogen fluoride (7664-39-3)		.63		.064
hydrogen sulfide (7783-06-4)		1.7		
maleic anhydride (108-31-6)		.25	.025	
manganese and compounds		.63		
manganese cyclopentadienyl tricarbonyl (12079-65-1)		.013		
manganese tetroxide (1317-35-7)		.13		
mercury, alkyl		.0013		
mercury, aryl and inorganic compounds		.013		
mercury, vapor (7439-97-6)		.013		
methyl chloroform (71-55-6)		250		.64
methylene chloride (75-09-2)	.1600		.39	
methyl ethyl ketone (78-93-3)		.78		22.4
methyl isobutyl ketone (108-10-1)		.52		.76
methyl mercaptan (74-93-1)			.013	
nickel carbonyl (13463-39-3)		.013		
nickel metal (7440-02-0)		.13		
nickel, soluble compounds, as nickel		.013		
nickel subsulfide (12035-72-2)	.014			
nitric acid (7697-37-2)				.0256
nitrobenzene (98-95-3)		1.3	.13	
n-nitrosodimethylamine (62-75-9)	.34			
non-specific chromium (VI) compounds, as chromium (VI) equivalent	.0056			
pentachlorophenol (87-86-5)		.063	.0064	
perchloroethylene (127-18-4)	.13000			
phenol (108-95-2)			.24	
phosgene (75-44-5)		.052		
phosphine (7803-51-2)				.032
polychlorinated biphenyls (1336-36-3)	.56			

<u>Obstructed or Non-Vertical Oriented Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
.soluble chromate compounds, as chromium (VI) equivalent		.0013		
.styrene (100-42-5)			.27	
.sulfuric acid (7664-93-9)		.025	.0025	
.tetrachlorodibenzo-p-dioxin (1746- 01-6)	.00020			
<del>1,1,1,2 tetrachloro 2,2, difluoroethane (76-11-9)</del>		<del>1100</del>		
<del>1,1,2,2 tetrachloro 1,2 difluoroethane (76-12-0)</del>		<del>1100</del>		
.1,1,2-tetrachloroethane (79-34-5)	.430			
.toluene (108-88-3)		.98		.14.4
.toluene diisocyanate,2,4-(584-84-9) and 2,6- (91-08-7) isomers		.0003		
.trichloroethylene (79-01-6)	.4000			
<del>trichlorofluoromethane (75-69-4)</del>			<del>.140</del>	
<del>1,1,2 trichloro 1,2,2 trifluoroethane (76-13-1)</del>				<del>.240</del>
.vinyl chloride (75-01-4)	.26			
.vinylidene chloride (75-35-4)		.25		
.xylene (1330-20-7)		.57		.16.4

1  
2 (b) A permit to emit toxic air pollutants shall be required for any facility where all emission release points are  
3 unobstructed and vertically oriented whose actual rate of emissions from all sources are greater than any one of the  
4 following toxic air pollutant permitting emissions rates:  
5

<u>Unobstructed Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
.acetaldehyde (75-07-0)				28.43

<u>Unobstructed Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
acetic acid (64-19-7)				3.90
acrolein (107-02-8)				0.08
acrylonitrile (107-13-1)		1.3	1.05	
ammonia (7664-41-7)				2.84
aniline (62-53-3)			1.05	
arsenic and inorganic arsenic compounds	0.194			
asbestos (1332-21-4)	7.748 x 10 <sup>-3</sup>			
aziridine (151-56-4)		0.3		
benzene (71-43-2)	11.069			
benzidine and salts (92-87-5)	1.384 x 10 <sup>-3</sup>			
benzo(a)pyrene (50-32-8)	3.044			
benzyl chloride (100-44-7)			0.53	
beryllium (7440-41-7)	0.378			
beryllium chloride (7787-47-5)	0.378			
beryllium fluoride (7787-49-7)	0.378			
beryllium nitrate (13597-99-4)	0.378			
bioavailable chromate pigments, as chromium (VI) equivalent	0.008			
bis-chloromethyl ether (542-88-1)	0.034			
bromine (7726-95-6)				0.21
1,3-butadiene (106-99-0)	40.585			
cadmium (7440-43-9)	0.507			
cadmium acetate (543-90-8)	0.507			
cadmium bromide (7789-42-6)	0.507			
carbon disulfide (75-15-0)		7.8		
carbon tetrachloride (56-23-5)	618.006			
chlorine (7782-50-5)		1.6		0.95
chlorobenzene (108-90-7)		92.7		
chloroform (67-66-3)	396.631			
chloroprene (126-99-8)		18.5	3.69	
cresol (1319-77-3)			2.32	

<u>Unobstructed Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
p-dichlorobenzene (106-46-7)				.69.50
dichlorodifluoromethane (75-71-8)		10445.4		
dichlorofluoromethane (75-43-4)		21.1		
di(2-ethylhexyl)phthalate (117-81-7)		1.3		
dimethyl sulfate (77-78-1)		0.1		
1,4-dioxane (123-91-1)		23.6		
epichlorohydrin (106-89-8)	.7655.891			
ethyl acetate (141-78-6)			.147.41	
ethylenediamine (107-15-3)		12.6	2.63	
ethylene dibromide (106-93-4)	36.896			
ethylene dichloride (107-06-2)	350.511			
ethylene glycol monoethyl ether (110-80-5)		5.1	2.00	
ethylene oxide (75-21-8)	2.490			
ethyl mercaptan (75-08-1)			.011	
fluorides		.07	.026	
formaldehyde (50-00-0)				.016
hexachlorocyclopentadiene (77-47-4)		$2.5 \times 10^{-2}$	.001	
hexachlorodibenzo-p-dioxin (57653-85-7)	.0007			
n-hexane (110-54-3)		46.3		
hexane isomers except n-hexane				.379.07
hydrazine (302-01-2)		$2.5 \times 10^{-2}$		
hydrogen chloride (7647-01-0)				.074
hydrogen cyanide (74-90-8)		5.9	.116	
hydrogen fluoride (7664-39-3)		1.3		.026
hydrogen sulfide (7783-06-4)		5.1		
maleic anhydride (108-31-6)		0.5	.011	
manganese and compounds		1.3		
manganese cyclopentadienyl tricarbonyl (12079-65-1)		$2.5 \times 10^{-2}$		
manganese tetroxide (1317-35-7)		0.3		
mercury, alkyl		$2.5 \times 10^{-3}$		

<u>Unobstructed Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
mercury, aryl and inorganic compounds		2.5 x 10 <sup>-2</sup>		
mercury, vapor (7439-97-6)		2.5 x 10 <sup>-2</sup>		
methyl chloroform (71-55-6)		505.4		257.98
methylene chloride (75-09-2)	2213.752		1.79	
methyl ethyl ketone (78-93-3)		155.8		93.19
methyl isobutyl ketone (108-10-1)		107.8		31.59
methyl mercaptan (74-93-1)			0.05	
nickel carbonyl (13463-39-3)		2.5 x 10 <sup>-2</sup>		
nickel metal (7440-02-0)		0.3		
nickel, soluble compounds, as nickel		2.5 x 10 <sup>-2</sup>		
nickel subsulfide (12035-72-2)	0.194			
nitric acid (7697-37-2)				1.05
nitrobenzene (98-95-3)		2.5	0.53	
n-nitrosodimethylamine (62-75-9)	4.612			
non-specific chromium (VI) compounds, as chromium (VI) equivalent	0.008			
pentachlorophenol (87-86-5)		0.1	0.03	
perchloroethylene (127-18-4)	17525.534			
phenol (108-95-2)			1.00	
phosgene (75-44-5)		0.1		
phosphine (7803-51-2)				0.14
polychlorinated biphenyls (1336-36-3)	7.656			
soluble chromate compounds, as chromium (VI) equivalent		2.6 x 10 <sup>-2</sup>		
styrene (100-42-5)			11.16	
sulfuric acid (7664-93-9)		0.5	0.11	
tetrachlorodibenzo-p-dioxin (1746-01-6)	2.767 x 10 <sup>-4</sup>			
<del>1,1,1,2 tetrachloro 2,2, difluoroethane (76-11-9)</del>		<del>2190.2</del>		
<del>1,1,2,2 tetrachloro 1,2 difluoroethane (76-12-0)</del>		<del>2190.2</del>		

<u>Unobstructed Toxic Air Pollutant Permitting Emission Rates (TPER)</u>				
Pollutant (CAS Number)	Carcinogens	Chronic Toxicants	Acute Systemic Toxicants	Acute Irritants
	lb/yr	lb/day	lb/hr	lb/hr
.1,1,2,2-tetrachloroethane (79-34-5)	.581.110			
.toluene (108-88-3)		.197.96		.58.97
.toluene diisocyanate,2,4-(584-84-9) and 2,6- (91-08-7) isomers		8.4 x 10 <sup>-3</sup>		
.trichloroethylene (79-01-6)	.5442.140			
<del>.trichlorofluoromethane (75-69-4)</del>			<del>.589.66</del>	
<del>.1,1,2 trichloro 1,2,2 trifluoroethane (76-13-1)</del>				<del>.1000.32</del>
.vinyl chloride (75-01-4)	.35.051			
.vinylidene chloride (75-35-4)		5.1		
.xylene (1330-20-7)		.113.7		.68.44

1  
2 (c) For the following pollutants, the highest emissions occurring for any 15-minute period shall be multiplied by four  
3 and the product shall be compared to the value in Paragraph (a) or (b) as applicable. These pollutants are:

- 4 (1) acetaldehyde (75-07-0);  
5 (2) acetic acid (64-19-7);  
6 (3) acrolein (107-02-8);  
7 (4) ammonia (7664-41-7);  
8 (5) bromine (7726-95-6);  
9 (6) chlorine (7782-50-5);  
10 (7) formaldehyde (50-00-0);  
11 (8) hydrogen chloride (7647-01-0);  
12 (9) hydrogen fluoride (7664-39-3); and  
13 (10) nitric acid (7697-37-2).

14  
15 *History Note: Authority G.S. 143-215.3(a)(1); 143-215-107; 143-215.108; 143B-282;*  
16 *Rule originally codified as part of 15A NCAC 02H .0610;*  
17 *Eff. July 1, 1998;*  
18 *Amended Eff. May 1, 2015; May 1, 2014; January 1, 2010; June 1, 2008; April 1, 2005; February*  
19 *1, 2005; April 1, ~~2001-2001~~;*  
20 *Readopted Eff.*  
21

1 15A NCAC 02Q .0712 is proposed for readoption without substantive changes as follows:

2

3 **15A NCAC 02Q .0712 CALLS BY THE DIRECTOR**

4 Notwithstanding any other provision of this Section or 15A NCAC ~~2D .1104, 02D .1100~~, upon a written finding that  
5 a source or facility emitting toxic air pollutants presents an unacceptable risk to human health based on the acceptable  
6 ambient levels in 15A NCAC ~~2D02D~~ .1104 or epidemiology studies, the Director may require the owner or operator  
7 of the source or facility to submit a permit application to comply with 15A NCAC ~~2D02D~~ .1100 for any or all of the  
8 toxic air pollutants emitted from the facility.

9

10 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.108; 143B-282; S.L. 1989, c. 168, s. 45;*

11 *Rule originally codified as part of 15A NCAC 2H .0610;*

12 *Eff. July 1, ~~1998~~ 1998;*

13 *Readopted Eff. \_\_\_\_\_.*

14

15



1 15A NCAC 02Q .0713 is proposed for readoption as a repeal as follows:

2

3 **15A NCAC 02Q .0713 POLLUTANTS WITH OTHERWISE APPLICABLE FEDERAL STANDARDS OR**  
4 **REQUIREMENTS**

5 ~~(a) This Rule applies to the establishment of emission limitations or any other requirements pursuant to the~~  
6 ~~requirements of this Section or 15A NCAC 2D .1100 for which a standard or requirement has been promulgated under~~  
7 ~~Section 112 of the federal Clean Air Act including those contained in 15A NCAC 2D .1110 and .1111.~~

8 ~~(b) For each facility subject to emission standards or requirements under Section 112 of the federal Clean Air Act,~~  
9 ~~permits issued or revised according to Section .0500 of this Subchapter shall contain specific conditions that:~~

10 ~~(1) reflect applicability criteria no less stringent than those in the otherwise applicable federal standards~~  
11 ~~or requirements;~~

12 ~~(2) require levels of control for each affected facility and source no less stringent than those contained~~  
13 ~~in the otherwise applicable federal standards or requirements;~~

14 ~~(3) require compliance and enforcement measures for each facility and source no less stringent than~~  
15 ~~those in the otherwise applicable federal standards or requirements;~~

16 ~~(4) express levels of control, compliance, and enforcement measures in the same form and units of~~  
17 ~~measure as the otherwise applicable federal standards or requirements; and~~

18 ~~(5) assure compliance by each affected facility no later than would be required by the otherwise~~  
19 ~~applicable federal standard or requirement.~~

20

21 *History Note: Authority G.S. 143-215.3(a)(1); 143-215.108; 143B-282; S.L. 1989, c. 168, s. 45;*

22 *Eff. July 1, ~~1998~~, 1998;*

23 *Repealed Eff.*

24

25